LMV981-N Single / LMV982 Dual 1.8V, RRIO Operational Amplifiers with Shutdown

Check for Samples: LMV981-N, LMV982-N

FEATURES

- **(Typical 1.8V Supply Values; Unless Otherwise Noted)**
- **Ensured 1.8V, 2.7V and 5V Specifications**
- **Output Swing**
  - **w/600Ω load 80mV from Rail**
  - **w/2kΩ load 30mV from Rail**
- **V_{CM} 200mV Beyond Rails**
- **Supply Current (Per Channel) 100µA**
- **Gain Bandwidth Product 1.4MHz**
- **Maximum V_{OS} 4.0mV**
- **Gain w/600Ω Load 101dB**
- **Ultra Tiny Package DSBGA 1.0mm x 1.5mm**
- **Turn-On Time from Shutdown 19µs**
- **Temperature Range −40°C to 125°C**

APPLICATIONS

- **Industrial and Automotive**
- **Consumer Communication**
- **Consumer Computing**
- **PDAs**
- **Portable audio**
- **Portable/Battery-Powered Electronic Equipment**
- **Supply Current Monitoring**
- **Battery Monitoring**

DESCRIPTION


LMV981-N/LMV982 are low voltage, low power operational amplifiers. LMV981-N/LMV982 operate from +1.8V to +5.0V supply voltages and have rail-to-rail input and output. LMV981-N/LMV982 input common mode voltage extends 200mV beyond the supplies which enables user enhanced functionality beyond the supply voltage range. The output can swing rail-to-rail unloaded and within 105mV from the rail with 600Ω load at 1.8V supply. LMV981-N/LMV982 are optimized to work at 1.8V which make them ideal for portable two-cell battery powered systems and single cell Li-Ion systems.

LMV981-N/LMV982 offer a shutdown pin that can be used to disable the device and reduce the supply current. The device is in shutdown when the SHDN-pin = low. The output will be high impedance in shutdown.

LMV981-N/LMV982 exhibit excellent speed-power ratio, achieving 1.4MHz gain bandwidth product at 1.8V supply voltage with very low supply current. LMV981-N/LMV982 are capable of driving a 600Ω load and up to 1000pF capacitive load with minimal ringing. LMV981-N/LMV982 have a high DC gain of 101dB, making them suitable for low frequency applications.

LMV981-N is offered in space saving 6-Bump DSBGA, SC70-6 and SOT-23-6 packages. The 6-Bump DSBGA package has only a 1.006mm x 1.514mm x 0.945mm footprint. LMV982 is offered in space saving VSSOP-10 package. These small packages are ideal solutions for area constrained PC boards and portable electronics such as cellular phones and PDAs.

Typical Application



$$V_{OUT} = \frac{R_{SENSE} \bullet R_3}{R_1} \bullet I_{Charge} = 1\Omega \bullet I_{Charge}$$

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2001–2013, Texas Instruments Incorporated

These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

Absolute Maximum Ratings (1)(2)

ESD Tolerance (3)	
Machine Model	200V
Human Body Model	2000V
Supply Voltage (V^+–V^-)	5.5V
Differential Input Voltage	± Supply Voltage
Voltage at Input/Output Pins	V^++0.3V, V^--0.3V
Storage Temperature Range	−65°C to 150°C
Junction Temperature (4)	150°C
For soldering specifications:	
http://www.ti.com/lit/SNOA549f	

(1) Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but specific performance is not ensured. For ensured specifications and the test conditions, see the Electrical Characteristics.
(2) If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/ Distributors for availability and specifications.
(3) Human Body Model, applicable std. MIL-STD-883, Method 3015.7. Machine Model, applicable std. JESD22-A115-A (ESD MM std. of JEDEC) Field-Induced Charge-Device Model, applicable std. JESD22-C101-C (ESD FICDM std. of JEDEC).
(4) The maximum power dissipation is a function of $T_{J(MAX)}$, θ_{JA}, and T_A. The maximum allowable power dissipation at any ambient temperature is $P_D = (T_{J(MAX)}–T_A)/\theta_{JA}$. All numbers apply for packages soldered directly into a PC board.

Operating Ratings (1)

Supply Voltage Range	1.8V to 5.0V
Temperature Range	−40°C to 125°C
Thermal Resistance (θ_{JA})	
6-Bump DSBGA	286°C/W
SC70-6	414°C/W
SOT-23-6	265°C/W
VSSOP-10	235°C/W

(1) Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but specific performance is not ensured. For ensured specifications and the test conditions, see the Electrical Characteristics.

1.8V DC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 1.8V, V^- = 0V, $V_{CM} = V^+/2$, $V_O = V^+/2$, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions	Min (2)	Typ (3)	Max (2)	Units
V_{OS}	Input Offset Voltage	LMV981-N (Single)		1	4 **6**	mV
		LMV982 (Dual)		1	5.5 **7.5**	
TCV_{OS}	Input Offset Voltage Average Drift			5.5		µV/°C
I_B	Input Bias Current			15	35 **50**	nA

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.

Copyright © 2001–2013, Texas Instruments Incorporated

1.8V DC Electrical Characteristics (continued)

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 1.8V, V^- = 0V, V_{CM} = V^+/2, V_O = V^+/2, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions		Min (2)	Typ (3)	Max (2)	Units
I_{OS}	Input Offset Current				13	25 **40**	nA
I_S	Supply Current (per channel)				103	185 **205**	µA
		In Shutdown	LMV981-N (Single)		0.156	1 **2**	
			LMV982 (Dual)		0.178	3.5 **5**	
CMRR	Common Mode Rejection Ratio	LMV981-N, 0 ≤ V_{CM} ≤ 0.6V 1.4V ≤ V_{CM} ≤ 1.8V (4)		60 **55**	78		dB
		LMV982, 0 ≤ V_{CM} ≤ 0.6V 1.4V ≤ V_{CM} ≤ 1.8V (4)		55 **50**	76		
		−0.2V ≤ V_{CM} ≤ 0V 1.8V ≤ V_{CM} ≤ 2.0V		50	72		
PSRR	Power Supply Rejection Ratio	1.8V ≤ V^+ ≤ 5V		75 **70**	100		dB
CMVR	Input Common-Mode Voltage Range	For CMRR Range ≥ 50dB	T_A = 25°C	V^- −0.2	−0.2 to 2.1	V^+ +0.2	V
			T_A = −40°C to 85°C	V^-		V^+	
			T_A = 125°C	V^- +0.2		V^+ −0.2	
A_V	Large Signal Voltage Gain LMV981-N (Single)	R_L = 600Ω to 0.9V, V_O = 0.2V to 1.6V, V_{CM} = 0.5V		77 **73**	101		dB
		R_L = 2kΩ to 0.9V, V_O = 0.2V to 1.6V, V_{CM} = 0.5V		80 **75**	105		
	Large Signal Voltage Gain LMV982 (Dual)	R_L = 600Ω to 0.9V, V_O = 0.2V to 1.6V, V_{CM} = 0.5V		75 **72**	90		dB
		R_L = 2kΩ to 0.9V, V_O = 0.2V to 1.6V, V_{CM} = 0.5V		78 **75**	100		
V_O	Output Swing	R_L = 600Ω to 0.9V V_{IN} = ± 100mV		1.65 **1.63**	1.72		V
					0.077	0.105 **0.120**	
		R_L = 2kΩ to 0.9V V_{IN} = ± 100mV		1.75 **1.74**	1.77		
					0.024	0.035 **0.04**	
I_O	Output Short Circuit Current (5)	Sourcing, V_O = 0V V_{IN} = 100mV		4 **3.3**	8		mA
		Sinking, V_O = 1.8V V_{IN} = −100mV		7 **5**	9		
Ton	Turn-on Time from Shutdown				19		µs
V_{SHDN}	Turn-on Voltage to enable part				1.0		V
	Turn-off Voltage				0.55		

(4) For ensured temperature ranges, see Input Common-Mode Voltage Range specifications.
(5) Applies to both single-supply and split-supply operation. Continuous short circuit operation at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of 45mA over long term may adversely affect reliability.

Copyright © 2001–2013, Texas Instruments Incorporated

1.8V AC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 1.8V, V^- = 0V, $V_{CM} = V^+/2$, $V_O = V^+/2$, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions	Min (2)	Typ (3)	Max (2)	Units
SR	Slew Rate	See (4)		0.35		V/µs
GBW	Gain-Bandwidth Product			1.4		MHz
Φ_m	Phase Margin			67		deg
G_m	Gain Margin			7		dB
e_n	Input-Referred Voltage Noise	f = 10 kHz, V_{CM} = 0.5V		60		nV/√Hz
i_n	Input-Referred Current Noise	f = 10 kHz		0.08		pA/√Hz
THD	Total Harmonic Distortion	f = 1kHz, A_V = +1 R_L = 600Ω, V_{IN} = 1 V_{PP}		0.023		%
	Amp-to-Amp Isolation	See (5)		123		dB

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.
(4) Connected as voltage follower with input step from V^- to V^+. Number specified is the slower of the positive and negative slew rates.
(5) Input referred, R_L = 100kΩ connected to $V^+/2$. Each amp excited in turn with 1kHz to produce $V_O = 3V_{PP}$. (For Supply Voltages <3V, $V_O = V^+$).

2.7V DC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 2.7V, V^- = 0V, $V_{CM} = V^+/2$, $V_O = V^+/2$, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions		Min (2)	Typ (3)	Max (2)	Units
V_{OS}	Input Offset Voltage	LMV981-N (Single)			1	4 **6**	mV
		LMV982 (Dual)			1	6 **7.5**	mV
TCV_{OS}	Input Offset Voltage Average Drift				5.5		µV/°C
I_B	Input Bias Current				15	35 **50**	nA
I_{OS}	Input Offset Current				8	25 **40**	nA
I_S	Supply Current (per channel)				105	190 **210**	µA
		In Shutdown	LMV981-N (Single)		0.061	1 **2**	
			LMV982 (Dual)		0.101	3.5 **5**	

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.

Copyright © 2001–2013, Texas Instruments Incorporated

2.7V DC Electrical Characteristics (continued)

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 2.7V, V^- = 0V, V_{CM} = V^+/2, V_O = V^+/2, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions		Min (2)	Typ (3)	Max (2)	Units
CMRR	Common Mode Rejection Ratio	LMV981-N, 0 ≤ V_{CM} ≤ 1.5V 2.3V ≤ V_{CM} ≤ 2.7V (4)		60 **55**	81		dB
		LMV982, 0 ≤ V_{CM} ≤ 1.5V 2.3V ≤ V_{CM} ≤ 2.7V (4)		55 **50**	80		
		−0.2V ≤ V_{CM} ≤ 0V 2.7V ≤ V_{CM} ≤ 2.9V		50	74		
PSRR	Power Supply Rejection Ratio	1.8V ≤ V^+ ≤ 5V V_{CM} = 0.5V		75 **70**	100		dB
CMVR	Input Common-Mode Voltage Range	For CMRR Range ≥ 50dB	T_A = 25°C	V^- −0.2	−0.2 to 3.0	V^++0.2	V
			T_A = −40°C to 85°C	V^-		V^+	
			T_A = 125°C	V^- +0.2		V^+−0.2	
A_V	Large Signal Voltage Gain LMV981-N(Single)	R_L = 600Ω to 1.35V, V_O = 0.2V to 2.5V		87 **86**	104		dB
		R_L = 2kΩ to 1.35V, V_O = 0.2V to 2.5V		92 **91**	110		
	Large Signal Voltage Gain LMV982 (Dual)	R_L = 600Ω to 1.35V, V_O = 0.2V to 2.5V		78 **75**	90		
		R_L = 2kΩ to 1.35V, V_O = 0.2V to 2.5V		81 **78**	100		
V_O	Output Swing	R_L = 600Ω to 1.35V V_{IN} = ±100mV		2.55 **2.53**	2.62		V
					0.083	0.110 **0.130**	
		R_L = 2kΩ to 1.35V V_{IN} = ±100mV		2.65 **2.64**	2.675		
					0.025	0.04 **0.045**	
I_O	Output Short Circuit Current (5)	Sourcing, V_O = 0V V_{IN} = 100mV		20 **15**	30		mA
		Sinking, V_O = 0V V_{IN} = −100mV		18 **12**	25		
Ton	Turn-on Time from Shutdown				12.5		µs
V_{SHDN}	Turn-on Voltage to enable part				1.9		V
	Turn-off Voltage				0.8		

(4) For ensured temperature ranges, see Input Common-Mode Voltage Range specifications.
(5) Applies to both single-supply and split-supply operation. Continuous short circuit operation at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of 45mA over long term may adversely affect reliability.

Copyright © 2001–2013, Texas Instruments Incorporated

2.7V AC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 2.7V, V^- = 0V, V_{CM} = 1.0V, V_O = 1.35V, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions	Min (2)	Typ (3)	Max (2)	Units
SR	Slew Rate	(4)		0.4		V/µs
GBW	Gain-Bandwidth Product			1.4		MHz
Φ_m	Phase Margin			70		deg
G_m	Gain Margin			7.5		dB
e_n	Input-Referred Voltage Noise	f = 10 kHz, V_{CM} = 0.5V		57		nV/√Hz
i_n	Input-Referred Current Noise	f = 10 kHz		0.08		pA/√Hz
THD	Total Harmonic Distortion	f = 1kHz, A_V = +1 R_L = 600Ω, V_{IN} = $1V_{PP}$		0.022		%
	Amp-to-Amp Isolation	(5)		123		dB

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.
(4) Connected as voltage follower with input step from V^- to V^+. Number specified is the slower of the positive and negative slew rates.
(5) Input referred, R_L = 100kΩ connected to $V^+/2$. Each amp excited in turn with 1kHz to produce $V_O = 3V_{PP}$. (For Supply Voltages <3V, $V_O = V^+$).

5V DC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 5V, V^- = 0V, $V_{CM} = V^+/2$, $V_O = V^+/2$, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions		Min (2)	Typ (3)	Max (2)	Units
V_{OS}	Input Offset Voltage	LMV981-N (Single)			1	4 **6**	mV
		LMV982 (Dual)			1	5.5 **7.5**	
TCV_{OS}	Input Offset Voltage Average Drift				5.5		µV/°C
I_B	Input Bias Current				14	35 **50**	nA
I_{OS}	Input Offset Current				9	25 **40**	nA
I_S	Supply Current (per Channel)				116	210 **230**	µA
		In Shutdown	LMV981-N (Single)		0.201	1 **2**	µA
			LMV982 (Dual)		0.302	3.5 **5**	
CMRR	Common Mode Rejection Ratio	0 ≤ V_{CM} ≤ 3.8V 4.6V ≤ V_{CM} ≤ 5.0V (4)		60 **55**	86		dB
		−0.2V ≤ V_{CM} ≤ 0V 5.0V ≤ V_{CM} ≤ 5.2V		50	78		

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.
(4) For ensured temperature ranges, see Input Common-Mode Voltage Range specifications.

Copyright © 2001–2013, Texas Instruments Incorporated

5V DC Electrical Characteristics (continued)

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 5V, V^- = 0V, V_{CM} = V^+/2, V_O = V^+/2, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions		Min (2)	Typ (3)	Max (2)	Units
PSRR	Power Supply Rejection Ratio	1.8V ≤ V^+ ≤ 5V V_{CM} = 0.5V		75 **70**	100		dB
CMVR	Input Common-Mode Voltage Range	For CMRR Range ≥ 50dB	T_A = 25°C	V^- −0.2	−0.2 to 5.3	V^+ +0.2	V
			T_A = −40°C to 85°C	V^-		V^+	
			T_A = 125°C	V^- +0.3		V^+ −0.3	
A_V	Large Signal Voltage Gain (LMV981-N Single)	R_L = 600Ω to 2.5V, V_O = 0.2V to 4.8V		88 **87**	102		dB
		R_L = 2kΩ to 2.5V, V_O = 0.2V to 4.8V		94 **93**	113		
	Large Signal Voltage Gain LMV982 (Dual)	R_L = 600Ω to 2.5V, V_O = 0.2V to 4.8V		81 **78**	90		dB
		R_L = 2kΩ to 2.5V, V_O = 0.2V to 4.8V		85 **82**	100		
V_O	Output Swing	R_L = 600Ω to 2.5V V_{IN} = ±100mV (4)		4.855 **4.835**	4.890		V
					0.120	0.160 **0.180**	
		R_L = 2kΩ to 2.5V V_{IN} = ±100mV		4.945 **4.935**	4.967		
					0.037	0.065 **0.075**	
I_O	Output Short Circuit Current (5)	LMV981-N, Sourcing, V_O = 0V V_{IN} = 100mV		80 **68**	100		mA
		Sinking, V_O = 5V V_{IN} = −100mV		58 **45**	65		
Ton	Turn-on Time from Shutdown				8.4		µs
V_{SHDN}	Turn-on Voltage to enable part				4.2		V
	Turn-off Voltage				0.8		

(5) Applies to both single-supply and split-supply operation. Continuous short circuit operation at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of 45mA over long term may adversely affect reliability.

5V AC Electrical Characteristics

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 5V, V^- = 0V, V_{CM} = V^+/2, V_O = 2.5V, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+.**Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions	Min (2)	Typ (3)	Max (2)	Units
SR	Slew Rate	(4)		0.42		V/µs
GBW	Gain-Bandwidth Product			1.5		MHz
Φ_m	Phase Margin			71		deg
G_m	Gain Margin			8		dB
e_n	Input-Referred Voltage Noise	f = 10 kHz, V_{CM} = 1V		50		nV/√Hz
i_n	Input-Referred Current Noise	f = 10 kHz		0.08		pA/√Hz

(1) Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that T_J = T_A. No ensured specification of parametric performance is indicated in the electrical tables under conditions of internal self heating where T_J > T_A. See Application Note section for information on temperature derating of this device. Absolute Maximum Ratings indicated junction temperature limits beyond which the device may be permanently degraded, either mechanically or electrically.
(2) All limits are specified by testing or statistical analysis.
(3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration. The typical values are not tested and are not ensured on shipped production material.
(4) Connected as voltage follower with input step from V^- to V^+. Number specified is the slower of the positive and negative slew rates.

Copyright © 2001–2013, Texas Instruments Incorporated

5V AC Electrical Characteristics (continued)

Unless otherwise specified, all limits ensured for T_J = 25°C. V^+ = 5V, V^- = 0V, $V_{CM} = V^+/2$, V_O = 2.5V, R_L > 1 MΩ and $\overline{SHDN}$ tied to V^+. **Boldface** limits apply at the temperature extremes. See (1).

Parameter		Test Conditions	Min (2)	Typ (3)	Max (2)	Units
THD	Total Harmonic Distortion	f = 1kHz, A_V = +1 R_L = 600Ω, V_O = 1 V_{PP}		0.022		%
	Amp-to-Amp Isolation	(5)		123		dB

(5) Input referred, R_L = 100kΩ connected to $V^+/2$. Each amp excited in turn with 1kHz to produce $V_O = 3V_{PP}$. (For Supply Voltages <3V, $V_O = V^+$).

Connection Diagrams

Top View




Figure 1. 6-Bump DSBGA Package
See Package Number YZR0006BBA

Top View




Figure 2. 6-Pin SC70 and SOT-23
See Package Numbers DCK0006A and DBV0006A

Top View




Figure 3. 10-Pin VSSOP Package
See Package Number DGS0010A

Copyright © 2001–2013, Texas Instruments Incorporated

Typical Performance Characteristics

Unless otherwise specified, V_S = +5V, single supply, T_A = 25°C.

Supply Current vs. Supply Voltage (LMV981-N)




Figure 4.

Sourcing Current vs. Output Voltage




Figure 5.

Sinking Current vs. Output Voltage




Figure 6.

Output Voltage Swing vs. Supply Voltage




Figure 7.

Output Voltage Swing vs. Supply Voltage




Figure 8.

Gain and Phase vs. Frequency




Figure 9.

Copyright © 2001–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Unless otherwise specified, V_S = +5V, single supply, T_A = 25°C.

Gain and Phase vs. Frequency




Figure 10.

Gain and Phase vs. Frequency




Figure 11.

Gain and Phase vs. Frequency




Figure 12.

CMRR vs. Frequency




Figure 13.

PSRR vs. Frequency




Figure 14.

Input Voltage Noise vs. Frequency




Figure 15.

Copyright © 2001–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Unless otherwise specified, V_S = +5V, single supply, T_A = 25°C.

Input Current Noise vs. Frequency




Figure 16.

THD vs. Frequency




Figure 17.

THD vs. Frequency




Figure 18.

Slew Rate vs. Supply Voltage




Figure 19.

Small Signal Non-Inverting Response




Figure 20.

Small Signal Non-Inverting Response




Figure 21.

Copyright © 2001–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Unless otherwise specified, V_S = +5V, single supply, T_A = 25°C.

Small Signal Non-Inverting Response




Figure 22.

Large Signal Non-Inverting Response




Figure 23.

Large Signal Non-Inverting Response




Figure 24.

Large Signal Non-Inverting Response




Figure 25.

Short Circuit Current vs. Temperature (Sinking)




Figure 26.

Short Circuit Current vs. Temperature (Sourcing)




Figure 27.

Copyright © 2001–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Unless otherwise specified, V_S = +5V, single supply, T_A = 25°C.

Offset Voltage vs. Common Mode Range




Figure 28.

Offset Voltage vs. Common Mode Range




Figure 29.

Offset Voltage vs. Common Mode Range




Figure 30.

Copyright © 2001–2013, Texas Instruments Incorporated

APPLICATION NOTE

Input and Output Stage

The rail-to-rail input stage of this family provides more flexibility for the designer. The LMV981-N/LMV982 use a complimentary PNP and NPN input stage in which the PNP stage senses common mode voltage near V^- and the NPN stage senses common mode voltage near V^+. The transition from the PNP stage to NPN stage occurs 1V below V^+. Since both input stages have their own offset voltage, the offset of the amplifier becomes a function of the input common mode voltage and has a crossover point at 1V below V^+.

This V_{OS} crossover point can create problems for both DC and AC coupled signals if proper care is not taken. Large input signals that include the V_{OS} crossover point will cause distortion in the output signal. One way to avoid such distortion is to keep the signal away from the crossover. For example, in a unity gain buffer configuration and with V_S = 5V, a 5V peak-to-peak signal will contain input-crossover distortion while a 3V peak-to-peak signal centered at 1.5V will not contain input-crossover distortion as it avoids the crossover point. Another way to avoid large signal distortion is to use a gain of −1 circuit which avoids any voltage excursions at the input terminals of the amplifier. In that circuit, the common mode DC voltage can be set at a level away from the V_{OS} cross-over point. For small signals, this transition in V_{OS} shows up as a V_{CM} dependent spurious signal in series with the input signal and can effectively degrade small signal parameters such as gain and common mode rejection ratio. To resolve this problem, the small signal should be placed such that it avoids the V_{OS} crossover point. In addition to the rail-to-rail performance, the output stage can provide enough output current to drive 600Ω loads. Because of the high current capability, care should be taken not to exceed the 150°C maximum junction temperature specification.

Shutdown Mode

The LMV981-N/LMV982 have a shutdown pin. To conserve battery life in portable applications, the LMV981-N/LMV982 can be disabled when the shutdown pin voltage is pulled low.

The shutdown pin can't be left unconnected. In case shut-down operation is not needed, the shutdown pin should be connected to V^+ when the LMV981-N/LMV982 are used. Leaving the shutdown pin floating will result in an undefined operation mode, either shutdown or active, or even oscillating between the two modes.

Input Bias Current Consideration

The LMV981-N/LMV982 family has a complementary bipolar input stage. The typical input bias current (I_B) is 15nA. The input bias current can develop a significant offset voltage. This offset is primarily due to I_B flowing through the negative feedback resistor, R_F. For example, if I_B is 50nA and R_F is 100kΩ, then an offset voltage of 5mV will develop ($V_{OS} = I_B \times R_F$). Using a compensation resistor (R_C), as shown in Figure 31, cancels this effect. But the input offset current (I_{OS}) will still contribute to an offset voltage in the same manner.

Copyright © 2001–2013, Texas Instruments Incorporated




Figure 31. Canceling the Offset Voltage due to Input Bias Current

Typical Applications

High Side Current Sensing

The high side current sensing circuit (Figure 32) is commonly used in a battery charger to monitor charging current to prevent over charging. A sense resistor R_{SENSE} is connected to the battery directly. This system requires an op amp with rail-to-rail input. The LMV981-N/LMV982 are ideal for this application because the common mode input range goes up to the rail.




Figure 32. High Side Current Sensing

Half-Wave Rectifier with Rail-to-Ground Output Swing

Since the LMV981-N/LMV982 input common mode range includes both positive and negative supply rails and the output can also swing to either supply, achieving half-wave rectifier functions in either direction is an easy task. All that is needed are two external resistors; there is no need for diodes or matched resistors. The half wave rectifier can have either positive or negative going outputs, depending on the way the circuit is arranged.

Copyright © 2001–2013, Texas Instruments Incorporated

In Figure 33 the circuit is referenced to ground, while in Figure 34 the circuit is biased to the positive supply. These configurations implement the half wave rectifier since the LMV981-N/LMV982 can not respond to one-half of the incoming waveform. It can not respond to one-half of the incoming because the amplifier can not swing the output beyond either rail therefore the output disengages during this half cycle. During the other half cycle, however, the amplifier achieves a half wave that can have a peak equal to the total supply voltage. R_I should be large enough not to load the LMV981-N/LMV982.




Figure 33. Half-Wave Rectifier with Rail-to-Ground Output Swing Referenced to Ground




Figure 34. Half-Wave Rectifier with Negative-Going Output Swing Referenced to V_{CC}

Instrumentation Amplifier with Rail-to-Rail Input and Output

Some manufactures make a non-“rail-to-rail”-op amp rail-to-rail by using a resistive divider on the inputs. The resistors divide the input voltage to get a rail-to-rail input range. The problem with this method is that it also divides the signal, so in order to get the obtained gain, the amplifier must have a higher closed loop gain. This raises the noise and drift by the internal gain factor and lowers the input impedance. Any mismatch in these precision resistors reduces the CMRR as well. The LMV981-N/LMV982 is rail-to-rail and therefore doesn't have these disadvantages.

Using three of the LMV981-N/LMV982 amplifiers, an instrumentation amplifier with rail-to-rail inputs and outputs can be made as shown in Figure 35.

In this example, amplifiers on the left side act as buffers to the differential stage. These buffers assure that the input impedance is very high and require no precision matched resistors in the input stage. They also assure that the difference amp is driven from a voltage source. This is necessary to maintain the CMRR set by the matching R_1-R_2 with R_3-R_4. The gain is set by the ratio of R_2/R_1 and R_3 should equal R_1 and R_4 equal R_2. With both rail-to-rail input and output ranges, the input and output are only limited by the supply voltages. Remember that even with rail-to-rail outputs, the output can not swing past the supplies so the combined common mode voltages plus the signal should not be greater that the supplies or limiting will occur. For additional applications, see Texas Instruments application notes AN–29, AN–31, AN–71, and AN–127.





Figure 35. Rail-to-rail instrumentation amplifier

Copyright © 2001–2013, Texas Instruments Incorporated

Simplified Schematic



REVISION HISTORY

Changes from Revision K (March 2013) to Revision L	Page
• Changed layout of National Data Sheet to TI format	17

Copyright © 2001–2013, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
LMV981MF	ACTIVE	SOT-23	DBV	6	1000	TBD	Call TI	Call TI	-40 to 125	A78A	Samples
LMV981MF/NOPB	ACTIVE	SOT-23	DBV	6	1000	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A78A	Samples
LMV981MFX	ACTIVE	SOT-23	DBV	6	3000	TBD	Call TI	Call TI	-40 to 125	A78A	Samples
LMV981MFX/NOPB	ACTIVE	SOT-23	DBV	6	3000	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A78A	Samples
LMV981MG	ACTIVE	SC70	DCK	6	1000	TBD	Call TI	Call TI	-40 to 125	A77	Samples
LMV981MG/NOPB	ACTIVE	SC70	DCK	6	1000	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A77	Samples
LMV981MGX	ACTIVE	SC70	DCK	6	3000	TBD	Call TI	Call TI	-40 to 125	A77	Samples
LMV981MGX/NOPB	ACTIVE	SC70	DCK	6	3000	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A77	Samples
LMV981TL/NOPB	ACTIVE	DSBGA	YZR	6	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM	-40 to 125	A H	Samples
LMV981TLX/NOPB	ACTIVE	DSBGA	YZR	6	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM	-40 to 125	A H	Samples
LMV982MM	ACTIVE	VSSOP	DGS	10	1000	TBD	Call TI	Call TI	-40 to 125	A87A	Samples
LMV982MM/NOPB	ACTIVE	VSSOP	DGS	10	1000	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A87A	Samples
LMV982MMX	ACTIVE	VSSOP	DGS	10	3500	TBD	Call TI	Call TI	-40 to 125	A87A	Samples
LMV982MMX/NOPB	ACTIVE	VSSOP	DGS	10	3500	Green (RoHS & no Sb/Br)	CU SN	Level-1-260C-UNLIM	-40 to 125	A87A	Samples

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


(4) Multiple Top-Side Markings will be inside parentheses. Only one Top-Side Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Top-Side Marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
LMV981MF	SOT-23	DBV	6	1000	178.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMV981MF/NOPB	SOT-23	DBV	6	1000	178.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMV981MFX	SOT-23	DBV	6	3000	178.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMV981MFX/NOPB	SOT-23	DBV	6	3000	178.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
LMV981MG	SC70	DCK	6	1000	178.0	8.4	2.25	2.45	1.2	4.0	8.0	Q3
LMV981MG/NOPB	SC70	DCK	6	1000	178.0	8.4	2.25	2.45	1.2	4.0	8.0	Q3
LMV981MGX	SC70	DCK	6	3000	178.0	8.4	2.25	2.45	1.2	4.0	8.0	Q3
LMV981MGX/NOPB	SC70	DCK	6	3000	178.0	8.4	2.25	2.45	1.2	4.0	8.0	Q3
LMV981TL/NOPB	DSBGA	YZR	6	250	178.0	8.4	1.12	1.63	0.76	4.0	8.0	Q1
LMV981TLX/NOPB	DSBGA	YZR	6	3000	178.0	8.4	1.12	1.63	0.76	4.0	8.0	Q1
LMV982MM	VSSOP	DGS	10	1000	178.0	12.4	5.3	3.4	1.4	8.0	12.0	Q1
LMV982MM/NOPB	VSSOP	DGS	10	1000	178.0	12.4	5.3	3.4	1.4	8.0	12.0	Q1
LMV982MMX	VSSOP	DGS	10	3500	330.0	12.4	5.3	3.4	1.4	8.0	12.0	Q1
LMV982MMX/NOPB	VSSOP	DGS	10	3500	330.0	12.4	5.3	3.4	1.4	8.0	12.0	Q1


TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
LMV981MF	SOT-23	DBV	6	1000	210.0	185.0	35.0
LMV981MF/NOPB	SOT-23	DBV	6	1000	210.0	185.0	35.0
LMV981MFX	SOT-23	DBV	6	3000	210.0	185.0	35.0
LMV981MFX/NOPB	SOT-23	DBV	6	3000	210.0	185.0	35.0
LMV981MG	SC70	DCK	6	1000	210.0	185.0	35.0
LMV981MG/NOPB	SC70	DCK	6	1000	210.0	185.0	35.0
LMV981MGX	SC70	DCK	6	3000	210.0	185.0	35.0
LMV981MGX/NOPB	SC70	DCK	6	3000	210.0	185.0	35.0
LMV981TL/NOPB	DSBGA	YZR	6	250	210.0	185.0	35.0
LMV981TLX/NOPB	DSBGA	YZR	6	3000	210.0	185.0	35.0
LMV982MM	VSSOP	DGS	10	1000	210.0	185.0	35.0
LMV982MM/NOPB	VSSOP	DGS	10	1000	210.0	185.0	35.0
LMV982MMX	VSSOP	DGS	10	3500	367.0	367.0	35.0
LMV982MMX/NOPB	VSSOP	DGS	10	3500	367.0	367.0	35.0


DBV (R–PDSO–G6) PLASTIC SMALL–OUTLINE PACKAGE



4073253–5/K 03/2006

NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
D. Leads 1,2,3 may be wider than leads 4,5,6 for package orientation.
E. Falls within JEDEC MO–178 Variation AB, except minimum lead width.


DGS (S–PDSO–G10) PLASTIC SMALL–OUTLINE PACKAGE



4073272/C 02/04

NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion.
D. Falls within JEDEC MO–187 variation BA.


DCK (R–PDSO–G6) PLASTIC SMALL–OUTLINE PACKAGE



4093553–4/G 01/2007

NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
D. Falls within JEDEC MO–203 variation AB.

YZR0006



TLA06XXX (Rev C)

D: Max = 1.565 mm, Min =1.504 mm

E: Max = 1.057 mm, Min =0.996 mm

4215044/A 12/12

NOTES: A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
B. This drawing is subject to change without notice.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to TI’s terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI’s goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or “enhanced plastic” are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have ***not*** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products		**Applications**	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	**TI E2E Community**	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2013, Texas Instruments Incorporated


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.