




DIMENSIONS FOR LARGE POLARIZATION RIB TERMINAL ONLY







SCALE 2:1




SEE SHEET 5
0.35mm² AND 0.50mm²
ISO WIRE SIZE P/N'S
33012-2004/3004
33001-4005/5005




SECTION B-B
SCALE 5:1






SECTION A-A

CARRIER BUMP DIRECTION
POINTS DOWN FOR TIN PLATED TERMINALS
POINTS UP FOR PRECIOUS PLATED TERMINALS



SECTION C-C
SCALE 5:1



NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATING TERMINAL SHOWN ON SD-33000-001
2. MATERIAL: ASTM B422, UNS C19025, HR04
   THICKNESS: 0.30 mm ±0.01
   TEMPER: FULL HARD (REF)
   TENSILE: 496 MIN MPA
3. TIN PLATED TERMINAL FINISH:
   OVERALL UNDERPLATE ELECTRODEPOSITED NICKEL
   OVERALL ELECTRODEPOSITED REFLOW TIN
4. GOLD PLATED TERMINAL FINISH
   OVERALL UNDERPLATE ELECTRODEPOSITED DUCTILE SULFAMATE NICKEL
   CONTACT AREA - ELECTRODEPOSITED GOLD
   GRIP AREA - ELECTRODEPOSITED 100% TIN MATTE FINISH
5. SILVER PLATED TERMINAL FINISH
   OVERALL UNDERPLATE ELECTRODEPOSITED DUCTILE SULFAMATE NICKEL
   CONTACT AREA - ELECTRODEPOSITED PURE SILVER (0.5% MAX IMPURITIES) SEMI-BRIGHT FINISH
   - SILVER ANTI-TARNISH : EVABRITE
   GRIP AREA - ELECTRODEPOSITED 100% TIN MATTE FINISH
6. MEETS PERFORMANCE SPECIFICATION FOR CABLE TO TERMINAL ELECTRICAL CRIMPS PER SAE/USCAR-21 (8/2001)
7. MEETS PERFORMANCE STANDARD FOR AUTOMOTIVE ELECTRICAL CONNECTOR SYSTEMS FOR SAE/USCAR-2, REV. 4 (TEMP CLASS 3) (4/2001)
8. MEETS ELECTRICAL CONNECTION SYSTEM DESIGN SPECIFICATION (SDS) REV.11 (5/2002)
9. MEETS FIELD CORRELATED LIFE TEST (FCLT) PER SAE/USCAR-20 (11/2001)
10. MEETS WIRING COMPONENT DESIGN GUIDLINES SAE/USCAR-12 REV 2 (12/2001)
11. TSC ON A DIMENSION TO BE INTERPRETED AS DISTANCE TO A THEORETICAL SHARP CORNER AS IF THE RADIUS WERE NOT PRESENT
12. REFERENCE 97BG-14474-AAB FOR LARGE POLARIZATION RIB CAVITY SPECIFICATION
13. INSERTION FORCE (TIN) AVG. FROM PV TESTING =
    3.8N LARGE POLARIZATION RIB
    3.5N SMALL POLARIZATION RIB
    (REFERENCE)
14. ALL DIMENSIONS EXCEPT (1), (2), (3) & (4) ARE COMMON TO BOTH SMALL AND LARGE POLARIZATION RIB TERMINALS
15. REFERENCE PK-31300-516 FOR REEL DIRECTION
16. REFERENCE AS-33012-002 FOR CRIMP INFORMATION

ENTER DESCRIPTION
EC NO: UAU2011-1208 2011/06/28
DRWN:ADHIR
CH'KD:
APPR:BMOSER 2011/07/06
DESCRIPTION
B3
REV

QUALITY SYMBOLS
FV =0
FE =0
FP =0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.005	± ---
2 PLACES	± 0.10	± ---
1 PLACE	± 0.3	± ---
ANGULAR ± 3 °		


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	4:1
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	L. PULLIAM 2005/06/21
CHECKED BY / DATE	A. DHIR 2005/06/21
APPROVED BY / DATE	B. MOSER 2005/06/22
MATERIAL NO.	SEE TABLE
TITLE	MX150 RECEPTACLE TERMINAL
	MOLEX INCORPORATED
DOCUMENT NO.	SD-33012-002
SHEET NO.	1 OF 5
SIZE	C


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TABLE

SUPPLIER PART NUMBER		PLATING	GRIP CODE	WIRE APPLICATION		A ±0.30	B ±0.30	C ±0.30	D ±0.30	COMMENTS
SMALL POLARIZATION RIB										
RIGHT PAYOFF DIRECTION B	LEFT PAYOFF DIRECTION D			SAE (AWG)	METRIC (mm²)					
33012-2001	33012-3001	TIN	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33012-2002	33012-3002	TIN	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33012-2003	33012-3003	TIN	22	22	0.35-0.50	2.5	2.6	0.9	1.0	
33012-2004	33012-3004	TIN	M3	N/A	0.35-0.50	2.5	2.7	0.9	1.54±0.1	PREFERRED TERMINAL FOR USE IN SEALED APPLICATION WITH 0.35& 0.50 WIRES (OD 1.2-1.7mm)
33001-2003	33001-3003	GOLD	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33001-2004	33001-3004	GOLD	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33001-2005	33001-3005	GOLD	22	22	0.35-0.50	2.5	2.6	0.9	1.0	
33001-4001	33001-5001	SILVER	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33001-4002	33001-5002	SILVER	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33001-4003	33001-5003	SILVER	22	22	0.35-0.50	2.5	2.6	0.9	1.0	
33001-4005	33001-5005	SILVER	M3	N/A	0.35-0.50	2.5	2.7	0.9	1.54±0.1	PREFERRED TERMINAL FOR USE IN SEALED APPLICATION WITH 0.35& 0.50 WIRES (OD 1.2-1.7mm) USE IN CLASS 3 (125° C) APPLICATIONS ONLY
LARGE POLARIZATION RIB - NOT TO BE USED IN MX150 SEALED CONNECTORS										
33012-2021	33012-3021	TIN	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33012-2022	33012-3022	TIN	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33012-2023	33012-3023	TIN	22	22	0.35-0.50	2.5	2.6	0.9	1.0	
33001-2021	33001-3021	GOLD	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33001-2022	33001-3022	GOLD	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33001-2023	33001-3023	GOLD	22	22	0.35-0.50	2.5	2.6	0.9	1.0	
33001-4021	33001-5021	SILVER	14	14/16	2.0-1.5	3.9	4.4	1.7	1.6	
33001-4022	33001-5022	SILVER	18	18/20	1.0-0.75	3.3	3.1	1.3	1.4	
33001-4023	33001-5023	SILVER	22	22	0.35-0.50	2.5	2.6	0.9	1.0	



SECTION G-G



GROMMET CAP OPENING

GROMMET SEAL / CAP CONFIGURATION TO MODIFY LARGE POLARIZATION RIB CAVITY TO ACCEPT SMALL POLARIZATION RIB APPLICATIONS

ENTER DESCRIPTION
EC NO: UAU2011-1208 2011/06/28
DRWN:ADHIR
CH'KD:
APPR:BMOSER 2011/07/06
DESCRIPTION
B3
REV

QUALITY SYMBOLS
F =0
F =0
F =0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.005	± ---
2 PLACES	± 0.10	± ---
1 PLACE	± 0.3	± ---
ANGULAR ± 3 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: L. PULLIAM DATE: 2005/06/21
CHECKED BY: A. DHIR DATE: 2005/06/21
APPROVED BY: B. MOSER DATE: 2005/06/22

TITLE: MX150 RECEPTACLE TERMINAL

molex MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-33012-002
SHEET NO.: 2 OF 5


SIZE: C


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION


THIS CHECKING - AID IS FOR SMALL POLARIZATION RIB TERMINALS ONLY




CHECKING - AID ASSEMBLY
SCALE 1:1









DETAIL A
SCALE 5:1



CHECKING - AID
UPPER



CHECKING - AID
LOWER



CRIMP REQUIREMENTS:

1. CRIMP STRAIGHTNESS MUST BE MAINTAINED USE A KNOCKDOWN TOOL LOCATED AS SHOWN TERMINAL BOX MUST NOT BE DEFORMED
2. AFTER CRIMPING, THE CRIMPED TERMINAL (AND UP TO 5 mm OF WIRE PAST THE INSULATOR CUTOFF TAB) MUST FIT FREELY INTO THE CHECKING-AID SHOWN ON THIS PAGE
3. FOR OTHER MECHANICAL REQUIREMENTS ON CRIMPED TERMINALS, REFER TO SAE/USCAR-21 (5-13-02) SECTIONS 4.2 (VISUAL INSPECTION), 4.2 (CROSS SECTION ANALYSIS) AND 4.4 (CONDUCTOR CRIMP PULLOUT FORCE)

UPPER & LOWER
CHECKING-AID
A2 TOOL STEEL
HARDEN & GRIND
ROCKWELL "C" 56-58

ENTER DESCRIPTION
EC NO: UAU2011-1208 2011/06/28
DRWN:ADHIR
CH'KD:
APPR:BMOSER 2011/07/06
DESCRIPTION
B3
REV

QUALITY SYMBOLS

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.005	± ---
2 PLACES	± 0.10	± ---
1 PLACE	± 0.3	± ---
ANGULAR ± 3 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY

DRAWN BY	L. PULLIAM 2005/06/21
CHECKED BY	A. DHIR 2005/06/21
APPROVED BY	B. MOSER 2005/06/22
MATERIAL NO.	SEE TABLE

SCALE: 2:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


TITLE
MX150
RECEPTACLE TERMINAL


MOLEX INCORPORATED

DOCUMENT NO. SD-33012-002
SHEET NO. 3 OF 5


SIZE C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION







SECTION D-D




NOTES: UNLESS OTHERWISE SPECIFIED


1. TOLERANCES: LINEAR ±0.10
   ANGULAR ±3°
2. ALL DRAFT WITHIN TOLERANCE.
3. MAX RADII ON ALL CORNERS SHOWN SHARP: 0.10
4. MAX FLASH PERMISSIBLE: 0.1
5. EJECTOR PIN MARKS PERMISSIBLE IF FLUSH TO 0.25 BELOW SURFACE.
6. MATERIAL: HOUSING/FINGER SPECIFICATION ENGINEERED FOR MATERIAL WITH THE FOLLOWING PROPERTIES:
   A. FLEXURAL MODULUS = 4,500 TO 9,400 MPa PER ASTM TEST D790
   B. ELONGATION AT YIELD = 2.3% OR BETTER PER ASTM TEST D638 TYPE V
7. CAVITY SPEC FOR USE ONLY WITH MOLEX RECEPTACLE TERMINAL PART NUMBERS SPECIFIED ELSEWHERE ON THIS DRAWING






SECTION E-E







DETAIL Z
SCALE 20:1



SECTION F-F



RECEPTACLE CAVITY ASSEMBLED VIEWS
FOR SMALL POLARIZATION RIB APPLICATIONS
FIG. 1



SECTION D-D
FOR LARGE POLARIZATION RIB APPLICATIONS
FIG. 2

PROBING DOWN THE THROAT MUST USE THIS TERMINAL PROBE

PROBE PIN DETAILS:
MANUFACTURER: LONE STAR INDUSTRIAL
PART NUMBER: LS054R-403-N-4.6
PIN DIAMETER: 0.025 IN (0.64mm)
TIP SHAPE: SPHERICAL
TEL: 915-779-7255

PREFERRED PROBING LOCATION IS NOT ON SPRING MEMBER

IF ELECTRICAL CONTINUITY PROBE TOUCHES SPRING MEMBER USE PROBING AS SHOWN IN FIG. 2

ENTER DESCRIPTION
EC NO: UAU2011-1208 2011/06/28
DRWN:ADHIR
CH'KD:
APPR:BMOSER 2011/07/06
DESCRIPTION
REV
B3

QUALITY SYMBOLS
=0
=0
=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.005	± ---
2 PLACES	± 0.10	± ---
1 PLACE	± 0.3	± ---
ANGULAR ± 3 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 5:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: L. PULLIAM DATE: 2005/06/21
CHECKED BY: A. DHIR DATE: 2005/06/21
APPROVED BY: B. MOSER DATE: 2005/06/22


TITLE
MX150
RECEPTACLE TERMINAL

molex MOLEX INCORPORATED


MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-33012-002
SHEET NO.: 4 OF 5

SIZE C


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION




ISO VIEW
SCALE 2:1





SECTION BB-BB





SECTION CC-CC





SECTION AA-AA

P/N'S 33012-2004/3004
33001-4005/5005

CARRIER BUMP DIRECTION
POINTS DOWN FOR TIN PLATED TERMINAL
POINTS UP FOR PRECIOUS METAL PLATED TERMINAL

ENTER DESCRIPTION
EC NO: UAU2011-1208 2011/06/28
DRWN:ADHIR
CH'KD:
APPR:BMOSER 2011/07/06
DESCRIPTION
B3
REV

QUALITY SYMBOLS
F =0
F =0
F =0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.005	± ---
2 PLACES	± 0.10	± ---
1 PLACE	± 0.3	± ---
ANGULAR ± 3 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 5:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: L. PULLIAM DATE: 2005/06/21
CHECKED BY: A. DHIR DATE: 2005/06/21
APPROVED BY: B. MOSER DATE: 2005/06/22

TITLE
MX150
RECEPTACLE TERMINAL

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-33012-002
SHEET NO.: 5 OF 5
SIZE: C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.