

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DW	—


REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASED.	19APR'12	JC	WK






RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05





NOTES:
1. MATERIAL:
   1.1 HOUSING: LCP, UL 94V-0, BLACK COLOR.
   1.2 CONTACT: PHOSPHOR BRONZE.
   1.3 SHELL: PHOSPHOR BRONZE.
   1.4 PANEL: PHOSPHOR BRONZE.
   1.5 REAR SHELL: SPCC.
2. FINISH:
   2.1 CONTACT
   GOLD FLASH ON THE CONTACT AREA,
   2.54um [100u"] MIN. MATTE-TIN PLATING ON THE SOLDERING AREA.
   1.27um [50u"] MIN. NICKEL UNDERPLATING OVERALL.
   2.2 SHELL: 2.54um [100u"] MIN. NICKEL PLATING.
   2.3 PANEL: 1.27um [50u"] MIN. NICKEL PLATING.
   2.4 REAR SHELL: 1.27um [50u"] MIN. NICKEL PLATING.
3. RECOMMENDED P.C.B THICKNESS : 1.60mm
4. REFLOW SOLDER CAPABLE TO 260°C PER TE CONNECTIVITY SPEC. 109-201, CONDITION B.
5. LOW HALOGEN SPECIFICATION:
   CHLORINE(Cl): 900ppm MAX.
   BROMINE(Br): 900ppm MAX.
   CHLORINE(Cl)+BROMINE(Br): 1500ppm MAX.



MOUNTING PANEL CUTOUT

2041495-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	± -
ANGLES	± 3°

MATERIAL: SEE NOTE
FINISH: SEE NOTE

DWN	J. CHEN 19APR2012
CHK	S. CHIEN 19APR2012
APVD	W. KODAMA 19APR2012
PRODUCT SPEC	108-57519
APPLICATION SPEC	—
WEIGHT	9.55 GRAMS

TE Connectivity

NAME: TRIPLE STACKED USB, A TYPE RECEPTACLE, R/A DIP CONN.

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-2041495	—


CUSTOMER DRAWING | SCALE — | SHEET 1 OF 2 | REV A


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
DW	—


REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			














10.55	9.55	100	10	1000
G/W (KG)	N/W (KG)	PCS/ TRAY	TRAY/ CARTON	PCS/ CARTON

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –

FINISH –

DWN –
CHK –
APVD –
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
TRIPLE STACKED USB, A TYPE RECEPTACLE, R/A DIP CONN.

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-2041495	—

CUSTOMER DRAWING

SCALE	SHEET	REV
—	2 OF 2	A


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.