
BZV55 series

DATA SHEET



Voltage regulator diodes

Voltage regulator diodes BZV55 series

FEATURES


- Total power dissipation: max. 500 mW
- Two tolerance series: ±2%, and approx. ±5%
- Working voltage range: nom. 2.4 to 75 V (E24 range)
- Non-repetitive peak reverse power dissipation: max. 40 W.

APPLICATIONS

- Low voltage stabilizers or voltage references.

DESCRIPTION

Low-power voltage regulator diodes in small hermetically sealed glass SOD80C SMD packages. The diodes are available in the normalized E24 ±2% (BZV55-B) and approx. ±5% (BZV55-C) tolerance range. The series consists of 37 types with nominal working voltages from 2.4 to 75 V.



The cathode is indicated by a yellow band.

Fig.1 Simplified outline (SOD80C) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
I_F	continuous forward current		–	250	mA
I_{ZSM}	non-repetitive peak reverse current	t_p = 100 µs; square wave; T_j = 25 °C prior to surge	see Tables 1 and 2		A
P_{tot}	total power dissipation	$T_{amb} \leq$ 50 °C; note 1	–	400	mW
		tie-point ≤ 50 °C; note 1	–	500	mW
P_{ZSM}	non-repetitive peak reverse power dissipation	t_p = 100 µs; square wave; T_j = 25 °C prior to surge; see Fig.3	–	40	W
T_{stg}	storage temperature		–65	+200	°C
T_j	junction temperature		–65	+200	°C

Note

1. Device mounted on a ceramic substrate of 10 × 10 × 0.6 mm.

ELECTRICAL CHARACTERISTICS

Total BZV55-B and BZV55-C series

T_j = 25 °C; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MAX.	UNIT
V_F	forward voltage	I_F = 10 mA; see Fig.4	0.9	V
I_R	reverse current			
	BZV55-B/C2V4	V_R = 1 V	50	µA
	BZV55-B/C2V7	V_R = 1 V	20	µA
	BZV55-B/C3V0	V_R = 1 V	10	µA
	BZV55-B/C3V3	V_R = 1 V	5	µA
	BZV55-B/C3V6	V_R = 1 V	5	µA
	BZV55-B/C3V9	V_R = 1 V	3	µA
	BZV55-B/C4V3	V_R = 1 V	3	µA
	BZV55-B/C4V7	V_R = 2 V	3	µA
	BZV55-B/C5V1	V_R = 2 V	2	µA
	BZV55-B/C5V6	V_R = 2 V	1	µA
	BZV55-B/C6V2	V_R = 4 V	3	µA
	BZV55-B/C6V8	V_R = 4 V	2	µA
	BZV55-B/C7V5	V_R = 5 V	1	µA
	BZV55-B/C8V2	V_R = 5 V	700	nA
	BZV55-B/C9V1	V_R = 6 V	500	nA
	BZV55-B/C10	V_R = 7 V	200	nA
	BZV55-B/C11	V_R = 8 V	100	nA
	BZV55-B/C12	V_R = 8 V	100	nA
	BZV55-B/C13	V_R = 8 V	100	nA
	BZV55-B/C15 to BZV55-B/C75	$V_R = 0.7V_{Znom}$	50	nA

Voltage regulator diodes

BZV55 series

Table 1 Per type, BZV55-**B/C2V4** to BZV55-**B/C24**

T_j = 25 °C unless otherwise specified.

BZV55-Bxxx Cxxx	WORKING VOLTAGE V_Z (V) at I_{Ztest} = 5 mA				DIFFERENTIAL RESISTANCE r_{dif} (Ω)				TEMP. COEFF. S_Z (mV/K) at I_{Ztest} = 5 mA (see Figs 5 and 6)			DIODE CAP. C_d (pF) at f = 1 MHz; V_R = 0 V	NON-REPETITIVE PEAK REVERSE CURRENT I_{ZSM} (A) at t_p = 100 μs; T_{amb} = 25 °C
	Tol. ±2% (B)		Tol. approx. ±5% (C)		at I_{Ztest} = 1 mA		at I_{Ztest} = 5 mA						
	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	MIN.	TYP.	MAX.	MAX.	MAX.
2V4	2.35	2.45	2.2	2.6	275	600	70	100	–3.5	–1.6	0	450	6.0
2V7	2.65	2.75	2.5	2.9	300	600	75	100	–3.5	–2.0	0	450	6.0
3V0	2.94	3.06	2.8	3.2	325	600	80	95	–3.5	–2.1	0	450	6.0
3V3	3.23	3.37	3.1	3.5	350	600	85	95	–3.5	–2.4	0	450	6.0
3V6	3.53	3.67	3.4	3.8	375	600	85	90	–3.5	–2.4	0	450	6.0
3V9	3.82	3.98	3.7	4.1	400	600	85	90	–3.5	–2.5	0	450	6.0
4V3	4.21	4.39	4.0	4.6	410	600	80	90	–3.5	–2.5	0	450	6.0
4V7	4.61	4.79	4.4	5.0	425	500	50	80	–3.5	–1.4	0.2	300	6.0
5V1	5.00	5.20	4.8	5.4	400	480	40	60	–2.7	–0.8	1.2	300	6.0
5V6	5.49	5.71	5.2	6.0	80	400	15	40	–2.0	1.2	2.5	300	6.0
6V2	6.08	6.32	5.8	6.6	40	150	6	10	0.4	2.3	3.7	200	6.0
6V8	6.66	6.94	6.4	7.2	30	80	6	15	1.2	3.0	4.5	200	6.0
7V5	7.35	7.65	7.0	7.9	30	80	6	15	2.5	4.0	5.3	150	4.0
8V2	8.04	8.36	7.7	8.7	40	80	6	15	3.2	4.6	6.2	150	4.0
9V1	8.92	9.28	8.5	9.6	40	100	6	15	3.8	5.5	7.0	150	3.0
10	9.80	10.20	9.4	10.6	50	150	8	20	4.5	6.4	8.0	90	3.0
11	10.80	11.20	10.4	11.6	50	150	10	20	5.4	7.4	9.0	85	2.5
12	11.80	12.20	11.4	12.7	50	150	10	25	6.0	8.4	10.0	85	2.5
13	12.70	13.30	12.4	14.1	50	170	10	30	7.0	9.4	11.0	80	2.5
15	14.70	15.30	13.8	15.6	50	200	10	30	9.2	11.4	13.0	75	2.0
16	15.70	16.30	15.3	17.1	50	200	10	40	10.4	12.4	14.0	75	1.5
18	17.60	18.40	16.8	19.1	50	225	10	45	12.4	14.4	16.0	70	1.5
20	19.60	20.40	18.8	21.2	60	225	15	55	12.3	15.6	18.0	60	1.5
22	21.60	22.40	20.8	23.3	60	250	20	55	14.1	17.6	20.0	60	1.25
24	23.50	24.50	22.8	25.6	60	250	25	70	15.9	19.6	22.0	55	1.25

Table 2 Per type, BZV55-**B/C27** to BZV55-**B/C75**

T_j = 25 °C unless otherwise specified.

BZV55-Bxxx Cxxx	WORKING VOLTAGE V_Z (V) at I_{Ztest} = 2 mA				DIFFERENTIAL RESISTANCE r_{dif} (Ω)				TEMP. COEFF. S_Z (mV/K) at I_{Ztest} = 2 mA (see Figs 5 and 6)			DIODE CAP. C_d (pF) at f = 1 MHz; V_R = 0 V	NON-REPETITIVE PEAK REVERSE CURRENT I_{ZSM} (A) at t_p = 100 μs; T_{amb} = 25 °C
	Tol. ±2% (B)		Tol. approx. ±5% (C)		at I_{Ztest} = 0.5 mA		at I_{Ztest} = 2 mA						
	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	MIN.	TYP.	MAX.	MAX.	MAX.
27	26.50	27.50	25.1	28.9	65	300	25	80	18.0	22.7	25.3	50	1.0
30	29.40	30.60	28.0	32.0	70	300	30	80	20.6	25.7	29.4	50	1.0
33	32.30	33.70	31.0	35.0	75	325	35	80	23.3	28.7	33.4	45	0.9
36	35.30	36.70	34.0	38.0	80	350	35	90	26.0	31.8	37.4	45	0.8
39	38.20	39.80	37.0	41.0	80	350	40	130	28.7	34.8	41.2	45	0.7
43	42.10	43.90	40.0	46.0	85	375	45	150	31.4	38.8	46.6	40	0.6
47	46.10	47.90	44.0	50.0	85	375	50	170	35.0	42.9	51.8	40	0.5
51	50.00	52.00	48.0	54.0	90	400	60	180	38.6	46.9	57.2	40	0.4
56	54.90	57.10	52.0	60.0	100	425	70	200	42.2	52.0	63.8	40	0.3
62	60.80	63.20	58.0	66.0	120	450	80	215	58.8	64.4	71.6	35	0.3
68	66.60	69.40	64.0	72.0	150	475	90	240	65.6	71.7	79.8	35	0.25
75	73.50	76.50	70.0	79.0	170	500	95	255	73.4	80.2	88.6	35	0.2

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j\text{-}tp}$	thermal resistance from junction to tie-point		300	K/W
$R_{th\ j\text{-}a}$	thermal resistance from junction to ambient	see Fig.2 and note 1	380	K/W

Note

1. Device mounted on a ceramic substrate of $10 \times 10 \times 0.6$ mm.

GRAPHICAL DATA






Fig.2 Thermal resistance from junction to ambient as a function of pulse duration.




(1) T_j = 25 °C (prior to surge).
(2) T_j = 150 °C (prior to surge).

Fig.3 Maximum permissible non-repetitive peak reverse power dissipation versus duration.




T_j = 25 °C.

Fig.4 Typical forward current as a function of forward voltage.



BZV55-B/C2V4 to BZV55-B/C4V3.
T_j = 25 to 150 °C.

Fig.5 Temperature coefficient as a function of working current; typical values.



BZV55-B/C4V7 to BZV55-B/C12.
T_j = 25 to 150 °C.

Fig.6 Temperature coefficient as a function of working current; typical values.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.