









SECTION K-K'










ISOMETRIC VIEW



LEGEND

SD-35362-****

- CKT NO.
- COLOR
  - 0 : NATURAL
  - 1 : BLACK
  - 2 : RED
  - 3 : YELLOW
  - 4 : BLUE
  - 5 : GREEN
  - 6 : TUBE PACKING (Natural Color)
  - 7 : TUBE PACKING (Red Color)
  - 8 : TUBE PACKING (Blue Color)
- FINAL GOOD (BULK)
  - 5 : SELECTIVE KINK (LEAD FREE)
  - 6 : NONE KINK (LEAD FREE)
- SUB ASSY (TUBE)
  - 7 : SELECTIVE KINK (LEAD FREE)
  - 8 : NONE KINK (LEAD FREE)

NOTES

1. MATERIAL : UNFILLED POLYAMIDE, UL94V-0
   PIN : BRASS . TIN PLATED
2. FINISHES : TERMINAL : Sn 2-3um OVERALL
3. PRODUCT SPECIFICATION : PS-35507-003
4. MATING HOUSING : 35507-**0*
   MATING TERMINAL : 50212-8000
5. KINK

CKT NO / CKT	1	2	3	4	5	N-2	N-1	N
6 CKT OVER	—	A	B	—	—	B	A	—
5 CKT	A	B	—	B	A			
4 CKT	A	B	B	A				

(C)	B	(A)	ENG. NO.	ENG. NO.	CKT
31.3	28	32.3	353621 5**	35362-15**	15
29.3	26	30.3	353621 4**	35362-14**	14
27.3	24	28.3	353621 3**	35362-13**	13
25.3	22	26.3	353621 2**	35362-12**	12
23.3	20	24.3	353621 1**	35362-11**	11
21.3	18	22.3	353621 0**	35362-10**	10
19.3	16	20.3	3536209**	35362-09**	9
17.3	14	18.3	3536208**	35362-08**	8
15.3	12	16.3	3536207**	35362-07**	7
13.3	10	14.3	3536206**	35362-06**	6
11.3	8	12.3	3536205**	35362-05**	5
9.3	6	10.3	3536204**	35362-04**	4

LEAD FREE	
30 over	±0.3
10 over 30 under	±0.25
10 under	±0.2
ANGLE	±3°
GENERAL TOLERANCE	

REVISED
EC NO: KOR2009-0123 2009/03/09
DRWN:HJEONG 2009/03/10
CHKD:YSOOKIM 2009/03/11
APPR:YUNSIKKIM 2009/03/11
DESCRIPTION
REV
D

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 5:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


		DATE
DRAWN BY	YSOOKIM	1996/09/11
CHECKED BY	YSOOKIM	1996/09/11
APPROVED BY	CWLEE	1996/09/11
MATERIAL NO.	SEE TABLEE	


TITLE: 2.0 W/B WAFER ASS'Y -LEAD FREE-

molex MOLEX INCORPORATED


DOCUMENT NO. SD-35362-002
SHEET NO. 1 OF 3
SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION








SECTION K-K'



ISOMETRIC VIEW







LEGEND

SD-35362-****

CKT NO.

COLOR
- 0 : NATURAL
- 1 : BLACK
- 2 : RED
- 3 : YELLOW
- 4 : BLUE
- 5 : GREEN
- 6 : TUBE PACKING (Natural Color)
- 7 : TUBE PACKING (Red Color)
- 8 : TUBE PACKING (Blue Color)

FINAL GOOD (BULK)
- 5 : SELECTIVE KINK (LEAD FREE)
- 6 : NONE KINK (LEAD FREE)

SUB ASSY (TUBE)
- 7 : SELECTIVE KINK (LEAD FREE)
- 8 : NONE KINK (LEAD FREE)


NOTES

1. MATERIAL : WAFER : UNFILLED POLYAMIDE, UL94V-0
   PIN : BRASS
2. FINISHES : TERMINAL : Sn 2.3um OVERALL
3. PRODUCT SPECIFICATION : PS-35507-003
4. MATING HOUSING : 35507-**0*
   MATING TERMINAL : 5021 2-8000
5. KINK

CKT NO / CKT	1	2	3	—	—	N-2	N-1	N
16±20 CKT	—	A	B	—	—	B	A	—

(C)	B	(A)	MATERIAL NO.	ENG. NO.	CKT
41.3	38	42.3	3536220**	35362-20**	20
39.3	36	40.3	353621 9**	35362-19**	19
37.3	34	38.3	353621 8**	35362-18**	18
35.3	32	36.3	353621 7**	35362-17**	17
33.3	30	34.3	353621 6**	35362-16**	16

MATED HEIGHT



LEAD FREE	
30 over	±0.3
10 over 30 under	±0.25
10 under	±0.2
ANGLE	±3°
GENERAL TOLERANCE	

REVISED
EC NO: KOR2009-0123 2009/03/09
DRWN:HJEONG 2009/03/10
CHKD:YSOOKIM 2009/03/11
APPR:YUNSIKKIM
DESCRIPTION
REV
D

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
ANGULAR ±---°		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	5:1
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	YSOOKIM 1996/09/11
CHECKED BY / DATE	JKOH 1996/09/11
APPROVED BY / DATE	CWLEE 1996/09/11
MATERIAL NO.	SEE TABLE
SIZE	A3


TITLE: 2.0 W/B WAFER ASS'Y -LEAD FREE-

MOLEX INCORPORATED


DOCUMENT NO. SD-35362-002


SHEET NO. 3 OF 3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



ISOMETRIC VIEW





KINK TABLE(FOR 35362-****)

CKT NO / CKT	1	2	3	4	5	N-2	N-1	N
6 CKT OVER	—	A	B	—	—	B	A	—
5 CKT	A	B	—	B	A			
4 CKT	A	B	B	A				
3 CKT	A	B	A					
2 CKT	—							

** 35362-0287 IS ONLY KINKED 2P

CKT NO / PRODUCT NO.	1	2
35362-0287	A	B

LEAD FREE

LEGEND.

E-35362-** * *

- 2-20 Circuits — CKT NO.
- COLOR & PACKING
  - 0 : NATURAL
  - 1 : BLACK
  - 2 : RED
  - 3 : YELLOW
  - 4 : BLUE
  - 5 : GREEN
  - 6 : TUBE PACKING (Natural Color)
  - 7 : TUBE PACKING (RED Color)
  - 8 : TUBE PACKING (BLUE Color)
- KINK
  - Final GOOD (Bulk) — 5 : SELECTIVE KINK / 6 : NONE KINK
  - Sub Assy (Tube) — 7 : SELECTIVE KINK / 8 : NONE KINK

NOTES

1. MATERIAL : TUBE - TRANSLUCENT P.V.C (P-1000)
   Wafer - POLYAMIDE, UL94V-0
   PIN - BRASS SQ 0.5mm
2. BOW(CAMBER) : 1.0mm MAX/Total Length
3. DIMENSIONS GIVEN ACROSS CENTER LINES ARE SYMMETRICAL ABOUT THOSE CENTER LINES WITH HALF THE TOTAL LENGTH.
4. TOTAL TUBE LENGTH : 560mm + -1mm
5. TWIST : 5° MAX./Total Length
6. BURRS : 0.2mm MAX.
7. SKEW : PRODUCTS MUST BE FLOWED SMOOTHLY WHEN THIS STICK IS PLACES 30° ANGLE.
8. THICKNESS : 0.6mm +-0.1mm
9. ARTWORK : PER E-35900-0434
   (SILK SCREEN COLOR : RED)
- C 10. APPLICABLE STOPPER(RUBBER) : 35900-0435

TABLE

	QT'y	Material NO.	ENG. NO.	CKT
	10	20**	-20**	20
D	10	19**	-19**	19
D	10	18**	-18**	18
D	10	17**	-17**	17
D	15	16**	-16**	16
	15	15**	-15**	15
	15	14**	-14**	14
	15	13**	-13**	13
	15	12**	-12**	12
	20	11**	-11**	11
	20	10**	-10**	10
	25	09**	-09**	9
	25	08**	-08**	8
	30	07**	-07**	7
	35	06**	-06**	6
	40	05**	-05**	5
	50	04**	-04**	4
	60	03**	-03**	3
C	70	3536202**	35362-02**	2

REVISED
EC NO: KOR2009-0123 2009/03/09
DRWN:HJEONG 2009/03/10
CH'KD:YSOOKIM 2009/03/11
APPR:YUNSIKKIM DESCRIPTION
B REV

QUALITY SYMBOLS
▼=0
C=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± 0.2	± ---
ANGULAR ± 1 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: 5:1	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: YSOOKIM DATE: 2000/12/11	TITLE: 2.0 W/B WAFER ASS'Y TUBE PACKING -LEAD FREE-		
CHECKED BY: JKOH DATE: 2000/12/11			
APPROVED BY: CWLEE DATE: 2000/12/11	molex MOLEX INCORPORATED		
MATERIAL NO.: SEE TABLE	DOCUMENT NO.: SD-35362-003	SHEET NO.: 1 OF 1	
SIZE: A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.