TOSHIBA Photocoupler GaAs Ired & Photo−Transistor


TLP521−1,TLP521−2,TLP521−4

Programmable Controllers

AC/DC−Input Module


Solid State Relay

Unit in mm




TOSHIBA 11−5B2

Weight: 0.26 g (typ.)



TOSHIBA 11−10C4

Weight: 0.54 g (typ.)



TOSHIBA 11−20A3


Weight: 1.1 g (typ.)

- Collector−emitter voltage: 55 V (min)
- Current transfer ratio: 50% (min)
  Rank GB: 100% (min)
- Isolation voltage: 2500 Vrms (min)
- UL recognized
  made in Japan: UL1577, file No. E67349
  made in Thailand: UL1577, file No. E152349

The TOSHIBA TLP521−1, −2 and −4 consist of a photo−transistor optically coupled to a gallium arsenide infrared emitting diode. The TLP521−2 offers two isolated channels in an eight lead plastic DIP package, while the TLP521−4 provides four isolated channels in a sixteen plastic DIP package.


Pin Configurations (top view)

TLP521-1




1 : Anode
2 : Cathode
3 : Emitter
4 : Collector

TLP521-2



1, 3 : Anode
2, 4 : Cathode
5, 7 : Emitter
6, 8 : Collector

TLP521-4



1, 3, 5, 7 : Anode
2, 4, 6, 8 : Cathode
9, 11, 13, 15 : Emitter
10, 12, 14, 16 : Collector

Not Recommended for New Design

Absolute Maximum Ratings (Ta = 25°C)

Characteristic		Symbol	Rating		Unit
			TLP521−1	TLP521−2 TLP521−4	
LED	Forward current	I_F	70	50	mA
	Forward current derating	ΔI_F /°C	−0.93 (Ta ≥ 50°C)	−0.5 (Ta ≥ 25°C)	mA /°C
	Pulse forward current	I_{FP}	1 (100μ pulse, 100pps)		A
	Reverse voltage	V_R	5		V
	Junction temperature	T_j	125		°C
Detector	Collector−emitter voltage	V_{CEO}	55		V
	Emitter−collector voltage	V_{ECO}	7		V
	Collector current	I_C	50		mA
	Collector power dissipation (1 circuit)	P_C	150	100	mW
	Collector power dissipation derating (1 circuit Ta ≥ 25°C)	ΔP_C /°C	−1.5	−1.0	mW /°C
	Junction temperature	T_j	125		°C
Storage temperature range		T_{stg}	−55~125		°C
Operating temperature range		T_{opr}	−55~100		°C
Lead soldering temperature		T_{sol}	260 (10 s)		°C
Total package power dissipation		P_T	250	150	mW
Total package power dissipation derating (Ta ≥ 25°C)		ΔP_T /°C	−2.5	−1.5	mW /°C
Isolation voltage		BV_S	2500 (AC, 1min., R.H.≤ 60%) (Note 1)		Vrms

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note 1: Device considered a two terminal device: LED side pins shorted together and detector side pins shorted together.

Recommended Operating Conditions

Characteristic	Symbol	Min	Typ.	Max	Unit
Supply voltage	V_{CC}	—	5	24	V
Forward current	I_F	—	16	25	mA
Collector current	I_C	—	1	10	mA
Operating temperature	T_{opr}	−25	—	85	°C

Note: Recommended operating conditions are given as a design guideline to obtain expected performance of the device. Additionally, each item is an independent guideline respectively. In developing designs using this product, please confirm specified characteristics shown in this document.

Not Recommended for New Design

Type	Classi−fication (*1)	Current Transfer Ratio (%) (I_C / I_F) I_F = 5mA, V_{CE} = 5V, Ta = 25°C		Marking Of Classification
		Min	Max	
TLP521	A	50	600	Blank, Y, Y■, G, G■, B, B■, GB
	Rank Y	50	150	Y, Y■
	Rank GR	100	300	G, G■
	Rank BL	200	600	B, B■
	Rank GB	100	600	G, G■, B, B■, GB
TLP521−2 TLP521−4	A	50	600	Blank, GR, BL, GB
	Rank GB	100	600	GR, BL, GB

*1: Ex. rank GB: TLP521−1 (GB)

(Note): Application type name for certification test, please use standard product type name, i.e.
TLP521−1 (GB): TLP521−1, TLP521−2 (GB): TLP521−2

Not Recommended for New Design

Individual Electrical Characteristics (Ta = 25°C)

	Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
LED	Forward voltage	V_F	I_F = 10 mA	1.0	1.15	1.3	V
	Reverse current	I_R	V_R = 5 V	—	—	10	μA
	Capacitance	C_T	V = 0, f = 1 MHz	—	30	—	pF
Detector	Collector−emitter breakdown voltage	$V_{(BR)\ CEO}$	I_C = 0.5 mA	55	—	—	V
	Emitter−collector breakdown voltage	$V_{(BR)\ ECO}$	I_E = 0.1 mA	7	—	—	V
	Collector dark current	I_{CEO}	V_{CE} = 24 V	—	10	100	nA
			V_{CE} = 24 V, Ta = 85°C	—	2	50	μA
	Capacitance (collector to emitter)	C_{CE}	V = 0, f = 1 MHz	—	10	—	pF

Coupled Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Condition	MIn	Typ.	Max	Unit
Current transfer ratio	I_C / I_F	I_F = 5 mA, V_{CE} = 5 V	50	—	600	%
		Rank GB	100	—	600	
Saturated CTR	I_C / $I_{F\ (sat)}$	IF = 1 mA, V_{CE} = 0.4 V	—	60	—	%
		Rank GB	30	—	—	
Collector−emitter saturation voltage	$V_{CE\ (sat)}$	I_C = 2.4 mA, I_F = 8 mA	—	—	0.4	V
		I_C = 0.2 mA, I_F = 1 mA	—	0.2	—	
		Rank GB	—	—	0.4	

Isolation Characteristics (Ta = 25°C)


Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
Capacitance (input to output)	C_S	V_S = 0, f = 1 MHz	—	0.8	—	pF
Isolation resistance	R_S	V_S = 500 V, R.H.≤ 60%	—	10^{11}	—	Ω
Isolation voltage	BV_S	AC, 1 minute	2500	—	—	Vrms
		AC, 1 second, in oil	—	5000	—	
		DC, 1 minute, in oil	—	5000	—	Vdc

Not Recommended for New Design

Switching Characteristics (Ta = 25°C)


Characteristic	Symbol	Test Condition	Min	Typ.	Max	Unit
Rise time	t_r	V_{CC} = 10 V I_C = 2 mA R_L = 100Ω	—	2	—	μs
Fall time	t_f		—	3	—	
Turn−on time	t_{on}		—	3	—	
Turn−off time	t_{off}		—	3	—	
Turn−on time	t_{ON}	R_L = 1.9 kΩ (Fig.1) V_{CC} = 5 V, I_F = 16 mA	—	2	—	μs
Storage time	t_s		—	15	—	
Turn−off time	t_{OFF}		—	25	—	

Fig.1 : SWITCHING TIME TEST CIRCUIT




Not Recommended for New Design


TLP521-1 I_F – Ta




TLP521-2
TLP521-4 I_F – Ta




TLP521-1 P_C – Ta




TLP521-2
TLP521-4 P_C – Ta



TLP521-1 I_{FP} – D_R




TLP521-2
TLP521-4 I_{FP} – D_R




Not Recommended for New Design


$I_F - V_F$




$\Delta V_F/\Delta Ta - I_F$




$I_{FP} - V_{FP}$




$I_{CEO} - Ta$



$I_C - V_{CE}$




$I_C - V_{CE}$




Not Recommended for New Design


$I_C - I_F$




$I_C/I_F - I_F$




$V_{CE(sat)} - Ta$



$I_C - Ta$



R_L – Switching Time



Not Recommended for New Design

RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively “TOSHIBA”), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively “Product”) without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA’s written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product’s quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before creating and producing designs and using, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the “TOSHIBA Semiconductor Reliability Handbook” and (b) the instructions for the application that Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS’ PRODUCT DESIGN OR APPLICATIONS.**
- Product is intended for use in general electronics applications (e.g., computers, personal equipment, office equipment, measuring equipment, industrial robots and home electronics appliances) or for specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems that require extraordinarily high levels of quality and/or reliability and/or a malfunction or failure of which may cause loss of human life, bodily injury, serious property damage or serious public impact (“Unintended Use”). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. Do not use Product for Unintended Use unless specifically permitted in this document.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- GaAs (Gallium Arsenide) is used in Product. GaAs is harmful to humans if consumed or absorbed, whether in the form of dust or vapor. Handle with care and do not break, cut, crush, grind, dissolve chemically or otherwise expose GaAs in Product.
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.

Not Recommended for New Design


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.