National Semiconductor

July 1998

DS36954
Quad Differential Bus Transceiver

General Description

The DS36954 is a low power, quad EIA-485 differential bus transceiver especially suited for high speed, parallel, multipoint, I/O bus applications. A compact 20-pin surface mount PLCC or SOIC package provides high transceiver integration and a very small PC board footprint.


Propagation delay skew between devices is specified to aid in parallel interface designs — limits on maximum and minimum delay times are guaranteed.

Five devices can implement a complete SCSI initiator or target interface. Three transceivers in a package are pinned out for data bus connections. The fourth transceiver, with the flexibility provided by its individual enables, can serve as a control bus transceiver.

Features


- Pinout for SCSI interface
- Compact 20-pin PLCC or SOIC package
- Meets EIA-485 standard for multipoint bus transmission
- Greater than 60 mA source/sink currents
- Thermal shutdown protection
- Glitch-free driver outputs on power up and down

Connection Diagrams



DS011014-1


Order Number DS36954V
See NS Package Number V20A



DS011014-19

Order Number DS36954M
See NS Package Number M20B

Logic Diagrams



DS011014-2

TRI-STATE® is a registered trademark of National Semiconductor Corporation.

© 1999 National Semiconductor Corporation

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Supply Voltage	7V
Control Input Voltage	V_{CC} + 0.5V
Driver Input Voltage	V_{CC} + 0.5V
Driver Output Voltage/ Receiver Input Voltage	−10V to +15V
Receiver Output Voltage	5.5V
Continuous Power Dissipation @ +25˚C	
V Package	1.73W
M Package	1.73W
Derate V Package	13.9 mW/˚C above +25˚C
Derate M Package	13.7 mW/˚C above +25˚C
Storage Temperature Range	−65˚C to +150˚C
Lead Temperature (Soldering 4 Sec.)	260˚C

Recommended Operating Conditions

	Min	Max	Units
Supply Voltage, V_{CC}	4.75	5.25	V
Bus Voltage	−7	+12	V
Operating Free Air Temperature (T_A)	0	+70	˚C

Electrical Characteristics (Note 2)

Over Supply Voltage and Operating Temperature ranges, unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Units
DRIVER CHARACTERISTICS						
V_{ODL}	Differential Driver Output Voltage (Full Load)	I_L = 60 mA, V_{CM} = 0V	1.5	1.9		V
V_{OD}	Differential Driver Output Voltage (Termination Load)	R_L = 100Ω (EIA-422)	2.0	2.25		V
		R_L = 54Ω (EIA-485)	1.5	2.0		V
ΔIVODI	Change in Magnitude of Driver Differential Output Voltage for Complementary Output States	R_L = 54 or 100Ω (Note 4) *(Figure 1)* (EIA-422/485)			0.2	V
V_{OC}	Driver Common Mode Output Voltage (Note 5)	R_L = 54Ω *(Figure 1)* (EIA-485)			3.0	V
ΔIVOCI	Change in Magnitude of Common Mode Output Voltage	(Note 4) *(Figure 1)* (EIA-422/485)			0.2	V
V_{OH}	Output Voltage High	I_{OH} = −55 mA	2.7	3.2		V
V_{OL}	Output Voltage Low	I_{OL} = 55 mA		1.4	1.7	V
V_{IH}	Input Voltage High		2.0			V
V_{IL}	Input Voltage Low				0.8	V
V_{CL}	Input Clamp Voltage	I_{CL} = −18 mA			−1.5	V
I_{IH}	Input High Current	V_{IN} = 2.4V (Note 3)			20	µA
I_{IL}	Input Low Current	V_{IN} = 0.4V (Note 3)			−20	µA
I_{OSC}	Driver Short-Circuit Output Current (Note 9)	V_O = −7V (EIA-485)		−130	−250	mA
		V_O = 0V (EIA-422)		−90	−150	mA
		V_O = +12V (EIA-485)		130	250	mA
RECEIVER CHARACTERISTICS						
I_{OSR}	Short Circuit Output Current	V_O = 0V (Note 9)	−15	−28	−75	mA
I_{OZ}	TRI-STATE® Output Current	V_O = 0.4V to 2.4V			20	µA
V_{OH}	Output Voltage High	V_{ID} = 0.2V, I_{OH} = 0.4 mA	2.4	3.0		V
V_{OL}	Output Voltage Low	V_{ID} = −0.2V, I_{OL} = 4 mA		0.35	0.5	V
V_{TH}	Differential Input High Threshold Voltage	V_O = V_{OH}, I_O = −0.4 mA (EIA-422/485)		0.03	0.2	V
V_{TL}	Differential Input Low Threshold Voltage (Note 6)	V_O = V_{OL}, I_O = 4.0 mA (EIA-422/485)	−0.20	−0.03		V
V_{HST}	Hysteresis (Note 7)	V_{CM} = 0V	35	60		mV
DRIVER AND RECEIVER CHARACTERISTICS						
V_{IH}	Enable Input Voltage High		2.0			V
V_{IL}	Enable Input Voltage Low				0.8	V

Electrical Characteristics (Note 2) (Continued)

Over Supply Voltage and Operating Temperature ranges, unless otherwise specified

Symbol	Parameter	Conditions		Min	Typ	Max	Units
DRIVER AND RECEIVER CHARACTERISTICS							
V_{CL}	Enable Input Clamp Voltage	I_{CL} = −18 mA				−1.5	V
I_{IN}	Line Input Current (Note 8)	Other Input = 0V, DE/$\overline{RE}$ = 0.8V, DE4 = 0.8V	V_I = +12V		0.5	1.0	mA
			V_I = −7V		−0.45	−0.8	mA
I_{ING}	Line Input Current (Note 8)	Other Input = 0V, DE/$\overline{RE}$ and DE4 = 2V	V_I = +12V			1.0	mA
		V_{CC} = 3.0V, T_A = +25˚C	V_I = −7V			−0.8	mA
I_{IH}	Enable Input Current High	V_{IN} = 2.4V, DE/$\overline{RE}$	V_{CC} = 3.0V		1	40	µA
			V_{CC} = 4.75V		1		µA
			V_{CC} = 5.25V		1	40	µA
		V_{IN} = 2.4V, DE4 or $\overline{RE4}$	V_{CC} = 3.0V		1	20	µA
			V_{CC} = 5.25V		1	20	µA
I_{IL}	Enable Input Current Low	V_{IN} = 0.8V, DE/$\overline{RE}$	V_{CC} = 3.0V		−6	−40	µA
			V_{CC} = 4.75V		−12		µA
			V_{CC} = 5.25V		−14	−40	µA
		V_{IN} = 0.8V, DE4 or $\overline{RE4}$	V_{CC} = 3.0V		−3	−20	µA
			V_{CC} = 5.25V		−7	−20	µA
I_{CCD}	Supply Current (Note 10)	No Load, DE/$\overline{RE}$ and DE4 = 2.0V			75	90	mA
I_{CCR}	Supply Current (Note 10)	No Load, DE/$\overline{RE}$ and $\overline{RE4}$ = 0.8V			50	70	mA

Switching Characteristics

Over Supply Voltage and Operating Temperature ranges, unless otherwise specified.

Symbol	Parameter	Conditions		Min	Typ	Max	Units
DRIVER SINGLE-ENDED CHARACTERISTICS							
t_{PZH}	Output Enable Time to High Level	R_L = 110Ω	(*Figure 5*)		35	40	ns
t_{PZL}	Output Enable Time to Low Level		(*Figure 6*)		25	40	ns
t_{PHZ}	Output Disable Time to High Level		(*Figure 5*)		15	25	ns
t_{PLZ}	Output Disable Time to Low Level		(*Figure 6*)		35	40	ns
DRIVER DIFFERENTIAL CHARACTERISTICS							
t_r, t_f	Rise and Fall Time	R_L = 54Ω			13	16	ns
t_{PLHD}	Differential Propagation	C_L = 50 pF		9	15	19	ns
t_{PHLD}	Delays (Note 15)	C_D = 15 pF		9	12	19	ns
t_{SKD}	$\lvert t_{PLHD} - t_{PHLD} \rvert$ Diff. Skew	(*Figures 3, 4, 9*)			3	6	ns
RECEIVER CHARACTERISTICS							
t_{PLHD}	Differential Propagation Delays	C_L = 15 pF		9	14	19	ns
t_{PHLD}		V_{CM} = 2.0V		9	13	19	ns
t_{SKD}	$\lvert t_{PLHD} - t_{PHLD} \rvert$ Diff. Receiver Skew	(*Figure 7*)			1	3	ns
t_{PZH}	Output Enable Time to High Level	C_L = 15 pF			15	22	ns
t_{PZL}	Output Enable Time to Low Level	(*Figure 8*)			20	30	ns
t_{PHZ}	Output Disable Time from High Level				20	30	ns
t_{PLZ}	Output Disable Time from Low Level				17	25	ns

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The tables of "Electrical Characteristics" specify conditions for device operation.

Note 2: Current into device pins is defined as positive. Current out of device pins is defined as negative. All voltages are referenced to ground unless otherwise specified.

Note 3: I_{IH} and I_{IL} include driver input current and receiver TRI-STATE leakage current on DR(1–3).

Note 4: Δ IVODI and Δ IVOCI are changes in magnitude of V_{OD} and V_{OC}, respectively, that occur when the input changes state.

Switching Characteristics (Continued)

Note 5: In EIA Standards EIA-422 and EIA-485, V_{OC}, which is the average of the two output voltages with respect to ground, is called output offset voltage, V_{OS} .

Note 6: Threshold parameter limits specified as an algebraic value rather than by magnitude.

Note 7: Hysteresis defined as $V_{HST} = V_{TH} - V_{TL}$.

Note 8: I_{IN} includes the receiver input current and driver TRI-STATE leakage current.

Note 9: Short one output at a time.

Note 10: Total package supply current.

Note 11: All typicals are given for V_{CC} = 5.0V and T_A = +25˚C.

Parameter Measurement Information




FIGURE 1. Driver V_{OD} and V_{OC} (Note 13)




FIGURE 3. Driver Differential Propagation Delay Load Circuit




FIGURE 2. Receiver V_{OH} and V_{OL}





FIGURE 4. Driver Differential Propagation Delays and Transition Times



S1 to OA for DI = 3V
S1 to OB for DI = 0V






FIGURE 5. Driver Enable and Disable Timing (t_{PZH}, t_{PHZ})


Parameter Measurement Information (Continued)





S1 to OA for DI = 0V
S1 to OB for DI = 3V

FIGURE 6. Driver Enable and Disable Timing (t_{PZL}, t_{PLZ})









FIGURE 7. Receiver Differential Propagation Delay Timing

Parameter Measurement Information (Continued)







S1 1.5V
S2 Open
S3 Closed



S1 −1.5V
S2 Closed
C3 Open




S1 1.5V
S2 Closed
C3 Closed



S1 −1.5V
S2 Closed
C3 Closed

FIGURE 8. Receiver Enable and Disable Timing



$$T_{CP} = \frac{(T_{fb} \times T_{rb}) - (T_{ra} \times T_{fa})}{T_{rb} - T_{ra} - T_{fa} + T_{fb}}$$

T_{ra}, T_{rb}, T_{fa} and T_{fb} are propagation delay measurements to the 20% and 80% levels.
T_{CP} = Crossing Point

FIGURE 9. Propagation Delay Timing for Calculations of Driver Differential Propagation Delays

Note 12: The input pulse is supplied by a generator having the following characteristics: f = 1.0 MHz, 50% duty cycle, $t_r$and t_f < 6.0 ns, Z_O = 50Ω.


Note 13: C_L includes probe and stray capacitance.

Note 14: Diodes are 1N916 or equivalent.


Note 15: Differential propagation delays are calculated from single-ended propagation delays measured from driver input to the 20% and 80% levels on the driver outputs (*Figure 9*) .

Parameter Measurement Information (Continued)


Note 16: On transceivers 1–3 the driver is loaded with receiver input conditions when DE/$\overline{RE}$ is high. Do not exceed the package power dissipation limit when testing.



Physical Dimensions inches (millimeters) unless otherwise noted



Order Number DS36954M
NS Package Number M20B



Order Number DS36954V
NS Package Number V20A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com

www.national.com

National Semiconductor Europe
Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 1 80-530 85 85
English Tel: +49 (0) 1 80-532 78 32
Français Tel: +49 (0) 1 80-532 93 58
Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group
Tel: 65-2544466
Fax: 65-2504466
Email: sea.support@nsc.com

National Semiconductor Japan Ltd.
Tel: 81-3-5639-7560
Fax: 81-3-5639-7507

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.