NTS0104

Dual supply translating transceiver; open drain; auto direction sensing

Rev. 2 — 27 April 2011 Product data sheet

1. General description

The NTS0104 is a 4-bit, dual supply translating transceiver with auto direction sensing, that enables bidirectional voltage level translation. It features two 4-bit input-output ports (An and Bn), one output enable input (OE) and two supply pins ($V_{CC(A)}$ and $V_{CC(B)}$). $V_{CC(A)}$ can be supplied at any voltage between 1.65 V and 3.6 V and $V_{CC(B)}$ can be supplied at any voltage between 2.3 V and 5.5 V, making the device suitable for translating between any of the voltage nodes (1.8 V, 2.5 V, 3.3 V and 5.0 V). Pins An and OE are referenced to $V_{CC(A)}$ and pins Bn are referenced to $V_{CC(B)}$. A LOW level at pin OE causes the outputs to assume a high-impedance OFF-state. This device is fully specified for partial power-down applications using I_{OFF}. The I_{OFF} circuitry disables the output, preventing the damaging backflow current through the device when it is powered down.

2. Features and benefits

- Wide supply voltage range:
  - $V_{CC(A)}$: 1.65 V to 3.6 V and $V_{CC(B)}$: 2.3 V to 5.5 V
- Maximum data rates:
  - Push-pull: 50 Mbps
- I_{OFF} circuitry provides partial Power-down mode operation
- Inputs accept voltages up to 5.5 V
- ESD protection:
  - HBM JESD22-A114E Class 2 exceeds 2500 V for A port
  - HBM JESD22-A114E Class 3B exceeds 8000 V for B port
  - MM JESD22-A115-A exceeds 200 V
  - CDM JESD22-C101E exceeds 1500 V
  - IEC61000-4-2 contact discharge exceeds 8000 V for B port
- Latch-up performance exceeds 100 mA per JESD 78B Class II
- Multiple package options
- Specified from −40 °C to +85 °C and −40 °C to +125 °C

3. Applications

- I^2C/SMBus
- UART
- GPIO

4. Ordering information

Table 1. Ordering information

Type number	Package			
	Temperature range	Name	Description	Version
NTS0104D	−40 °C to +125 °C	SO14	plastic small outline package; 14 leads; body width 3.9 mm	SOT108-1
NTS0104PW	−40 °C to +125 °C	TSSOP14	plastic thin shrink small outline package; 14 leads; body width 4.4 mm	SOT402-1
NTS0104BQ	−40 °C to +125 °C	DHVQFN14	plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 × 3 × 0.85 mm	SOT762-1
NTS0104GU16	−40 °C to +125 °C	XQFN16	plastic, extremely thin quad flat package; no leads; 16 terminals; body 1.80 × 2.60 × 0.50 mm	SOT1161-1
NTS0104GU12	−40 °C to +125 °C	XQFN12	plastic, extremely thin quad flat package; no leads; 12 terminals; body 1.70 × 2.0 × 0.50 mm	SOT1174-1

5. Marking

Table 2. Marking

Type number	Marking code
NTS0104D	NTS0104D
NTS0104PW	NTS0104
NTS0104BQ	S0104
NTS0104GU16	s4
NTS0104GU12	s4

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

6. Functional diagram




Fig 1. Logic symbol

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

7. Pinning information

7.1 Pinning






Fig 2. Pin configuration SO14 (SOT108-1) and TSSOP14 (SOT402-1)



Transparent top view


(1) This is not a supply pin, the substrate is attached to this pad using conductive die attach material. There is no electrical or mechanical requirement to solder this pad however if it is soldered the solder land should remain floating or be connected to GND.

Fig 3. Pin configuration DHVQFN14 (SOT762-1)



Transparent top view

Fig 4. Pin configuration XQFN16 (SOT1161-1)



Transparent top view

Fig 5. Pin configuration XQFN12 (SOT1174-1)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

7.2 Pin description

Table 3. Pin description

Symbol	Pin			Description
	SOT108-1, SOT402-1 and SOT762-1	SOT1161-1	SOT1174-1	
$V_{CC(A)}$	1	16	1	supply voltage A
A1, A2, A3, A4	2, 3, 4, 5	1, 2, 3, 4	2, 3, 4, 5	data input or output (referenced to $V_{CC(A)}$)
n.c.	6, 9	5, 14, 15	-	not connected
GND	7	6, 7	6	ground (0 V)
OE	8	8	12	output enable input (active HIGH; referenced to $V_{CC(A)}$)
B4, B3, B2, B1	10, 11, 12, 13	9, 10, 11, 12	7, 8, 9, 10	data input or output (referenced to $V_{CC(B)}$)
$V_{CC(B)}$	14	13	11	supply voltage B

8. Functional description

Table 4. Function table[1]

Supply voltage		Input	Input/output	
$V_{CC(A)}$	$V_{CC(B)}$	OE	An	Bn
1.65 V to $V_{CC(B)}$	2.3 V to 5.5 V	L	Z	Z
1.65 V to $V_{CC(B)}$	2.3 V to 5.5 V	H	input or output	output or input
GND[2]	GND[2]	X	Z	Z

[1] H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

[2] When either $V_{CC(A)}$ or $V_{CC(B)}$ is at GND level, the device goes into power-down mode.

9. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		Min	Max	Unit
$V_{CC(A)}$	supply voltage A			−0.5	+6.5	V
$V_{CC(B)}$	supply voltage B			−0.5	+6.5	V
V_I	input voltage	A port and OE input	[1][2]	−0.5	+6.5	V
		B port	[1][2]	−0.5	+6.5	V
V_O	output voltage	Active mode	[1][2]			
		A or B port		−0.5	V_{CCO} + 0.5	V
		Power-down or 3-state mode	[1]			
		A port		−0.5	+4.6	V
		B port		−0.5	+6.5	V
I_{IK}	input clamping current	V_I < 0 V		−50	-	mA
I_{OK}	output clamping current	V_O < 0 V		−50	-	mA
I_O	output current	V_O = 0 V to V_{CCO}	[2]	-	±50	mA
I_{CC}	supply current	$I_{CC(A)}$ or $I_{CC(B)}$		-	100	mA

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 5. Limiting values *...continued*

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		Min	Max	Unit
I_{GND}	ground current			−100	-	mA
T_{stg}	storage temperature			−65	+150	°C
P_{tot}	total power dissipation	T_{amb} = −40 °C to +125 °C	[3]	-	250	mW

[1] The minimum input and minimum output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] V_{CCO} is the supply voltage associated with the output.

[3] For SO14 packages: above 70 °C the value of P_{tot} derates linearly at 8 mW/K.
For TSSOP14 packages: above 60 °C the value of P_{tot} derates linearly at 5.5 mW/K.
For DHVQFN14 packages: above 60 °C the value of P_{tot} derates linearly at 4.5 mW/K.
For XQFN12 packages: above 128 °C the value of P_{tot} derates linearly with 11.5 mW/K.
For XQFN16 packages: above 135 the value of P_{tot} derates linearly at 16.9 mW/K.

10. Recommended operating conditions

Table 6. Recommended operating conditions[1][2]

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{CC(A)}$	supply voltage A		1.65	3.6	V
$V_{CC(B)}$	supply voltage B		2.3	5.5	V
T_{amb}	ambient temperature		−40	+125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	A or B port; push-pull driving			
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	-	10	ns/V
		OE input			
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	-	10	ns/V

[1] The A and B sides of an unused I/O pair must be held in the same state, both at V_{CCI} or both at GND.

[2] $V_{CC(A)}$ must be less than or equal to $V_{CC(B)}$.

11. Static characteristics

Table 7. Typical static characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); T_{amb} = 25 °C.

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
I_I	input leakage current	OE input; V_I = 0 V to 3.6 V; $V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	-	±1	µA
I_{OZ}	OFF-state output current	A or B port; V_O = 0 V or V_{CCO}; $V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[1]	-	-	±1	µA
I_{OFF}	power-off leakage current	A port; V_I or V_O = 0 V to 3.6 V; $V_{CC(A)}$ = 0 V; $V_{CC(B)}$ = 0 V to 5.5 V		-	-	±1	µA
		B port; V_I or V_O = 0 V to 5.5 V; $V_{CC(B)}$ = 0 V; $V_{CC(A)}$ = 0 V to 3.6 V		-	-	±1	µA
C_I	input capacitance	OE input; $V_{CC(A)}$ = 3.3 V; $V_{CC(B)}$ = 3.3 V		-	2	-	pF

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 7. Typical static characteristics *...continued*

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); T_{amb} = 25 °C.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$C_{I/O}$	input/output capacitance	A port	-	4	-	pF
		B port	-	7	-	pF
		A or B port; $V_{CC(A)}$ = 3.3 V; $V_{CC(B)}$ = 3.3 V	-	9	-	pF

[1] V_{CCO} is the supply voltage associated with the output.

Table 8. Typical supply current

At recommended operating conditions; voltages are referenced to GND (ground = 0 V); T_{amb} = 25 °C.

$V_{CC(A)}$	$V_{CC(B)}$						Unit
	2.5 V		3.3 V		5.0 V		
	$I_{CC(A)}$	$I_{CC(B)}$	$I_{CC(A)}$	$I_{CC(B)}$	$I_{CC(A)}$	$I_{CC(B)}$	
1.8 V	0.1	0.5	0.1	1.5	0.1	4.6	µA
2.5 V	0.1	0.1	0.1	0.8	0.1	3.8	µA
3.3 V	-	-	0.1	0.1	0.1	2.8	µA

Table 9. Static characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		–40 °C to +85 °C		–40 °C to +125 °C		Unit
				Min	Max	Min	Max	
V_{IH}	HIGH-level input voltage	A port						
		$V_{CC(A)}$ = 1.65 V to 1.95 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[1]	V_{CCI} – 0.2	-	V_{CCI} – 0.2	-	V
		$V_{CC(A)}$ = 2.3 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[1]	V_{CCI} – 0.4	-	V_{CCI} – 0.4	-	V
		B port						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[1]	V_{CCI} – 0.4	-	V_{CCI} – 0.4	-	V
		OE input						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		$0.65V_{CC(A)}$	-	$0.65V_{CC(A)}$	-	V
V_{IL}	LOW-level input voltage	A or B port						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	0.15	-	0.15	V
		OE input						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	$0.35V_{CC(A)}$	-	$0.35V_{CC(A)}$	V
V_{OH}	HIGH-level output voltage	A or B port; I_O = –20 µA						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[2]	$0.67V_{CCO}$	-	$0.67V_{CCO}$	-	V
V_{OL}	LOW-level output voltage	A or B port; I_O = 1 mA	[2]					
		$V_I \leq 0.15$ V; $V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	0.4	-	0.4	V

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 9. Static characteristics *...continued*

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		–40 °C to +85 °C		–40 °C to +125 °C		Unit
				Min	Max	Min	Max	
I_I	input leakage current	OE input; V_I = 0 V to 3.6 V; $V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	±2	-	±12	µA
I_{OZ}	OFF-state output current	A or B port; V_O = 0 V or V_{CCO}; $V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V	[2]	-	±2	-	±12	µA
I_{OFF}	power-off leakage current	A port; V_I or V_O = 0 V to 3.6 V; $V_{CC(A)}$ = 0 V; $V_{CC(B)}$ = 0 V to 5.5 V		-	±2	-	±12	µA
		B port; V_I or V_O = 0 V to 3.6 V; $V_{CC(B)}$ = 0 V; $V_{CC(A)}$ = 0 V to 3.6 V		-	±2	-	±12	µA
I_{CC}	supply current	V_I = 0 V or V_{CCI}; I_O = 0 A	[1]					
		$I_{CC(A)}$						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	2.4	-	15	µA
		$V_{CC(A)}$ = 3.6 V; $V_{CC(B)}$ = 0 V		-	2.2	-	15	µA
		$V_{CC(A)}$ = 0 V; $V_{CC(B)}$ = 5.5 V		-	–1	-	–8	µA
		$I_{CC(B)}$						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	12	-	30	µA
		$V_{CC(A)}$ = 3.6 V; $V_{CC(B)}$ = 0 V		-	–1	-	–5	µA
		$V_{CC(A)}$ = 0 V; $V_{CC(B)}$ = 5.5 V		-	1	-	6	µA
		$I_{CC(A)} + I_{CC(B)}$						
		$V_{CC(A)}$ = 1.65 V to 3.6 V; $V_{CC(B)}$ = 2.3 V to 5.5 V		-	14.4	-	45	µA

[1] V_{CCI} is the supply voltage associated with the input.

[2] V_{CCO} is the supply voltage associated with the output.

12. Dynamic characteristics

Table 10. Dynamic characteristics for temperature range –40 °C to +85 °C[1]

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.

Symbol	Parameter	Conditions	$V_{CC(B)}$						Unit
			2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
			Min	Max	Min	Max	Min	Max	
$V_{CC(A)}$ = 1.8 V ± 0.15 V									
t_{PHL}	HIGH to LOW propagation delay	A to B	-	4.6	-	4.7	-	5.8	ns
t_{PLH}	LOW to HIGH propagation delay	A to B	-	6.8	-	6.8	-	7.0	ns
t_{PHL}	HIGH to LOW propagation delay	B to A	-	4.4	-	4.5	-	4.7	ns
t_{PLH}	LOW to HIGH propagation delay	B to A	-	5.3	-	4.5	-	0.5	ns

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 10. Dynamic characteristics for temperature range −40 °C to +85 °C[1]

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.

Symbol	Parameter	Conditions		$V_{CC(B)}$						Unit
				2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
				Min	Max	Min	Max	Min	Max	
t_{en}	enable time	OE to A; B		-	200	-	200	-	200	ns
t_{dis}	disable time	OE to A; no external load	[2]	-	35	-	35	-	35	ns
		OE to B; no external load	[2]	-	35	-	35	-	35	ns
		OE to A		-	230	-	230	-	230	ns
		OE to B		-	200	-	200	-	200	ns
t_{TLH}	LOW to HIGH output transition time	A port		3.2	9.5	2.3	9.3	1.8	7.6	ns
		B port		3.3	10.8	2.7	9.1	2.7	7.6	ns
t_{THL}	HIGH to LOW output transition time	A port		2.0	5.9	1.9	6.0	1.7	13.3	ns
		B port		2.9	7.6	2.8	7.5	2.8	10.0	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	0.7	-	0.7	-	0.7	ns
t_W	pulse width	data inputs		20	-	20	-	20	-	ns
f_{data}	data rate			-	50	-	50	-	50	Mbps
$V_{CC(A)}$ = 2.5 V ± 0.2 V										
t_{PHL}	HIGH to LOW propagation delay	A to B		-	3.2	-	3.3	-	3.4	ns
t_{PLH}	LOW to HIGH propagation delay	A to B		-	3.5	-	4.1	-	4.4	ns
t_{PHL}	HIGH to LOW propagation delay	B to A		-	3.0	-	3.6	-	4.3	ns
t_{PLH}	LOW to HIGH propagation delay	B to A		-	2.5	-	1.6	-	0.7	ns
t_{en}	enable time	OE to A; B		-	200	-	200	-	200	ns
t_{dis}	disable time	OE to A; no external load	[2]	-	35	-	35	-	35	ns
		OE to B; no external load	[2]	-	35	-	35	-	35	ns
		OE to A		-	200	-	200	-	200	ns
		OE to B		-	200	-	200	-	200	ns
t_{TLH}	LOW to HIGH output transition time	A port		2.8	7.4	2.6	6.6	1.8	6.2	ns
		B port		3.2	8.3	2.9	7.9	2.4	6.8	ns
t_{THL}	HIGH to LOW output transition time	A port		1.9	5.7	1.9	5.5	1.8	5.3	ns
		B port		2.2	7.8	2.4	6.7	2.6	6.6	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	0.7	-	0.7	-	0.7	ns
t_W	pulse width	data inputs		20	-	20	-	20	-	ns
f_{data}	data rate			-	50	-	50	-	50	Mbps
$V_{CC(A)}$ = 3.3 V ± 0.3 V										
t_{PHL}	HIGH to LOW propagation delay	A to B		-	-	-	2.4	-	3.1	ns
t_{PLH}	LOW to HIGH propagation delay	A to B		-	-	-	4.2	-	4.4	ns

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 10. Dynamic characteristics for temperature range −40 °C to +85 °C[1]

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.

Symbol	Parameter	Conditions		$V_{CC(B)}$						Unit
				2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
				Min	Max	Min	Max	Min	Max	
t_{PHL}	HIGH to LOW propagation delay	B to A		-	-	-	2.5	-	3.3	ns
t_{PLH}	LOW to HIGH propagation delay	B to A		-	-	-	2.5	-	2.6	ns
t_{en}	enable time	OE to A; B		-	-	-	200	-	200	ns
t_{dis}	disable time	OE to A; no external load	[2]	-	-	-	35	-	35	ns
		OE to B; no external load	[2]	-	-	-	35	-	35	ns
		OE to A		-	-	-	260	-	260	ns
		OE to B		-	-	-	200	-	200	ns
t_{TLH}	LOW to HIGH output transition time	A port		-	-	2.3	5.6	1.9	5.9	ns
		B port		-	-	2.5	6.4	2.1	7.4	ns
t_{THL}	HIGH to LOW output transition time	A port		-	-	2.0	5.4	1.9	5.0	ns
		B port		-	-	2.3	7.4	2.4	7.6	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	-	-	0.7	-	0.7	ns
t_W	pulse width	data inputs		-	-	20	-	20	-	ns
f_{data}	data rate			-	-	-	50	-	50	Mbps

[1] t_{en} is the same as t_{PZL} and t_{PZH}.
t_{dis} is the same as t_{PLZ} and t_{PHZ}.

[2] Delay between OE going LOW and when the outputs are actually disabled.

[3] Skew between any two outputs of the same package switching in the same direction.

Table 11. Dynamic characteristics for temperature range −40 °C to +125 °C[1]

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.

Symbol	Parameter	Conditions	$V_{CC(B)}$						Unit
			2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
			Min	Max	Min	Max	Min	Max	
$V_{CC(A)}$ = 1.8 V ± 0.15 V									
t_{PHL}	HIGH to LOW propagation delay	A to B	-	5.8	-	5.9	-	7.3	ns
t_{PLH}	LOW to HIGH propagation delay	A to B	-	8.5	-	8.5	-	8.8	ns
t_{PHL}	HIGH to LOW propagation delay	B to A	-	5.5	-	5.7	-	5.9	ns
t_{PLH}	LOW to HIGH propagation delay	B to A	-	6.7	-	5.7	-	0.7	ns
t_{en}	enable time	OE to A; B	-	200	-	200	-	200	ns

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 11. Dynamic characteristics for temperature range −40 °C to +125 °C[1] …continued

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.

Symbol	Parameter	Conditions		$V_{CC(B)}$						Unit
				2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
				Min	Max	Min	Max	Min	Max	
t_{dis}	disable time	OE to A; no external load	[2]	-	45	-	45	-	45	ns
		OE to B; no external load	[2]	-	45	-	45	-	45	ns
		OE to A		-	250	-	250	-	250	ns
		OE to B		-	220	-	220	-	220	ns
t_{TLH}	LOW to HIGH output transition time	A port		3.2	11.9	2.3	11.7	1.8	9.5	ns
		B port		3.3	13.5	2.7	11.4	2.7	9.5	ns
t_{THL}	HIGH to LOW output transition time	A port		2.0	7.4	1.9	7.5	1.7	16.7	ns
		B port		2.9	9.5	2.8	9.4	2.8	12.5	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	0.8	-	0.8	-	0.8	ns
t_W	pulse width	data inputs		20	-	20	-	20	-	ns
f_{data}	data rate			-	50	-	50	-	50	Mbps
$V_{CC(A)}$ = 2.5 V ± 0.2 V										
t_{PHL}	HIGH to LOW propagation delay	A to B		-	4.0	-	4.2	-	4.3	ns
t_{PLH}	LOW to HIGH propagation delay	A to B		-	4.4	-	5.2	-	5.5	ns
t_{PHL}	HIGH to LOW propagation delay	B to A		-	3.8	-	4.5	-	5.4	ns
t_{PLH}	LOW to HIGH propagation delay	B to A		-	3.2	-	2.0	-	0.9	ns
t_{en}	enable time	OE to A; B		-	200	-	200	-	200	ns
t_{dis}	disable time	OE to A; no external load	[2]	-	45	-	45	-	45	ns
		OE to B; no external load	[2]	-	45	-	45	-	45	ns
		OE to A		-	220	-	220	-	220	ns
		OE to B		-	220	-	220	-	220	ns
t_{TLH}	LOW to HIGH output transition time	A port		2.8	9.3	2.6	8.3	1.8	7.8	ns
		B port		3.2	10.4	2.9	9.7	2.4	8.3	ns
t_{THL}	HIGH to LOW output transition time	A port		1.9	7.2	1.9	6.9	1.8	6.7	ns
		B port		2.2	9.8	2.4	8.4	2.6	8.3	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	0.8	-	0.8	-	0.8	ns
t_W	pulse width	data inputs		20	-	20	-	20	-	ns
f_{data}	data rate			-	50	-	50	-	50	Mbps
$V_{CC(A)}$ = 3.3 V ± 0.3 V										
t_{PHL}	HIGH to LOW propagation delay	A to B		-	-	-	3.0	-	3.9	ns
t_{PLH}	LOW to HIGH propagation delay	A to B		-	-	-	5.3	-	5.5	ns

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Table 11. Dynamic characteristics for temperature range −40 °C to +125 °C[1] …continued

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 8; for wave forms see Figure 6 and Figure 7.


Symbol	Parameter	Conditions		$V_{CC(B)}$						Unit
				2.5 V ± 0.2 V		3.3 V ± 0.3 V		5.0 V ± 0.5 V		
				Min	Max	Min	Max	Min	Max	
t_{PHL}	HIGH to LOW propagation delay	B to A		-	-	-	3.2	-	4.2	ns
t_{PLH}	LOW to HIGH propagation delay	B to A		-	-	-	3.2	-	3.3	ns
t_{en}	enable time	OE to A; B		-	-	-	200	-	200	ns
t_{dis}	disable time	OE to A; no external load	[2]	-	-	-	45	-	45	ns
		OE to B; no external load	[2]	-	-	-	45	-	45	ns
		OE to A		-	-	-	280	-	280	ns
		OE to B		-	-	-	220	-	220	ns
t_{TLH}	LOW to HIGH output transition time	A port		-	-	2.3	7.0	1.9	7.4	ns
		B port		-	-	2.5	8.0	2.1	9.3	ns
t_{THL}	HIGH to LOW output transition time	A port		-	-	2.0	6.8	1.9	6.3	ns
		B port		-	-	2.3	9.3	2.4	9.5	ns
$t_{sk(o)}$	output skew time	between channels	[3]	-	-	-	0.8	-	0.8	ns
t_W	pulse width	data inputs		-	-	20	-	20	-	ns
f_{data}	data rate			-	-	-	50	-	50	Mbps

[1] t_{en} is the same as t_{PZL} and t_{PZH}.
t_{dis} is the same as t_{PLZ} and t_{PHZ}.

[2] Delay between OE going LOW and when the outputs are actually disabled.

[3] Skew between any two outputs of the same package switching in the same direction.

13. Waveforms




Measurement points are given in Table 12.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig 6. The data input (An, Bn) to data output (Bn, An) propagation delay times

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.



Measurement points are given in Table 12.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig 7. Enable and disable times

Table 12. Measurement points[1][2]


Supply voltage	Input	Output		
V_{CCO}	V_M	V_M	V_X	V_Y
1.8 V ± 0.15 V	$0.5V_{CCI}$	$0.5V_{CCO}$	V_{OL} + 0.15 V	V_{OH} − 0.15 V
2.5 V ± 0.2 V	$0.5V_{CCI}$	$0.5V_{CCO}$	V_{OL} + 0.15 V	V_{OH} − 0.15 V
3.3 V ± 0.3 V	$0.5V_{CCI}$	$0.5V_{CCO}$	V_{OL} + 0.3 V	V_{OH} − 0.3 V
5.0 V ± 0.5 V	$0.5V_{CCI}$	$0.5V_{CCO}$	V_{OL} + 0.3 V	V_{OH} − 0.3 V

[1] V_{CCI} is the supply voltage associated with the input.

[2] V_{CCO} is the supply voltage associated with the output.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.



Test data is given in Table 13.

All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz; Z_O = 50 Ω; dV/dt ≥ 1.0 V/ns.

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

V_{EXT} = External voltage for measuring switching times.

Fig 8. Test circuit for measuring switching times

Table 13. Test data

Supply voltage		Input		Load		V_{EXT}		
$V_{CC(A)}$	$V_{CC(B)}$	V_I[1]	$\Delta t/\Delta V$	C_L	R_L[2]	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}[3]
1.65 V to 3.6 V	2.3 V to 5.5 V	V_{CCI}	≤ 1.0 ns/V	15 pF	50 kΩ, 1 MΩ	open	open	$2V_{CCO}$

[1] V_{CCI} is the supply voltage associated with the input.

[2] For measuring data rate, pulse width, propagation delay and output rise and fall measurements, R_L = 1 MΩ; for measuring enable and disable times, R_L = 50 kΩ.

[3] V_{CCO} is the supply voltage associated with the output.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

14. Application information

14.1 Applications

Voltage level-translation applications. The NTS0104 can be used in point-to-point applications to interface between devices or systems operating at different supply voltages. The device is primarily targeted at I^2C or 1-wire which use open-drain drivers, it may also be used in applications where push-pull drivers are connected to the ports, however the NTB0104 may be more suitable.




Fig 9. Typical operating circuit

14.2 Architecture

The architecture of the NTS0104 is shown in Figure 10. The device does not require an extra input signal to control the direction of data flow from A to B or B to A.




Fig 10. Architecture of NTS0104 I/O cell (one channel)

The NTS0104 is a "switch" type voltage translator, it employs two key circuits to enable voltage translation:

1. A pass-gate transistor (N-channel) that ties the ports together.
2. An output edge-rate accelerator that detects and accelerates rising edges on the I/O pins.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

The gate bias voltage of the pass gate transistor (T3) is set at approximately one threshold voltage above the V_{CC} level of the low-voltage side. During a LOW-to-HIGH transition the output one-shot accelerates the output transition by switching on the PMOS transistors (T1, T2) bypassing the 10 kΩ pull-up resistors and increasing current drive capability. The one-shot is activated once the input transition reaches approximately $V_{CCI}/2$; it is de-activated approximately 50 ns after the output reaches $V_{CCO}/2$. During the acceleration time the driver output resistance is between approximately 50 Ω and 70 Ω. To avoid signal contention and minimize dynamic I_{CC}, the user should wait for the one-shot circuit to turn-off before applying a signal in the opposite direction. Pull-up resistors are included in the device for DC current sourcing capability.

14.3 Input driver requirements

As the NTS0104 is a switch type translator, properties of the input driver directly effect the output signal. The external open-drain or push-pull driver applied to an I/O determines the static current sinking capability of the system; the max data rate, HIGH-to-LOW output transition time (t_{THL}) and propagation delay (t_{PHL}) are dependent upon the output impedance and edge-rate of the external driver. The limits provided for these parameters in the datasheet assume a driver with output impedance below 50 Ω is used.

14.4 Output load considerations

The maximum lumped capacitive load that can be driven is dependant upon the one-shot pulse duration. In cases with very heavy capacitive loading there is a risk that the output will not reach the positive rail within the one-shot pulse duration.
To avoid excessive capacitive loading and to ensure correct triggering of the one-shot it's recommended to use short trace lengths and low capacitance connectors on NTS0104 PCB layouts. To ensure low impedance termination and avoid output signal oscillations and one-shot re-triggering, the length of the PCB trace should be such that the round trip delay of any reflection is within the one-shot pulse duration (approximately 50 ns).

14.5 Power up

During operation $V_{CC(A)}$ must never be higher than $V_{CC(B)}$, however during power-up $V_{CC(A)} \geq V_{CC(B)}$ does not damage the device, so either power supply can be ramped up first. There is no special power-up sequencing required. The NTS0104 includes circuitry that disables all output ports when either $V_{CC(A)}$ or $V_{CC(B)}$ is switched off.

14.6 Enable and disable

An output enable input (OE) is used to disable the device. Setting OE = LOW causes all I/Os to assume the high-impedance OFF-state. The disable time (t_{dis} with no external load) indicates the delay between when OE goes LOW and when outputs actually become disabled. The enable time (t_{en}) indicates the amount of time the user must allow for one one-shot circuitry to become operational after OE is taken HIGH. To ensure the high-impedance OFF-state during power-up or power-down, pin OE should be tied to GND through a pull-down resistor, the minimum value of the resistor is determined by the current-sourcing capability of the driver.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

14.7 Pull-up or pull-down resistors on I/Os lines


Each A port I/O has an internal 10 kΩ pull-up resistor to $V_{CC(A)}$, and each B port I/O has an internal 10 kΩ pull-up resistor to $V_{CC(B)}$. If a smaller value of pull-up resistor is required, an external resistor must be added parallel to the internal 10 kΩ, this will effect the V_{OL} level. When OE goes LOW the internal pull-ups of the NTS0104 are disabled.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

15. Package outline

SO14: plastic small outline package; 14 leads; body width 3.9 mm **SOT108-1**



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	$D^{(1)}$	$E^{(1)}$	e	H_E	L	L_p	Q	v	w	y	$Z^{(1)}$	θ
mm	1.75	0.25 0.10	1.45 1.25	0.25	0.49 0.36	0.25 0.19	8.75 8.55	4.0 3.8	1.27	6.2 5.8	1.05	1.0 0.4	0.7 0.6	0.25	0.25	0.1	0.7 0.3	8^o 0^o
inches	0.069	0.010 0.004	0.057 0.049	0.01	0.019 0.014	0.0100 0.0075	0.35 0.34	0.16 0.15	0.05	0.244 0.228	0.041	0.039 0.016	0.028 0.024	0.01	0.01	0.004	0.028 0.012	

Note

1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT108-1	076E06	MS-012				~~99-12-27~~ 03-02-19

Fig 11. Package outline SOT108-1 (SO14)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

TSSOP14: plastic thin shrink small outline package; 14 leads; body width 4.4 mm **SOT402-1**



DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	D (1)	E (2)	e	H_E	L	L_p	Q	v	w	y	Z (1)	θ
mm	1.1	0.15 0.05	0.95 0.80	0.25	0.30 0.19	0.2 0.1	5.1 4.9	4.5 4.3	0.65	6.6 6.2	1	0.75 0.50	0.4 0.3	0.2	0.13	0.1	0.72 0.38	8^o 0^o

Notes

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT402-1		MO-153				~~99-12-27~~ 03-02-18

Fig 12. Package outline SOT402-1 (TSSOP14)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

DHVQFN14: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 x 3 x 0.85 mm **SOT762-1**



DIMENSIONS (mm are the original dimensions)

UNIT	$A^{(1)}$ max.	A_1	b	c	$D^{(1)}$	D_h	$E^{(1)}$	E_h	e	e_1	L	v	w	y	y_1
mm	1	0.05 0.00	0.30 0.18	0.2	3.1 2.9	1.65 1.35	2.6 2.4	1.15 0.85	0.5	2	0.5 0.3	0.1	0.05	0.05	0.1

Note

1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT762-1	- - -	MO-241	- - -			~~02-10-17~~ 03-01-27

Fig 13. Package outline SOT762-1 (DHVQFN14)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

XQFN16: plastic, extremely thin quad flat package; no leads; 16 terminals; body 1.80 x 2.60 x 0.50 mm **SOT1161-1**



Dimensions

Unit[1]		A	A_1	A_3	b	D	E	e	e_1	e_2	L	L_1	v	w	y	y_1
mm	max	0.5	0.05		0.25	1.9	2.7				0.45	0.55				
	nom			0.127	0.20	1.8	2.6	0.4	1.2	1.2	0.40	0.50	0.1	0.05	0.05	0.05
	min		0.00		0.15	1.7	2.5				0.35	0.45				

Note

1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.

sot1161-1_po


Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1161-1	- - -	- - -	- - -			~~09-12-28~~ 09-12-29

Fig 14. Package outline SOT1161-1 (XQFN16)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

XQFN12: plastic, extremely thin quad flat package; no leads; 12 terminals; body 1.70 x 2.00 x 0.50 mm **SOT1174-1**



Dimensions

Unit[1]		A	A_1	A_3	b	D	E	e	e_1	L	L_1	v	w	y	y_1
	max	0.5	0.05		0.25	1.8	2.1			0.55					
mm	nom			0.127	0.20	1.7	2.0	0.4	1.6	0.50	0.15	0.1	0.05	0.05	0.05
	min		0.00		0.15	1.6	1.9			0.45					

Note

1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.

sot1174-1_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1174-1	- - -	MO-288	- - -			10-04-07 10-04-21

Fig 15. Package outline SOT1174-1 (XQFN12)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

16. Abbreviations

Table 14. Abbreviations

Acronym	Description
CDM	Charged Device Model
CMOS	Complementary Metal Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
GPIO	General Purpose Input Output
HBM	Human Body Model
I^2C	Inter-Integrated Circuit
MM	Machine Model
SMBus	System Management Bus
UART	Universal Asynchronous Receiver Transmitter

17. Revision history

Table 15. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
NTS0104 v.2	20110427	Product data sheet	-	NTS0104 v.1
Modifications:	• Added Table 8: total supply current (typical). • SOT1174 changed to SOT1174-1.			
NTS0104 v.1	20101125	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

18. Legal information

18.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

18.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

18.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This NXP Semiconductors product has been qualified for use in automotive applications. The product is not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

18.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

19. Contact information

For more information, please visit: **http://www.nxp.com**

For sales office addresses, please send an email to: **salesaddresses@nxp.com**

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2011. All rights reserved.

20. Contents

1 General description 1
2 Features and benefits 1
3 Applications 1
4 Ordering information 2
5 Marking 2
6 Functional diagram 3
7 Pinning information 4
7.1 Pinning 4
7.2 Pin description 5
8 Functional description 5
9 Limiting values 5
10 Recommended operating conditions 6
11 Static characteristics 6
12 Dynamic characteristics 8
13 Waveforms 12
14 Application information 15
14.1 Applications 15
14.2 Architecture 15
14.3 Input driver requirements 16
14.4 Output load considerations 16
14.5 Power up 16
14.6 Enable and disable 16
14.7 Pull-up or pull-down resistors on I/Os lines . . 17
15 Package outline 18
16 Abbreviations 23
17 Revision history 23
18 Legal information 24
18.1 Data sheet status 24
18.2 Definitions 24
18.3 Disclaimers 24
18.4 Trademarks 25
19 Contact information 25
20 Contents 26

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2011. **All rights reserved.**

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 27 April 2011
Document identifier: NTS0104


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.