

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- -
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AD	39


REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	R2	REVISED PER ECO-15-004641	28MAR2015	NK	JO






SECTION A–A
SCALE 20:1






SECTION B–B
INSULATION RANGE .025–.060
SCALE 20:1



SECTION C–C
SCALE 20:1



SECTION D–D
SCALE 20:1

1. .000100 MIN BRIGHT TIN–LEAD OVER .000050 MIN NICKEL ON ENTIRE CONTACT
2. .000050 MIN NICKEL ON ENTIRE CONTACT; .000015 MIN GOLD ON CONTACT AREA; .000050 MIN BRIGHT TIN–LEAD ON AREA M.
3. .000050 MIN NICKEL ON ENTIRE CONTACT; .000030 MIN GOLD ON CONTACT AREA; .000050 MIN BRIGHT TIN–LEAD ON AREA M.
4. LOOSE PIECE CUT–OFF DIMENSION.
5. .000100–.000200 TIN OVER .000050–.000100 NICKEL ON ENTIRE CONTACT.
6. PREPLATED MATERIAL: (.000015 MIN GOLD ON CONTACT AREA, .000050–.000100 TIN ON AREA M, ALL OVER .000050–.000100 NICKEL ON ENTIRE CONTACT).
7. PREPLATED MATERIAL: (.000030 MIN GOLD ON CONTACT AREA, .000050–.000100 TIN ON AREA M, ALL OVER .000050–.000100 NICKEL ON ENTIRE CONTACT).

REMARKS	FINISH	PART NO
STRIP	7	1–104479–8
LOOSE PIECE	7 REF	1–104479–3
LOOSE PIECE	6 REF	1–104479–2
LOOSE PIECE	5 REF	1–104479–1
STRIP	7	1–104479–0
STRIP	6	104479–9
STRIP	5	104479–8
LOOSE PIECE	3 REF	104479–7
LOOSE PIECE	2 REF	104479–6
LOOSE PIECE	1 REF	104479–5
STRIP	3	104479–4
STRIP	2	104479–3
STRIP	1	104479–2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .005
4 PLC ± –
ANGLES ± –

MATERIAL: PHOSPHOR BRONZE
FINISH: SEE TABLE

DWN C.OBERMAN 5-9-89
CHK K. HELM 5-12-89
APVD R.FLICKER 5-12-89
PRODUCT SPEC 108-1472
APPLICATION SPEC 114-25038
WEIGHT –

TE Connectivity

NAME: CONTACT, CRIMP SNAP-IN AMPMODU SHORT POINT, 20-24 AWG

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-104479	–

CUSTOMER DRAWING | SCALE 10:1 | SHEET 1 OF 1 | REV R2