MATERIALS AND FINISHES

COUPLING SLEEVE: BRASS
PLATED NICKEL

BODY: BRASS
PLATED TRI-M3

RETENTION CAP: BRASS
PLATED TRI-M3


INSULATORS: TEFLON


RETENTION SPRING: STAINLESS STEEL
PASSIVATED


GROUND SPRING: BERYLLIUM COPPER
PLATED GOLD


CONTACT: BRASS
PLATED GOLD


CRIMP TUBE: BRASS
PLATED NICKEL

















RECOMMENDED CABLE STRIP DIMENSION

73254-0071	ONE PER BAG
73254-0070	TRAY
PART NO	PACKAGING

CHG: UPDATE PACKAGING FOR 73254-0070 PER RF15-E211
EC NO: URF2015-0657 2015/05/25
DRWN: RYEH
CH'KD:
APPR: YCHENG 2015/05/29
DESCRIPTION
B3
REV

QUALITY SYMBOLS
=0
=0
=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---
0 PLACE	±	±

ANGULAR ± 2 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: 5:1
DESIGN UNITS: INCH
THIRD ANGLE PROJECTION

		DATE
DRAWN BY	SSS	2003/10/01
CHECKED BY	TEF	2003/10/01
APPROVED BY	GMH	2003/10/01

TITLE: QMA PLUG STRAIGHT LMR240 50 OHM QMA-PC, EWR-4121

molex

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-73254-007
SHEET NO.: 1 OF 1
SIZE: C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION