
High performance hyfen rectangular cable connectors

Description

MSM rectangular connectors offers an extremely reliable, rugged, and versatile connection system .
They are a range of multiway connectors available in 8 sizes from 14 to 104 positions.
MS-M cable connectors can be offered with a full range of hardware and accessories. Guiding pins and sockets, turnable jackscrews, a variety of cable hoods, pin protection shrouds and discrimination pins make this connector range a truly versatile system.



Features and benefits

- Connectors supplied pre-assembled except for panel mount versions.
- Available in 14-20-26-34-42-50-75 and 104 positions.
- **34 contact positions suitable for V.35 applications (see V.35 section)**
- Full range of accessories available including hoods, strain relief clamps, guide pins, jackscrews and pin protection shrouds.
- MS-M hyfen complies with NFC 93426 - HE 621-622 and MIL-C-28748 specifications.

Performance characteristics

Operating temperature:	-55°C to +125°C
Insulation resistance:	5000 MΩ min.
Test potential:	2000 VAC
Durability:	500 matings and unmatings.
Vibration resistance	Per MIL-STD 202 method 204
Shock:	Per MIL-C-STD 202 method 207

Construction

Connector Material : Glass filled Phenolic
Flammability rating : UL94-V0
Hoods: Aluminium alloy
gold chromate or anodized
Polyamide 6.6 - black - UL94-V2
Cable clamps: Stainless steel
Polarizing hardware: Brass nickel plated
Shrouds: Aluminium alloy
gold chromate or anodized

Contact accommodation


- "MS-M" Hyfen connectors accept Trim-Trio removable snap-lock contacts (see contact section)
- Contacts to be ordered seperately.

How to order


Connector family	**MS** **MS**	**34** **34**	**P** **P**	**M** **M**	**124** **120**	**S** **S-**	**GE** **--**	**16** **--**
Contact arrangement								
Type of housing: **P:** plug body for male contacts **S:** Receptacle housing for female contacts								
N° 16 contact								
Design variation								
Pin protection shroud								
GE = plastic turnable jackscrews								
Code for special variations								

Contact arrangement


14 POS.




20 POS.




26 POS.




34 POS.




42 POS.



50 POS



75 POS.




The contact position identification letters or numbers shown in the above diagrams apply to MS-M plug and receptacle connectors. Dimensionally, corresponding types of plug and receptacle mouldings are the same and differ only in that the contact position lettering/numbering of the plug (MS-PM) is a mirror image of that of the receptacle (MS-RM). Note that pins and/or sockets can be used in either the plug or receptacle moulding.

Note: Contact identification is shown for wiring face of the receptacle and mating face at plug connector.

Panel mount connectors with guiding hardware (MS--M1)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version for female contacts	A	B	D	E	Fig.
14	MS14PM1	MS14RM1	23.8	31.8	20.1		1-2
20	MS20PM1	MS20RM1	31.75	39.65	27.95	11.7	
26	MS26PM1	MS26RM1	33.3	41.3	27.2	15.0	
34	MS34PM1	MS34RM1	42.8	50.8	35.7	19.1	
42	MS42PM1	MS42RM1	50.55	58.65	42.95		
50	MS50PM1	MS50RM1	57.95	69.1	50.85	22.1	
75	MS75PM1	MS75RM1				31.2	1-3

Panel mount connectors with fixed jackscrew hardware (MS--M58)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version for female contacts	A	B	D	E	Fig.
14	MS14PM58	MS14RM58	23.8	31.8	20.1		1-2
20	MS20PM58	MS20RM58	31.75	39.65	27.95	11.7	
26	MS26PM58	MS26RM58	33.3	41.3	27.2	15.0	
34	MS34PM58	MS34RM58	42.8	50.8	35.7	19.1	
42	MS42PM58	MS42RM58	50.55	58.65	42.95		
50	MS50PM58	MS50RM58	57.95	69.1	50.85	22.1	
75	MS75PM58	MS75RM58				31.2	1-3

Cable connector without strain relief and turnable jackscrew hardware (MS—M57)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version for female contacts	A	B	D	E	Fig.
14	MS14PM57	MS14RM57	23.8	31.8	20.1		
20	MS20PM57	MS20RM57	31.75	39.65	27.95	11.7	1-2
26	MS26PM57	MS26RM57	33.3	41.3	27.2	15.0	
34	MS34PM57	MS34RM57	42.8	50.8	35.7	19.1	
42	MS42PM57	MS42RM57	50.55	58.65	42.95		
50	MS50PM57	MS50RM57	57.95	69.1	50.85	22.1	
75	MS75PM57	MS75RM57				31.2	1-3

Cable connector with metal butterfly hood and turnable jackscrew hardware (MS--M124K)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version for female contacts	A	B	E	G max	Fig.
14	MS14PM124K	MS14RM124K	23.8	31.8	11.7	14.7	
20	MS20PM124K	MS20RM124K	31.75	39.65			
26	MS26PM124K	MS26RM124K	33.3	41.3	15.0	18	1-2
34	MS34PM124K	MS34RM124K	42.8	50.8	19.1		
42	MS42PM124K	MS42RM124K	50.55	58.65		22.2	
50	MS50PM124K	MS50RM124K	57.95	69.1	22.1		
75	MS75PM124K	MS75RM124K			31.2	31.8	1-3

Cable connector with metal butterfly hood and fixed jackscrew hardware (MS--M140)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version female contacts	A	B	E	G max	H	Fig.
14	MS14PM140	MS14RM140	23.8	31.8	11.7	14.7	48.7	1-2
20	MS20PM140	MS20RM140	31.75	39.65				
26	MS26PM140	MS26RM140	33.3	41.3	15.0	18		
34	MS34PM140	MS34RM140	42.8	50.8	19.1	22.2	56.7	
42	MS42PM140	MS42RM140	50.55	58.65				
50	MS50PM140	MS50RM140	57.95	69.1	22.1			1-3
75	MS75PM140	MS75RM140			31.2	31.8		

Cable connector with metal butterfly hood and guiding hardware (MS--M120)






Connector size	Part number: Plug version for male contacts	Part number: Receptacle version female contacts	A	B	E	G max	H	Fig.
14	MS14PM120	MS14RM120	23.8	31.8	11.7	14.7	48.7	1-2
20	MS20PM120	MS20RM120	31.75	39.65				
26	MS26PM120	MS26RM120	33.3	41.3	15.0	18		
34	MS34PM120	MS34RM120	42.8	50.8	19.1	22.2	56.7	
42	MS42PM120	MS42RM120	50.55	58.65				
50	MS50PM120	MS50RM120	57.95	69.1	22.1			1-3
75	MS75PM120	MS75RM120			31.2	31.8		

MS34 Cable connector with 1 piece metal suitcase hood (MS34--MEHM)






Part number		Description
Plug version for male contacts	Receptacle version for female contacts	
MS34PMEHM	MS34RMEHM	Anodised hood, plastic strain relief and turnable hardware.
MS34PMSEHM	MS34RMSEHM	Shielded version with nickel plated hood, metal strain relief and turnable hardware

Cable connector with Alu die cast hood (MS-M157GE00)






Connector size	Part number		A	B	C	D	E max.	F	Fig.
	Plug version for male contacts	Receptacle version for female contacts							
50	MS50PM157GE00	MS50RM157GE00	57.95	65.85	73.0	56.0	20.0	22.2	1-2
75	MS75PM157GE00	MS75RM157GE00	57.95	65.85	73.0	56.0	25.0	31.2	1-3

Cable connector with die cast hood and turnable jackscrew hardware (MS—MJD10)






Connector size	Part number Plug version for male contacts	Part number Receptacle version female contacts	A	B	C	D max	E	G max	Fig.
20	MS20PMJD10	MS20RMJD10	31.75	39.65			11.7	22	
26	MS26PMJD10	MS26RMJD10	33.3	41.3	44.3	71	15		
34	MS34PMJD10	MS34RMJD10	42.8	50.8					1-2
42	MS42PMJD10	MS42RMJD10	50.55	58.65	61,5	80	19.1	26.5	
50	MS50PMJD10	MS50RMJD10	57.95	69.1	69		22.1	27.5	
75	MS75PMJD10	MS75RMJD10			72		31.2	33	1-3

Cable connector with diecast hood and fixed jackscrew hardware (MS—MJD58)






Connector size	Part number Plug version for male contacts	Part number Receptacle version female contacts	A	B	C	D max	E	G max	Fig.
20	MS20PMJD58	MS20RMJD58	31.75	39.65	44,3	55	11.7	22	
34	MS34PMJD58	MS34RMJD58	42.8	50.8	61,5				1-2
42	MS42PMJD58	MS42RMJD58	50.55	58.65		63	19.1	26.5	
50	MS50PMJD58	MS50RMJD58	57.95	69.1	69		22.1	27.5	
75	MS75PMJD58	MS75RMJD58			72	65	31.2	33	1-3

MSD104 receptacle cable connector with central jackscrew (MSD104RM)






Connector size	Part number	Orientation of guide sockets
104	MSD104RM489	A, B, C, D

MSD104 plug cable connector without cable clamp (MSD104PM)






Connector size	Part number	Orientation of guide sockets
104	MSD104PM494	A, B, C, D

MSD104 cable hood with cable clamp (MSH104M1)





Connector size	Part number	Orientation of guide sockets
104	**MSH104M1**	A combination hood and cable clamp assembly which can be used on MSD104 receptacle or cable plug connector

MS-M panel cut-out dimensions




Fig.1 Fig.2 Fig.3 Fig.4 Fig.5

Connector size	Fig.	A	B	C	D	E	F
14	**1 or 2**	12.45	20.83	23.80	---	---	---
20	**1 or 2**	12.45	28.70	31.75			
26	**2 or 3**	15.75	28.20	33.30			
34	**4**	19.80	36.60	42.80	49.30	6.35	11.90
42	**4**		43.70	50.55	56.90		
50	**4**		51.60	57.95	64.30		
75	**4**	29.10				14.20	19.40
104	**5**	29.50	55.60	63.50	72.64	12.70	20.62

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru