FASTON Printed Circuit Board Tabs and Receptacles

Product Facts

- **Full line of PCB tabs and receptacles**
- **Straight and right-angle tabs available in .250, .187 and .110 series**
- **Receptacles produced in .250/.205 x .032 or .025. Standard or low insertion force receptacles available**
- **Strip product for automatic insertion**
- **Compatible with industry insertion equipment or full line of equipment available from TE**



TE now offers a complete line of printed circuit board tabs and receptacles. TE PCB product can be found in switches and on control boards around the world. Our product offering includes .250, .187 and .110 series vertical tabs, .250 and .187 right-angle tabs and .250/.205 vertical receptacles. Product is available in loose piece and strip form. In a short time, our product offering has grown from a handful of part numbers to dozens of parts. We continue to add to our product family as design changes, innovation and customers' requirements expand.

Insertion equipment is available for our entire strip product line. TE currently has an entry level semi-automatic, air-powered bench machine under development for customers with moderate insertion requirements. The compact, fully automatic AccuSerter 2 machine is available for applications where larger volumes will be inserted and where programmable, microprocessor controlled equipment is desired. TE also offers the P300 and P350 series machines for even higher automation. Capabilities include: servo drive, force monitoring, up to three heads. This machine is available in stand-alone or in-line configurations.

The TE product has been designed to be compatible with industry insertion equipment. In many cases, this product will work as a "drop in" replacement for existing product. In some cases, slight modifications or minor tooling changes are necessary. Please consult technical support or the global application tooling group for more details.

TE is one of the only companies that offers printed circuit board tabs and receptacles as well as the crimp to wire receptacles and tabs that offer a complete solution for your packaging needs.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752


Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)

250 Series Printed Circuit Board Tabs


Stock Thickness — .032 [0.81]
Board Hole Size —
.055 ± .002 [1.40 ± 0.05] Dia.



Dimensions					Material and Finish	UL	CSA	Terminal Part No.	
W	L	K	E	M				Strip[2]	Loose Piece[1]
.312 7.92	.502 12.75	.125 3.18	.312 7.92	.377 9.58	Tin Plated Brass	X	X	63839-1[3]	—
	.547 13.89	.157 3.99	.312 7.92	.400 10.16	Tin Plated Brass	X	X	63986-1	—
	.552 14.02	.150 3.81	.312 7.92	.402 10.21	Tin Plated Brass	X	X	1217566-1	—
						X	X	1217539-1	—
.295 7.49	.622 15.80	.125 3.18	.312 7.92	.497 12.62	Tin Plated Brass	X	X	—	62409-1[3]
						—	—	—	1217056-1
.280 7.11	.487 12.37	.125 3.18	.312 7.92	.362 9.19	Tin Plated Brass	X	X	62650-1[3]	—
	.532 13.51	.175 4.45	.312 7.92	.357 9.07	Tin Plated Brass	X	X	63650-1[3]	—
	.622 15.80	.125 3.18	.452 11.48	.497 12.62	Tin Plated Brass	X	X	—	63900-1
						X	X	63755-1[3]	—

[1] Board hole size: .060/.053 [1.52/1.35] dia.
[2] Insertion equipment available.
[3] Dimple.

Stock Thickness — .032 [0.81]
Board Hole Size —
.100 ± .002 [2.54 ± 0.05] Dia.



Material and Finish	UL	CSA	Terminal Part No.	
			Strip[1]	Loose Piece
Tin Plated Brass	X	X	63066-1	63067-1

[1] Insertion equipment available.

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752


Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)

250 Series Printed Circuit Board Tabs (Continued)


Stock Thickness — .032 [0.81]
Board Hole Size —
.055 ± .002 [1.40 ± 0.05] Dia.



Dimensions				Material and Finish			Terminal Part No.	
L	K	E	M				Strip[1]	Loose Piece
.552 14.02	**.150** 3.81	**.312** 7.92	**.402** 10.21	Tin Plated Brass	X	X	63862-1[2]	1742188-1[2]
					X	X	63824-1	63849-1
.582 14.78	**.180** 4.57	**.312** 7.92	**.402** 10.21	Tin Plated Brass	X	X	1217136-1	1217421-1
.650 16.51	**.150** 3.81	**.410** 10.41	**.500** 12.70	Tin Plated Brass	X	X	1217126-1[2]	—
.710 18.03	**.150** 3.81	**.470** 11.94	**.560** 14.22	Tin Plated Brass	X	X	1217125-1	1217169-1
.780 26.18	**.150** 3.81	**.540** 13.72	**.630** 16.00	Tin Plated Brass	X	X	1217127-1	1217167-1

[1] Insertion equipment available.
[2] Dimple.

Stock Thickness — .032 [0.81]
Board Hole Size —
.055 ± .002 [1.40 ± 0.05] Dia.



Dimension L	Material and Finish			Terminal Part No.
1.062 26.97	Tin Plated Brass	X	X	63949-1
1.207 30.66	Tin Plated Brass	X	X	63950-1

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752

Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999


UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)

250 Series Printed Circuit Board Tabs (Continued)

Right-Angle Printed Circuit Board Tabs

Stock Thickness — .032 [0.81]
Board Hole Size —
.055 ± .002 [1.40 ± 0.05] Dia.




Dimensions		Material and Finish	UL	CSA	Terminal Part No.	
E	L				Strip[1]	Loose Piece
.312 7.92	**.800** 20.32	Tin Plated Brass	X	X	63951-1	1217754-1
.358 9.09	**.630** 16.00	Tin Plated Brass	—	—	—	928814-1
.662 16.83	**1.00** 25.40	Tin Plated Brass	—	—	63952-1	—

[1] Insertion equipment available.

205 Series Printed Circuit Board Only

Stock Thickness — .020 [0.51]
Board Hole Size —
.100 – .095 [2.54 – 2.41] Dia.




Dimensions		Material and Finish	UL	CSA	Terminal Part No.
L	W				
.525 13.34	**.070** 1.78	Tin Plated Brass	X	X	62411-1[1]
.545 13.84	**.160** 4.06	Tin Plated Brass	X	X	60284-2[1]

[1] Loose piece only.

.250/.205 Printed Circuit Board Receptacles

Stock Thickness — .016 [0.41]



Style	Fits Tab	Dimensions		Material and Finish	UL	CSA	Part No.	
		A	L				Strip	Loose Piece
A	**.032** 0.81 (LIF)	**.075** 1.91	**.480** 12.19	Tin Plated Brass	—	—	63968-1	—
	.032 0.81	**.075** 1.91	**.480** 12.19	Tin Plated Brass	—	—	63969-1	1217080-1
	.025 0.64 (LIF)	**.075** 1.91	**.480** 12.19	Tin Plated Brass	—	—	63994-1	—
	.025 0.64	**.075** 1.91	**.510** 12.95	Tin Plated Brass	—	—	1217137-1[2]	—
			.480 12.19	Tin Plated Brass	—	—	1217180-1	—
B	**.020** 0.51	—	—	Tin Plated Phos Bronze	—	—	1217107-1[1]	—
C	**.250 x .016** 6.35 x 0.41 Spade	—	—	Tin Plated Brass	—	—	62751-1	62806-1

Note: All part numbers are RoHS compliant.

[1] Horizontal mount.
[2] .180 [4.57] length — solder legs.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752


Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015


FASTON Printed Circuit Board Tabs and Receptacles (Continued)

187 Series
Printed Circuit Board Tabs

Stock Thickness — .020 [0.51]




A



B


Type	Board Thickness	Dimensions T	L	E	H	Material and Finish	UL	CSA	Terminal Part No.
A	**.062** 1.57	—	**.545** 13.84	**.250** 6.35	—	Tin Plated Brass	X	X	61907-1[1]
B	**.062** 1.57	**.250** 6.35	**.332** 8.43	**.250** 6.35	**.303** 7.70	Pre-Tin Brass	X	X	62221-1[2]

[1] Loose piece only.
[2] Insertion equipment available.



Tab Thickness	Board Hole Size	Dimensions L	M	H	Material and Finish	UL	CSA	Terminal Part No. Strip[2]	Loose Piece
.032 0.81	**.053-.057** 1.35-1.45	**.487** 12.37	**.362** 9.19	**.280** 7.11	Tin Plated Brass	X	X	63525-1[1]	1217057-1[1]
.020 0.51	**.050-.054** 1.27-1.37	**.487** 12.37	**.362** 9.19	**.285** 7.24	Tin Plated Brass	X	X	63603-1	1217131-1
		.440 11.18	**.315** 8.00	**.312** 7.92	Tin Plated Brass	X	X	63838-1	—

[1] Dimple.
[2] Insertion equipment available.



Tab Thickness	Dimensions L	E	M	Material and Finish	UL	CSA	Terminal Part No. Strip[3]	Loose Piece
.032 0.81	**.490** 12.45	**.250** 6.35	**.340** 8.64	Tin Plated Brass	X	X	63860-1[1]	—
					X	X	1217133-1	—
	.510 12.95	**.250** 6.35	**.370** 9.40	Tin Plated Brass	X	X	1742361-1	—
	.710 18.03	**.470** 11.94	**.560** 14.22	Tin Plated Brass	X	X	1217124-1	—
	.635 16.13	**.395** 10.03	**.485** 12.32	Tin Plated Brass	X	X	—	1217332-1[2]
.020 0.51	**.490** 12.45	**.250** 6.35	**.340** 8.64	Tin Plated Brass	X	X	63823-1	63892-1
	.510 12.95	**.250** 6.35	**.370** 9.40	Tin Plated Brass	X	X	1742362-1	—

[1] Dimple.
[2] No hole or dimple.
[3] Insertion equipment available.

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752


Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)

187 Series Printed Circuit Board Tabs
(Continued)


Right-Angle Printed Circuit Board Tabs



Stock Thickness	Board Hole Size	Material and Finish	UL	CSA	Terminal Part No.
.032 0.81	**.053-.057** 1.35-1.45	Tin Plated Brass	X	X	1217061-1
			—	—	1217756-1[1]
.020 0.51	**.050-.054** 1.27-1.37	Tin Plated Brass	X	X	1217062-1
			—	—	1217156-1[1]

[1] Loose piece.

Tab Caps 187 and 250 Series



Tab Size	Material	UL 94[1]	Color	Dimensions		Insulator Part No.
				T	W	
"187" Series .020 [0.51] Thick	Nylon	V2	Natural	**.320** 8.13	**.260** 6.60	360041-1
"250" Series .032 [0.81] Thick	Nylon	V2	Natural	**.380** 9.65	**.320** 8.13	360042-1

[1] Flammability rating.

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752


Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015


FASTON Printed Circuit Board Tabs and Receptacles (Continued)

.110 Series Printed Circuit Board Tabs


Stock Thickness — .020 [0.51]




A



B



C




D

Style	Mating Hole Diameter	Dim. L	Material and Finish	UL	CSA	Terminal Part No.
A	**.060-.055** 1.52-1.40	**.490** 12.45	Tin Plated Brass	X	X	61134-3[1]
B	**.067-.063** 1.70-1.60	**.485** 12.32	Tin Plated Brass	X	X	61968-1[2]
				X	X	62437-1[1]
C	**.044-.048** 1.12-1.22	**.490** 12.45	Tin Plated Brass	X	X	62395-1[2]
		.622 15.80	Tin Plated Brass	X	X	63756-1[2,3]

[1] Loose piece only.
[2] Insertion machine available.
[3] .032 [0.81] stock.
[4] .060 [1.52] tab width.

Right-Angle Printed Circuit Board Tabs



Tab Thickness	PCB Hole Dia. +0/-.01 [+0/-.03]	Material and Finish	UL	CSA	Terminal Part No.
.032 0.81	**.055** 1.40	Tin Plated Brass	—	—	725963-2
.020 0.51	**.051** 1.30	Tin Plated Brass	—	—	725996-2

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.


Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752

Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)

FASTON RAST 5 Tab Header Assembly, 250 Series



Product Facts

- **.250 x .032 [6.3 x 0.8] FASTON Tabs built on 5 mm centerlines**
- **Shrouded header assembly that conforms to the European RAST 5 Standard**
- **Mating TE connector families include Positive Lock RAST 5 connector system, AMP standard timer RAST 5, AMP multifitting, AMP multifitting MKII, AMP MONO-SHAPE TAB MKI, and AMP MONO-SHAPE MKII**
- **Vertical and right-angle versions available in 2 through 8 positions**
- **Tin plated brass tabs are standard, silver plated tab versions are available upon request**
- **Lead free design is RoHS and ELV compliant**
- **UL 94 V-0 housing meets Glow Wire IEC 60695-1 Section 30.2.3 – 750° No Flame**
- **Component recognition USR and CSR under file no. E28476**
- **VDE tested according to DIN EN61984 (VDE0627): 2002-09; EN61984: 2001 VDE reg. no. B718**

The FASTON RAST 5 Tab header assembly system is designed to provide a RAST 5 interface to a printed circuit board. The RAST 5 standard defines and standardizes the connector mating interface. 250 series tabs are placed on 5mm center lines with a plastic shroud that has keying, polarization, and locking features that help prevent mismating of the corresponding RAST 5 female receptacle housing. The header assembly is designed to accept any RAST 5 compliant female receptacle system or individual quick connects.

The most common application for this product is for household appliance controls where OEMs want to minimize the possibility of crossed wires. It is also suited for other applications such as gaming, vending, and exercise equipment controls as well as residential, commercial and industrial HVAC and light industrial equipment. The system comes fully assembled and is easily press fit into the board for the soldering operation. Preassembly of the tabs into the header ensures tab perpendicularity to the board. The solder leg PCB layout is based on the industry standard for similar systems available on the market. To further enhance correct placement onto the board, the vertical system includes a plastic post which allows header placement to be polarized.

Material
UL 94 V-0, 6/6 Nylon

See TE Catalog 1654742 for the complete line of RAST products.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.


Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752

Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999


UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

FASTON Printed Circuit Board Tabs and Receptacles (Continued)


FASTON RAST 5 Tab Header Assembly, 250 Series
(Continued)



Vertical Orientation



Right-Angle Orientation



PCB Layout
(Ref.) from Component Side

No. of Positions	RAST 5 Configuration	Dim. A	Part Numbers	
			Vertical	Right-Angle
2	02-A	.484 [12.30]	521382-2	521384-2
	02-C	.484 [12.30]	2-521382-2	2-521384-2
	02-E	.484 [12.30]	3-521382-2	3-521384-2
	02-I	.484 [12.30]	5-521382-2	5-521384-2
3	03-A	.681 [17.30]	521382-3	521384-3
	03-B	.681 [17.30]	1-521382-3	1-521384-3
	03-D	.681 [17.30]	2-521382-3	2-521384-3
	03-K	.681 [17.30]	4-521382-3	—
4	04-A	.878 [22.30]	521382-4	521384-4
	04-B	.878 [22.30]	1-521382-4	1-521384-4
	04-F	.878 [22.30]	3-521382-4	3-521384-4
	04-G	.878 [22.30]	4-521382-4	4-521384-4
5	05-B	1.075 [27.30]	521382-5	521384-5
6	06-A	1.272 [32.30]	521382-6	521384-6
	06-D	1.272 [32.30]	1-521382-6	1-521384-6
7	07-C	1.469 [37.30]	521382-7	521384-7
8	08-D	1.665 [42.30]	521382-8	521384-8
	08-C	1.665 [42.30]	2-521382-8	2-521384-8

Refer to the TE Customer Drawing for additional details and specific keying patterns.
For more information related to the RAST 5 Standard, see TE Literature Distribution no. 1308243.

Available variations include: silver plated tabs, DIN style tabs, and Glow Wire housings.

RAST 5 headers mate to the following product families: AMP multifitting MKII, RAST 5 Positive Lock MKIII, AMP Standard Timer and AMP Standard Power Timer.

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 3-11

www.te.com

Dimensions are shown for reference purposes only. Specifications subject to change.

Dimensions are in inches and millimeters unless otherwise specified.
USA: +1 (800) 522-6752

Canada: +1 (905) 475-6222
Mexico/C. Am.: +52 (0) 55-1106-0800
Latin/S. Am.: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru