molex
one company > a world of innovation


This document was generated on 04/16/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0546841204

Status: Active

Description: 0.40mm (.016") Pitch Board-to-Board SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 3.50mm (.138") Stacking Height, 120 Circuits



Series image - Reference only

Documents:

3D Model
Drawing (PDF)
Product Specification PS-54684-006 (PDF)
Product Specification PS-54684-008 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	PCB Receptacles
Series	54684
Application	Board-to-Board
Product Name	SlimStack™

Physical

Circuits (Loaded)	120
Color - Resin	Brown
Durability (mating cycles max)	30
Glow-Wire Compliant	No
Mated Height (in)	0.138 In
Mated Height (mm)	3.50 mm
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Vertical
PCB Locator	No
PCB Retention	None
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface (in)	0.016 In
Pitch - Mating Interface (mm)	0.40 mm
Plating min: Mating (µin)	4
Plating min: Mating (µm)	0.1
Plating min: Termination (µin)	2
Plating min: Termination (µm)	0.05
Polarized to PCB	No
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-25°C to +105°C
Termination Interface: Style	Surface Mount

Electrical

Current - Maximum per Contact	0.3A
Voltage - Maximum	30V

Material Info

Reference - Drawing Numbers

Product Specification	PS-54684-006, PS-54684-008, RPS-54684-013, RPS-54684-015, RPS-54684-016, RPS-54684-017, RPS-54684-021
Sales Drawing	SD-54684-011, SD-54684-012

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here


Please visit the Contact Us section for any non-product compliance questions.


Search Parts in this Series
54684Series


Mates With
55526 PCB Header


This document was generated on 04/16/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION










参考基板レイアウト（マウント面）
P.C.BOARD
PATTERN DIMENSION (REF.)
(MOUNTING AREA)



C	B	A	MATERIAL NO.	CIRCUIT
24.6	23.6	26.7	54684-1203	120
20.6	19.6	22.7	54684-1003	100
18.6	17.6	20.7	54684-0903	90
16.6	15.6	18.7	54684-0803	80
14.6	13.6	16.7	54684-0703	70
12.6	11.6	14.7	54684-0603	60
10.6	9.6	12.7	54684-0503	50
5.4	4.4	7.5	54684-0243	24

MODEL NO. 54684-***3

注記 NOTES:

1. 使用材料 MATERIAL
   ハウジング：液晶ポリマー　ガラス充填 UL94V-0 茶色
   HOUSING:LIQUID CRYSTAL POLYMER
   GLASS FILLED UL94V-0
   COLOR BROWN
   ターミナル：リン青銅（t＝0.15）
   TERMINAL:PHOSPHOR BRONZE(t=0.15)
2. メッキ仕様 PLATING
   金メッキ 0.10 マイクロメートル以上（コンタクト部）
   GOLD 0.10 MICROMETER MINIMUM(CONTACT AREA)
   金メッキ 0.4 マイクロメートル以下（テール部）
   GOLD 0.4 MICROMETER MAXIMUM(TAIL AREA)
   下地メッキ：ニッケルメッキ1.5 マイクロメートル以上
   UNDER PLATING : NICKEL 1.5MICROMETER MINIMUM
   ＊コンタクト部とテール部はニッケルメッキによって分断されている金メッキです。
   DIVIDE INTO PARTS THE GOLD PLATING OF THE CONTACT PART AND THE TAIL PART BY THE NICKEL PLATING.

△3 （全極数／2）＝偶数の場合に適用。
APPLY FOR (CIRCUIT/2)=EVEN.

4. 嵌合相手：55526シリーズ、501017シリーズ。
MATE WITH : 55526 SERIES AND 501017 SERIES.

5. テール平坦度は、0.08MAX.
TAIL COPLANARITY TO BE 0.08MAX.

REVISED
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV D

GENERAL TOLERANCES (UNLESS SPECIFIED)


10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	T.KAIHO 2003/07/15
CHECKED BY / DATE	T.ITO 2003/07/15
APPROVED BY / DATE	T.YAMAGU 2003/07/15
MATERIAL NO.	SEE CHART
TITLE	0.4BB CONN.REC HSGASSY NO BOSS NI BARRIER -LEAD FREE-
	MOLEX INCORPORATED
DOCUMENT NO.	SD-54684-011
SHEET NO.	1 OF 1
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

引き出し方向
PULL OUT
DIRECTION







DETAIL "F"

NOTES

1. 製品詳細寸法については図面 SD-54684-011 を参照下さい。
   RE DETAILED DIMENSION, SEE SD-54684-011
2. 梱包数量：１５００個／リール
   NUMBER OF CONNECTORS : 1500PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH



4. トップテープの剥離強度：0.1N ～ 0.7N(10.2gf ～ 71.4gf)
   （剥離方向は下図参照）
   尚、本規格値は出荷時に適用。（但し、輸送時に剥離が発生しないこと。）
   PEELING OFF FORCE OF TOP TAPE : 0.1N ～0.7N(10.2gf ～ 71.4gf)
   (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG,)
   THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
   PEEL OFF SHOULD NOT BE ALLOWED , DURING TRANSPORTATION.



5. 材料(MATERIAL)
   キャリアテープ(CARRIER TAPE)：ポリプロピレン(POLYPROPYLENE)
   トップテープ(TOPTAPE)： PET , PE , PEF
   リール(REEL)：ポリスチレン（PS）<リサイクル材を含む>
   POLYSTYREN(PS) <RECYCLE MATERIAL CONTAINED>

REVISED				
E	EC NO: J2010-2361	DRWN:MKATO	CHKD:THIRATA	APPR:MSASAO
REV	DESCRIPTION	2010/05/21	2010/05/24	2010/06/09

GENERAL TOLERANCES (UNLESS SPECIFIED)	
10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: ---	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: T.KAIHO	DATE: 2003/07/15	TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-	
CHECKED BY: T.ITO	DATE: 2003/07/15		
APPROVED BY: T.YAMAGU	DATE: 2003/07/15	molex MOLEX INCORPORATED	
MATERIAL NO.: SEE CHART		DOCUMENT NO.: SD-54684-012	SHEET NO.: 1 OF 4

MODEL NO. 54684-***4

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



24mm WIDTH CARRIER TAPE

24mm幅キャリアテープ

24	25.5	7.7	54684-0244	24
キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.

MODEL NO. 54684-***4

REVISED
E
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15

TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-


MOLEX INCORPORATED


MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-54684-012
SHEET NO.: 2 OF 4

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

引き出し方向
PULL OUT DIRECTION





32mm幅キャリアテープ
32mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.
32	33.5	20.9	54684-0904	90
		18.9	54684-0804	80
		16.9	54684-0704	70
		14.9	54684-0604	60
		12.9	54684-0504	50

MODEL NO. 54684-***4

REVISED
E
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15
MATERIAL NO.: SEE CHART

TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-

MOLEX INCORPORATED

DOCUMENT NO.: SD-54684-012
SHEET NO.: 3 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



44mm幅キャリアテープ

44mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.
44	45.5	26.9	54684-1204	120
		22.9	54684-1004	100

MODEL NO. 54684-***4

REVISED
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV E

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15
MATERIAL NO.: SEE CHART

TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-

MOLEX INCORPORATED

DOCUMENT NO.: SD-54684-012
SHEET NO.: 4 OF 4

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru