
samtec

E.L.P.™
EXTENDED LIFE PRODUCT
10 year Mixed Flowing Gas with 30µ" Gold
Call Samtec for maximum mated cycles



(2,54 mm) .100"

THROUGH-HOLE .025" SQ POST HEADER

Mates with:
SSW, SSQ, SSM, ESW, ESQ, BCS, BSW, CES, SLW, IDSD, IDSS, SMSD, SMSS

SPECIFICATIONS

For complete specifications see www.samtec.com?TSW or www.samtec.com?TSW

Insulator Material:
TSW: Black Glass Filled Polyester
HTSW: Natural Liquid Crystal Polymer
Terminal Material:
Phosphor Bronze
Plating:
Au or Sn over 50µ" (1,27 µm) Ni
Operating Temp Range:
-55°C to +125°C with Gold
-55°C to +105°C with Tin
Voltage Rating:
550 VAC mated with SSW;
500 VAC mated with BCS or ESQ;
450 VAC -RA/-RE mated with BCS or SSM
400 VAC mated with CES
RoHS Compliant: Yes
Lead–Free Solderable:
Wave Only


CURRENT RATING (PER PIN)						
TSW mated with						
ESW	SSW	SLW	SSQ	SSM	BCS	SNT
5.2 A	5.7 A	5.2 A	6.3 A	5.2 A	4.6 A	4.3 A
1 POSITION POWERED PER ROW						

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594 FILE NO: 090871_0_000

APPLICATIONS



ALSO AVAILABLE (MOQ Required)

- Other platings
  Contact Samtec.


Note: Some lengths, styles and options are non-standard, non-returnable.

TYPE STRIP – **PIN CENTERS** – **NO. PINS PER ROW**


TSW = Standard Strip

HTSW = Hi-Temp Strip


–1 = .100" (2,54 mm) Centers, All Positions Filled



–2 = .200" (5,08 mm) Centers, Every Other Position Filled




Straight Pin Versions



01 thru 50
= .100" (2,54 mm) Center Version


Right Angle Versions




02 thru 25
= .200" (5,08 mm) Center Version

Due to technical progress, all designs, specifications and components are subject to change without notice.


SAMTEC USA • Tel: +1-800-SAMTEC-9 or +1-812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: +1-408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: +1-800-726-8329
SAMTEC SOUTH AMERICA • Tel: +55 31 3786 3227 SAMTEC UNITED KINGDOM • Tel: +44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: +33 1 60 95 06 60 SAMTEC ITALY • Tel: +39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46 8 4477280 SAMTEC BENELUX • Tel: +44 01236 739292
SAMTEC ISRAEL • Tel: +972 3 7526600 SAMTEC INDIA • Tel: +91 80 3272 1612 SAMTEC ANZ • Tel: +613 9580 0683 SAMTEC SINGAPORE • Tel: +65 6745 5955 SAMTEC JAPAN • Tel: +81 45 475 1385
SAMTEC SHANGHAI • Tel: +86 21 6083 3766 SAMTEC SHENZHEN • Tel: +86 755 83776780 SAMTEC TAIWAN • Tel: +886 2 2735 6109 SAMTEC HONG KONG • Tel: +852 26904858 SAMTEC KOREA • Tel: +82 31 717 5685




TSW–112–07–G–T



TSW–109–10–F–D–RA



HTSW–120–13–T–D



TSW–114–16–G–S–RE

TSW, HTSW SERIES

LEAD STYLE

PLATING OPTION

–F
= Gold flash on post, Matte Tin on tail

–L
= 10µ" (0,25 µm) Gold on post, Matte Tin on tail

–G
= 10µ" (0,25 µm) Gold on post, Gold flash on balance

–T
= Matte Tin

OTHER SOLUTIONS

- Elevated Right Angle option
- Shunts

Contact Samtec

ROW OPTION

–S
= Single Row

–D
= Double Row


–T
= Triple Row

–Q
= Double Row (5,08 mm) .200" row space


OTHER OPTIONS

– RA or –RE
= Right Angle

–NA
= Right Angle (using straight body for coplanar mating with SSW-RA series)




–LL
= Locking Lead



Two leads per strip crimped in opposite directions on or near centerline. See charts for available styles. N/A with single row 1 or 2 positions. Recommended hole size (1,02 mm ± 0,03 mm) .040" ± .001"

–LC
= Locking Clip (Styles –08 thru –13 & –22 only)



Requires 4 pin minimum (NA with -T,-Q,-RA or -RE)

–LA
= –RA Option with –LL Option

–"XXX"
= Polarized Position

Straight Pin Versions

(Specify "LEAD STYLE" from chart)


	STYLE	A	B	C
*	– 05	(3,30) .130	(8,51) .335	(2,67) .105
*	– 06	(2,41) .095	(7,62) .300	(2,67) .105
*	– 07	(2,54) .100	(10,92) .430	(5,84) .230
*	– 08	(5,08) .200	(13,46) .530	
	– 09	(10,16) .400	(18,54) .730	
	–10	(12,70) .500	(21,08) .830	
	–11	(15,24) .600	(23,62) .930	
	–12	(17,78) .700	(26,16) 1.030	
	–13	(22,86) .900	(31,24) 1.230	
	–14	(2,79) .110	(13,46) .530	(8,13) .320
*	–15		(18,54) .730	(13,21) .520
*	–16	(7,87) .310		(8,13) .320
*	–17	(2,79) .110	(21,08) .830	(15,74) .620

* Available with –LL (Locking Lead) Option

	STYLE	A	B	C
*	–18	(2,79) .110	(23,62) .930	(18,29) .720
*	–19		(26,16) 1.030	(20,83) .820
*	– 20		(31,24) 1.230	(25,91) 1.020
*	– 21		(36,32) 1.430	(30,99) 1.220
*	– 22	(7,62) .300	(16,00) .630	(5,84) .230
*	– 23	(2,92) .115	(11,30) .445	
*	– 24		(12,15) .480	(6,73) .265
*	– 25	(5,33) .210	(16,00) .630	(8,13) .320
▲	– 26	(3,20) .126	(11,58) .456	(5,84) .230
	– 27	(25,40) 1.000	(33,78) 1.330	
	– 28	(20,32) .800	(28,70) 1.130	
	– 29	(23,11) .910	(33,78) 1.330	(8,13) .320
	– 30	(18,03) .710	(28,70) 1.130	
+	– 41	(0,89) .035	(9,27) .365	(5,84) .230
+	– 42	(1,27) .050	(11,94) .470	(8,13) .320

\+ Style –41 & –42 available with HTSW only.

▲Except: Style –26 (0,46) .018 DIA Tail



Specify -07 for best mate with IDXX Series IDC Cable

Right Angle Versions


(Specify "LEAD STYLE" from chart and select –RA or –RE from other options)

	–RA LEAD STYLE	SINGLE (–S) A	SINGLE (–S) C	DOUBLE (–D) A	TRIPLE (–T & –Q) A
	– 08	(2,29) .090	(5,84) .230	(2,29) .090	(2,29) .090
	– 09	(7,37) .290		(7,37) .290	(7,37) .290
	–10	(9,91) .390		(9,91) .390	(9,91) .390
	–11	(12,45) .490		(12,45) .490	(12,45) .490
	–12	(14,99) .590		(14,99) .590	(14,99) .590
	–13	(20,07) .790		(20,07) .790	N/A
*	–16	(5,08) .200	(8,13) .320	(5,08) .200	(5,08) .200
	– 21	(25,15) .990	(5,84) .230	N/A	N/A
*	– 22	(4,83) .190		(4,83) .190	(4,83) .190
*	– 25	(2,54) .100	(8,13) .320	(2,54) .100	(2,54) .100
	– 27	(22,61) .890	(5,84) .230	N/A	N/A
	– 28	(17,53) .690		(17,53) .690	
	– 29	(20,32) .800	(8,13) .320	N/A	
	– 30	(15,24) .600		(15,24) .600	

– RE LEAD STYLE	SINGLE A	C
– 09	(4,83) .190	(5,84) .230
–10	(7,37) .290	
–11	(9,91) .390	
–12	(12,45) .490	
–13	(17,53) .690	
–16	(2,54) .100	(8,13) .320
– 21	(22,61) .890	(5,84) .230
– 22	(2,29) .090	
– 27	(20,07) .790	
– 28	(14,99) .590	

*Available with –LA (Locking Lead) Option

LEAD STYLE	B
–RA	(1,52) .060
–RE	(4,06) .160



Due to technical progress, all designs, specifications and components are subject to change without notice.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru