
# Optocoupler, Phototransistor Output, High Reliability, 5300 $V_{RMS}$




## FEATURES

- Good CTR linearity depending on forward current
- Isolation test voltage, 5300 $V_{RMS}$
- High collector emitter voltage, $V_{CEO}$ = 70 V
- Low saturation voltage
- Fast switching times
- Low CTR degradation
- Temperature stable
- Low coupling capacitance
- End stackable, 0.100" (2.54 mm) spacing
- High common mode interference immunity
- Lead (Pb)-free component
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

Pb-free
e3
RoHS COMPLIANT

## DESCRIPTION

The SFH610A (DIP) and SFH6106 (SMD) feature a high current transfer ratio, low coupling capacitance and high isolation voltage. These couplers have a GaAs infrared diode emitter, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a plastic DIP-4 or SMD package.

The coupling devices are designed for signal transmission between two electrically separated circuits.

The couplers are end-stackable with 2.54 mm spacing.

Creepage and clearance distances of > 8.0 mm are achieved with option 6. This version complies with IEC 60950 (DIN VDE 0805) for reinforced insulation up to an operation voltage of 400 $V_{RMS}$ or DC. Specifications subject to change.

## AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- DIN EN 60747-5-5 (VDE 0884) available with option 1
- CSA 93751
- BSI IEC 60950; IEC 60065

## ORDERING INFORMATION

| PART | REMARKS |
|---|---|
| SFH610A-1 | CTR 40 % to 80 %, DIP-4 |
| SFH610A-2 | CTR 63 % to 125 %, DIP-4 |
| SFH610A-3 | CTR 100 % to 200 %, DIP-4 |
| SFH610A-4 | CTR 160 % to 320 %, DIP-4 |
| SFH610A-5 | CTR 250 % to 500 %, DIP-4 |
| SFH6106-1 | CTR 40 % to 80 %, SMD-4 |
| SFH6106-2 | CTR 63 % to 125 %, SMD-4 |
| SFH6106-3 | CTR 100 % to 200 %, SMD-4 |
| SFH6106-4 | CTR 160 % to 320 %, SMD-4 |
| SFH6106-5T | CTR 250 % to 500 %, SMD-4, tape and reel |
| SFH610A-1X006 | CTR 40 % to 80 %, DIP-4 400 mil |
| SFH610A-1X018T | CTR 40 % to 80 %, SMD-4 400 mil, wide leadspread |
| SFH610A-2X006 | CTR 63 % to 125 %, DIP-4 400 mil |
| SFH610A-3X006 | CTR 100 % to 200 %, DIP-4 400 mil |
| SFH610A-3X007 | CTR 100 % to 200 %, SMD-4 |
| SFH610A-4X006 | CTR 160 % to 320 %, DIP-4 400 mil |

**Note**

- For additional information on the available options refer to option information.



For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| ABSOLUTE MAXIMUM RATINGS ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | |
|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **SYMBOL** | **VALUE** | **UNIT** |
| **INPUT** | | | | |
| Reverse voltage | | $V_R$ | 6 | V |
| DC forward current | | $I_F$ | 60 | mA |
| Surge forward current | t ≤ 10 µs | $I_{FSM}$ | 2.5 | A |
| Power dissipation | | $P_{diss}$ | 100 | mW |
| **OUTPUT** | | | | |
| Collector emitter voltage | | $V_{CE}$ | 70 | V |
| Emitter collector voltage | | $V_{EC}$ | 7 | V |
| Collector current | | $I_C$ | 50 | mA |
| | $t_p$ ≤ 1.0 ms | $I_C$ | 100 | mA |
| Power dissipation | | $P_{diss}$ | 150 | mW |
| **COUPLER** | | | | |
| Isolation test voltage between emitter and detector | | $V_{ISO}$ | 5300 | $V_{RMS}$ |
| Creepage distance | | | ≥ 7 | mm |
| Clearance distance | | | ≥ 7 | mm |
| Insulation thickness between emitter and detector | | | ≥ 0.4 | mm |
| Comparative tracking index per DIN IEC112/VDE 0303 part 1 | | | ≥ 175 | |
| Isolation resistance | $V_{IO}$ = 500 V, $T_{amb}$ = 25 °C | $R_{IO}$ | ≥ $10^{12}$ | Ω |
| | $V_{IO}$ = 500 V, $T_{amb}$ = 100 °C | $R_{IO}$ | ≥ $10^{11}$ | Ω |
| Storage temperature range | | $T_{stg}$ | - 55 to + 150 | °C |
| Ambient temperature range | | $T_{amb}$ | - 55 to + 100 | °C |
| Soldering temperature (1) | max. 10 s, dip soldering distance to seating plane ≥ 1.5 mm | $T_{sld}$ | 260 | °C |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

(1) Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **INPUT** | | | | | | | |
| Forward voltage | $I_F$ = 60 mA | | $V_F$ | | 1.25 | 1.65 | V |
| Reverse current | $V_R$ = 6 V | | $I_R$ | | 0.01 | 10 | µA |
| Capacitance | $V_R$ = 0 V, f = 1 MHz | | $C_O$ | | 13 | | pF |
| Thermal resistance | | | $R_{thja}$ | | 750 | | K/W |
| **OUTPUT** | | | | | | | |
| Collector emitter capacitance | $V_{CE}$ = 5 V, f = 1 MHz | | $C_{CE}$ | | 5.2 | | pF |
| Thermal resistance | | | $R_{thja}$ | | 500 | | K/W |
| Collector emitter leakage current | $V_{CE}$ = 10 V | SFH610A-1 | $I_{CEO}$ | | 2 | 50 | nA |
| | | SFH6106-1 | $I_{CEO}$ | | 2 | 50 | nA |
| | | SFH610A-2 | $I_{CEO}$ | | 2 | 50 | nA |
| | | SFH6106-2 | $I_{CEO}$ | | 2 | 50 | nA |
| | | SFH610A-3 | $I_{CEO}$ | | 5 | 100 | nA |
| | | SFH6106-3 | $I_{CEO}$ | | 5 | 100 | nA |
| | | SFH610A-4 | $I_{CEO}$ | | 5 | 100 | nA |
| | | SFH6106-4 | $I_{CEO}$ | | 5 | 100 | nA |
| | | SFH610A-5 | $I_{CEO}$ | | 5 | 100 | nA |
| | | SFH6106-5T | $I_{CEO}$ | | 5 | 100 | nA |



For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| ELECTRICAL CHARACTERISTICS ($T_{amb}$ = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **COUPLER** | | | | | | | |
| Collector emitter saturation voltage | $I_F$ = 10 mA, $I_C$ = 2.5 mA | | $V_{CEsat}$ | | 0.25 | 0.4 | V |
| Coupling capacitance | f = 1 MHz | | $C_C$ | | 0.4 | | pF |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

| CURRENT TRANSFER RATIO | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| $I_C/I_F$ | $I_F$ = 10 mA, $V_{CE}$ = 5.0 V | SFH610A-1 | CTR | 40 | | 80 | % |
| | | SFH6106-1 | CTR | 40 | | 80 | % |
| | | SFH610A-2 | CTR | 63 | | 125 | % |
| | | SFH6106-2 | CTR | 63 | | 125 | % |
| | | SFH610A-3 | CTR | 100 | | 200 | % |
| | | SFH6106-3 | CTR | 100 | | 200 | % |
| | | SFH610A-4 | CTR | 160 | | 320 | % |
| | | SFH6106-4 | CTR | 160 | | 320 | % |
| | | SFH610A-5 | CTR | 250 | | 500 | % |
| | | SFH6106-5T | CTR | 250 | | 500 | % |
| | $I_F$ = 1 mA, $V_{CE}$ = 5 V | SFH610A-1 | CTR | 13 | 30 | | % |
| | | SFH6106-1 | CTR | 13 | 30 | | % |
| | | SFH610A-2 | CTR | 22 | 45 | | % |
| | | SFH6106-2 | CTR | 22 | 45 | | % |
| | | SFH610A-3 | CTR | 34 | 70 | | % |
| | | SFH6106-3 | CTR | 34 | 70 | | % |
| | | SFH610A-4 | CTR | 56 | 90 | | % |
| | | SFH6106-4 | CTR | 56 | 90 | | % |

| SWITCHING CHARACTERISTICS | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **PART** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| **NON-SATURATED** | | | | | | | |
| Current | $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $I_F$ | | 10 | | mA |
| Rise time | $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_r$ | | 2 | | µs |
| Fall time | $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_f$ | | 2 | | µs |
| Turn-on time | $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_{on}$ | | 3 | | µs |
| Turn-off time | $V_{CC}$ = 5 V, $R_L$ = 75 Ω | | $t_{off}$ | | 2.3 | | µs |
| Cut-off frequency | $V_{CC}$ = 5 V | | $F_{CO}$ | | 250 | | kHz |
| **SATURATED** | | | | | | | |
| Current | | SFH610A-1 | $I_F$ | | 20 | | mA |
| | | SFH6106-1 | | | | | |
| | | SFH610A-2 | $I_F$ | | 10 | | mA |
| | | SFH6106-2 | | | | | |
| | | SFH610A-3 | $I_F$ | | 10 | | mA |
| | | SFH6106-3 | | | | | |
| | | SFH610A-4 | $I_F$ | | 5 | | mA |
| | | SFH6106-4 | | | | | |



For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| SWITCHING CHARACTERISTICS | | | | | | | |
|---|---|---|---|---|---|---|---|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| SATURATED | | | | | | | |
| Rise time | | SFH610A-1 | $t_r$ | | 2 | | µs |
| | | SFH6106-1 | | | | | |
| | | SFH610A-2 | $t_r$ | | 3 | | µs |
| | | SFH6106-2 | | | | | |
| | | SFH610A-3 | $t_r$ | | 3 | | µs |
| | | SFH6106-3 | | | | | |
| | | SFH610A-4 | $t_r$ | | 4 | | µs |
| | | SFH6106-4 | | | | | |
| Fall time | | SFH610A-1 | $t_f$ | | 11 | | µs |
| | | SFH6106-1 | | | | | |
| | | SFH610A-2 | $t_f$ | | 14 | | µs |
| | | SFH6106-2 | | | | | |
| | | SFH610A-3 | $t_f$ | | 14 | | µs |
| | | SFH6106-3 | | | | | |
| | | SFH610A-4 | $t_f$ | | 15 | | µs |
| | | SFH6106-4 | | | | | |
| Turn-on time | | SFH610A-1 | $t_{on}$ | | 3 | | µs |
| | | SFH6106-1 | | | | | |
| | | SFH610A-2 | $t_{on}$ | | 4.2 | | µs |
| | | SFH6106-2 | | | | | |
| | | SFH610A-3 | $t_{on}$ | | 4.2 | | µs |
| | | SFH6106-3 | | | | | |
| | | SFH610A-4 | $t_{on}$ | | 6 | | µs |
| | | SFH6106-4 | | | | | |
| Turn-off time | | SFH610A-1 | $t_{off}$ | | 18 | | µs |
| | | SFH6106-1 | | | | | |
| | | SFH610A-2 | $t_{off}$ | | 23 | | µs |
| | | SFH6106-2 | | | | | |
| | | SFH610A-3 | $t_{off}$ | | 23 | | µs |
| | | SFH6106-3 | | | | | |
| | | SFH610A-4 | $t_{off}$ | | 25 | | µs |
| | | SFH6106-4 | | | | | |

**Note**

- All values presented are typical values.



For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| SAFETY AND INSULATIO RATINGS | | | | | | |
|---|---|---|---|---|---|---|
| **PARAMETER** | **TEST CONDITION** | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNIT** |
| Climatic classification (according to IEC 68 part 1) | | | | 55/100/21 | | |
| Comparative tracking index | | CTI | 175 | | 399 | |
| $V_{IOTM}$ | | | 10000 | | | V |
| $V_{IORM}$ | | | 890 | | | V |
| $P_{SO}$ | | | | | 400 | mW |
| $I_{SI}$ | | | | | 275 | mA |
| $T_{SI}$ | | | | | 175 | °C |
| Creepage distance | standard DIP-4 | | 7 | | | mm |
| Clearance distance | standard DIP-4 | | 7 | | | mm |
| Creepage distance | 400 mil DIP-4 | | 8 | | | mm |
| Clearance distance | 400 mil DIP-4 | | 8 | | | mm |
| Insulation thickness, reinforced rated | per IEC 60950 2.10.5.1 | | 0.4 | | | mm |

**Note**

- As per IEC 60747-5-2, § 7.4.3.8.1, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

## TYPICAL CHARACTERISTICS ($T_{amb}$ = 25 °C, unless otherwise specified)





Fig. 1 - Linear Operation (without saturation)





Fig. 3 - Switching Operation (with saturation)





Fig. 2 - Current Transfer Ratio (CTR) vs. Temperature





Fig. 4 - Output Characteristics (typ.) Collector Current vs. Collector Emitter Voltage



For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 5 - Diode Forward Voltage vs. Forward Current





Fig. 8 - Permissible Power Dissipation vs. Temperature





Fig. 6 - Transistor Capacitance (typ.) vs. Collector Emitter Voltage





Fig. 9 - Permissible Diode Forward Current vs. Ambient Temperature






Fig. 7 - Permissible Pulse Handling Capability Forward Current vs. Pulse Width




For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

**PACKAGE DIMENSIONS** in inches (millimeters)











For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


**Option 6**




**Option 7**




**Option 8**






For technical questions, contact: optocoupleranswers@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**

## Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

## Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/