Low Charge Injection 16-Channel High Voltage Analog Switch with Bleed Resistors

Features

- HVCMOS technology for high performance
- Integrated bleed resistors on the outputs
- 16 Channels of high voltage analog switch
- 3.3V input logic level compatible
- 20MHz data shift clock frequency
- Very low quiescent power dissipation-10µA
- Low parasitic capacitance
- DC to 10MHz analog signal frequency
- -60dB typical off-isolation at 5MHz
- CMOS logic circuitry for low power
- Excellent noise immunity
- Cascadable serial data register with latches
- Flexible operating supply voltages

Applications

- Medical ultrasound imaging
- NDT metal flaw detection
- Piezoelectric transducer drivers
- Optical MEMS modules


General Description

The Supertex HV2701 is a low charge injection, 16-channel, high voltage, analog switch integrated circuit (IC) with bleed resistors. The device can be used in applications requiring high voltage switching controlled by low voltage control signals, such as medical ultrasound imaging and piezoelectric transducer drivers. The bleed resistors eliminate voltage built up on capacitive loads such as piezoelectric transducers.

Input data is shifted into a 16-bit shift register that can then be retained in a 16-bit latch. To reduce any possible clock feed-through noise, the latch enable bar should be left high until all bits are clocked in. Data is clocked in during the rising edge of the clock. Using HVCMOS technology, this device combines high voltage bilateral DMOS switches and low power CMOS logic to provide efficient control of high voltage analog signals.

The device is suitable for various combinations of high voltage supplies, e.g., V_{PP}/V_{NN}: +40V/-160V, +100V/-100V, and +160V/-40V.

Block Diagram




Ordering Information

DEVICE	Package Options
	48-Lead LQFP (FG) *(7x7x1.4mm body, 0.50mm pitch)*
HV2701	HV2701FG-G

-G indicates package is RoHS compliant ('Green')

Pin Configuration



48-Lead LQFP Package (FG)
(top view)

Absolute Maximum Ratings

Parameter	Value
V_{DD} Logic supply	-0.5V to +7V
V_{PP}-V_{NN} differential supply	220V
V_{PP} Positive supply	-0.5V to V_{NN}+200V
V_{NN} Negative supply	+0.5V to -200V
Logic input voltage	-0.5V to V_{DD} +0.3V
Analog signal range	V_{NN} to V_{PP}
Peak analog signal current/channel	3.0A
Storage temperature	-65°C to 150°C
Power dissipation	1.0W


Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

Product Marking

Top Marking



Bottom Marking



YY = Year Sealed
WW = Week Sealed
L = Lot Number
C = Country of Origin*
A = Assembler ID*
_____ = "Green" Packaging

**May be part of top marking*

48-Lead LQFP Package (FG)

Recommended Operation Conditions

Symbol	Parameter	Value
V_{DD}	Logic power supply voltage	3.0V to 5.5V
V_{PP}	Positive high voltage supply	+40V to V_{NN} +200V
V_{NN}	Negative high voltage supply	-40V to –160V
V_{IH}	High level input voltage	0.9V_{DD} to V_{DD}
V_{IL}	Low level input voltage	0V to 0.1V_{DD}
V_{SIG}	Analog signal voltage peak-to-peak	V_{NN}+10V to V_{PP}- 0V
T_A	Operating free air temperature	0°C to 70°C

Notes:

1. Power up/down sequence is arbitrary except GND must be powered-up first and powered-down last.
2. V_{SIG} must be within V_{NN} and V_{PP} or floating during power up/down transition.
3. Rise and fall times of power supplies V_{DD}, V_{PP}, and V_{NN} should not be less than 1.0msec.

DC Electrical Characteristics

(over recommended operating conditions unless otherwise noted)

Sym	Parameter	0°C		+25°C			+70°C		Units	Conditions	
		Min	Max	Min	Typ	Max	Min	Max			
R_{ONS}	Small signal switch on-resistance	-	30	-	26	38	-	48	Ω	I_{SIG} = 5.0mA	V_{PP} = +40V, V_{NN} = -160V
		-	25	-	22	27	-	32		I_{SIG} = 200mA	
		-	25	-	22	27	-	30		I_{SIG} = 5.0mA	V_{PP} = +100V, V_{NN} = -100V
		-	18	-	18	24	-	27		I_{SIG} = 200mA	
		-	23	-	20	25	-	30		I_{SIG} = 5.0mA	V_{PP} = +160V, V_{NN} = -40V
		-	22	-	16	25	-	27		I_{SIG} = 200mA	
ΔR_{ONS}	Small signal switch on-resistance matching	-	20	-	5.0	20	-	20	%	I_{SIG} = 5.0mA, V_{PP} = +100V, V_{NN} = -100V	
R_{ONL}	Large signal switch on-resistance	-	-	-	15	-	-	-	Ω	V_{SIG} = V_{PP} -10V, I_{SIG} = 1.0A	
R_{INT}	Value of output bleed resistor	-	-	20	35	50	-	-	KΩ	Output Switch to RGND I_{RINT} = 0.5mA	
I_{SOL}	Switch off leakage per switch*	-	5.0	-	1.0	10	-	15	µA	V_{SIG} = V_{PP} -10V and V_{NN} +10V	
V_{OS}	DC offset switch off*	-	300	-	100	300	-	300	mV	No Load	
	DC offset switch on*	-	500	-	100	500	-	500	mV		
I_{PPQ}	Quiescent V_{PP} supply current	-	-	-	10	50	-	-	µA	All switches off	
I_{NNQ}	Quiescent V_{NN} supply current	-	-	-	-10	-50	-	-	µA	All switches off	
I_{PPQ}	Quiescent V_{PP} supply current	-	-	-	10	50	-	-	µA	All switches on, I_{SW} = 5.0mA	
I_{NNQ}	Quiescent V_{NN} supply current	-	-	-	-10	-50	-	-	µA	All switches on, I_{SW} = 5.0mA	
I_{SW}	Switch output peak current	-	3.0	-	3.0	2.0	-	2.0	A	V_{SIG} duty cycle < 0.1%	
f_{SW}	Output switching frequency	-	-	-	-	50	-	-	kHz	Duty cycle = 50%	
I_{PP}	Average V_{PP} supply current	-	6.5	-	-	7.0	-	8.0	mA	V_{PP} = +40V, V_{NN} = -160V	All output switches are turning On and Off at 50KHz with no load.
		-	4.0	-	-	5.5	-	5.5		V_{PP} = +100V, V_{NN} = -100V	
		-	4.0	-	-	5.0	-	5.5		V_{PP} = +160V, V_{NN} = -40V	
I_{NN}	Average V_{NN} supply current	-	6.5	-	-	7.0	-	8.0	mA	V_{PP} = +40V, V_{NN} = -160V	
		-	4.0	-	-	5.0	-	5.5		V_{PP} = +100V, V_{NN} = -100V	
		-	4.0	-	-	5.0	-	5.5		V_{PP} = +160V, V_{NN} = -40V	
I_{DD}	Average V_{DD} supply current	-	4.0	-	-	4.0	-	4.0	mA	f_{CLK} = 5.0MHz, V_{DD} = 5.0V	
I_{DDQ}	Quiescent V_{DD} supply current	-	10	-	-	10	-	10	µA	All logic inputs are static	
I_{SOR}	Data out source current	0.45	-	0.45	0.70	-	0.40	-	mA	V_{OUT} = V_{DD} -0.7V	
I_{SINK}	Data out sink current	0.45	-	0.45	0.70	-	0.40	-	mA	V_{OUT} = 0.7V	
C_{IN}	Logic input capacitance	-	10	-	-	10	-	10	pF	---	

** See Test Circuits on page 5*


AC Electrical Characteristics

(over recommended operating conditions, V_{DD}= 5.0V, $t_R = t_F \leq$ 5.0ns, 50% duty cycle, C_{LOAD} = 20pF, unless otherwise noted)


Sym	Parameter	0°C		+25°C			+70°C		Units	Conditions
		Min	Max	Min	Typ	Max	Min	Max		
t_{SD}	Set up time before $\overline{LE}$ rises	25	-	25	-	-	25	-	ns	---
t_{WLE}	Time width of $\overline{LE}$	56	-	-	56	-	56	-	ns	V_{DD} = 3.0V
		12	-	-	12	-	12	-		V_{DD} = 5.0V
t_{DO}	Clock delay time to data out	50	100	50	78	100	50	100	ns	V_{DD} = 3.0V
		15	40	15	30	40	15	40		V_{DD}= 5.0V
t_{WCL}	Time width of CL	55	-	55	-	-	55	-	ns	---
t_{SU}	Set up time data to clock	21	-	-	21	-	21	-	ns	V_{DD}= 3.0V
		7	-	-	7	-	7	-		V_{DD}= 5.0V
t_H	Hold time data from clock	2	-	2	-	-	2	-	ns	V_{DD}= 3.0 or 5.0V
f_{CLK}	Clock frequency	-	8	-	-	8	-	8	MHz	V_{DD}= 3.0V
		-	20	-	-	20	-	20		V_{DD}= 5.0V
t_R,t_F	Clock rise and fall times	-	50	-	-	50	-	50	ns	----
T_{ON}	Turn ON time*	-	5.0	-	-	5.0	-	5.0	µs	V_{SIG} = V_{PP}-10V, R_{LOAD} = 10KΩ
T_{OFF}	Turn OFF time*	-	5.0	-	-	5.0	-	5.0	µs	V_{SIG} = V_{PP}-10V, R_{LOAD} = 10KΩ
dv/dt	Maximum V_{SIG} slew rate	-	20	-	-	20	-	20	v/ns	V_{PP} = +40V, V_{NN} = -160V
		-	20	-	-	20	-	20		V_{PP} = +100V, V_{NN} = -100V
		-	20	-	-	20	-	20		V_{PP} = +160V, V_{NN} = -40V
K_O	Off isolation*	-30	-	-30	-33	-	-30	-	dB	f = 5.0MHz, 1KΩ//15pF load
		-58	-	-58	-	-	-58	-		f = 5.0MHz, 50Ω load
K_{CR}	Switch crosstalk*	-60	-	-60	-70	-	-60	-	dB	f = 5.0MHz, 50Ω load
I_{ID}	Output switch isolation diode current	-	300	-	-	300	-	300	mA	300ns pulse width, 2.0% duty cycle
$C_{SG(OFF)}$	Off capacitance SW to GND	5.0	17	5.0	12	17	5.0	17	pF	0V, f = 1.0MHz
$C_{SG(ON)}$	On capacitance SW to GND	25	50	25	38	50	25	50	pF	0V, f = 1.0MHz
$+V_{SPK}$	Output voltage spike*	-	-	-	-	150	-	-	mV	V_{PP} = +40V, V_{NN} = -160V, R_{LOAD} = 50Ω
$-V_{SPK}$										
$+V_{SPK}$		-	-	-	-	150	-	-		V_{PP} = +100V, V_{NN} = -100V, R_{LOAD} = 50Ω
$-V_{SPK}$										
$+V_{SPK}$		-	-	-	-	150	-	-		V_{PP} = +160V, V_{NN} = -40V, R_{LOAD} = 50Ω
$-V_{SPK}$										
QC	Charge injection*	-	-	-	820	-	-	-	pC	V_{PP}= +40V, V_{NN}= -160V, V_{SIG}= 0V
		-	-	-	600	-	-	-		V_{PP}= +100V, V_{NN}= -100V, V_{SIG}= 0V
		-	-	-	350	-	-	-		V_{PP}= +160V, V_{NN}= -40V, V_{SIG}= 0V

** See Test Circuits on page 5*


HV2701 Test Circuits




Switch Off Leakage
per Switch




DC Offset Switch
ON/OFF




TURN (TON/TOFF)
ON/OFF TIME




OFF Isolation




Output Switch Isolation
Diode Current



Switch Crosstalk



Q = 1000pF x ΔV_{OUT}
Charge Injection



Output Voltage Spike


Logic Function Table

D0	D1	...	D7	D8	...	D15	$\overline{LE}$	CL	SW0	SW1	...	SW7	SW8	...	SW15
L	-		-	-		-	L	L	OFF	-		-	-		-
H	-		-	-		-	L	L	ON	-		-	-		-
-	L		-	-		-	L	L	-	OFF		-	-		-
-	H		-	-		-	L	L	-	ON		-	-		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		L	-		-	L	L	-	-		OFF	-		-
-	-		H	-		-	L	L	-	-		ON	-		-
-	-	...	-	L	...	-	L	L	-	-	...	-	OFF	...	-
-	-		-	H		-	L	L	-	-		-	ON		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		-	-		-	L	L	-	-		-	-		-
-	-		-	-		L	L	L	-	-		-	-		OFF
-	-		-	-		H	L	L	-	-		-	-		ON
X	X	X	X	X	X	X	H	L	HOLD PREVIOUS STATE						
X	X	X	X	X	X	X	X	H	ALL SWITCHES OFF						

Notes:

1. *The 16 switches operate independently.*
2. *Serial data is clocked in on the L to H transition of the CLK.*
3. *All 16 switches go to a state retaining their latched condition at the rising edge of $\overline{LE}$. When $\overline{LE}$ is low the shift registers data flow through the latch.*
4. *D_{OUT} is high when data in the shift register 15 is high.*
5. *Shift registers clocking has no effect on the switch states if $\overline{LE}$ is high.*
6. *The CL clear input overrides all other inputs.*

Logic Timing Waveforms




Pin Configuration
48-Lead LQFP (FG)

Pin #	Function	Pin #	Function	Pin #	Function	Pin #	Function
1	NC	13	VNN	25	SW15B	37	SW10B
2	NC	14	NC	26	SW15A	38	SW10A
3	SW4B	15	VPP	27	SW14B	39	SW9B
4	SW4A	16	NC	28	SW14A	40	SW9A
5	SW3B	17	GND	29	SW13B	41	SW8B
6	SW3A	18	VDD	30	SW13A	42	SW8A
7	SW2B	19	DIN	31	SW12B	43	SW7B
8	SW2A	20	CLK	32	SW12A	44	SW7A
9	SW1B	21	$\overline{\text{LE}}$	33	SW11B	45	SW6B
10	SW1A	22	CLR	34	SW11A	46	SW6A
11	SW0B	23	DOUT	35	NC	47	SW5B
12	SW0A	24	RGND	36	NC	48	SW5A


NC = No Internal Connection

48-Lead LQFP Package Outline (FG)


7x7mm body, 1.4mm height (min), 0.50mm pitch



Top View



View B



Side View

Note 1:

A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier may be either a mold, or an embedded metal or marked feature.

Symbol		A	A1	A2	b	D	D1	E	E1	e	L	L1	L2	θ
Dimension (mm)	MIN	1.40	0.05	1.35	0.17	8.80	6.80	8.80	6.80	0.50 BSC	0.45	1.00 REF	0.25 BSC	0°
	NOM	-	-	1.40	0.22	9.00	7.00	9.00	7.00		0.60			3.5°
	MAX	1.60	0.15	1.45	0.27	9.20	7.20	9.20	7.20		0.75			7°

JEDEC Registration MS-026, Variation BBC, Issue D, Jan. 2001.

Drawings not to scale.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to http://www.supertex.com/packaging.html.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell its products for use in such applications, unless it receives an adequate "product liability indemnification insurance agreement". **Supertex** does not assume responsibility for use of devices described and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the **Supertex** website: http//www.supertex.com.

©2007 **Supertex inc.** All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 222-8888 / FAX: (408) 222-4895
www.supertex.com

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/