

















参考基板レイアウト（マウント面）
P.C.B. PATTERN DIMENSION.(REFERENCE)
(MOUNTING AREA)

注記 NOTES

1. 使用材料 MATERIAL
   ハウジング：液晶ポリマー ガラス充填 UL94V-0 茶色
   HOUSING:LIQUID CRYSTAL POLYMER, GLASS FILLED, UL94V-0, COLOR BROWN
   ターミナル：リン青銅（t＝0.15）
   TERMINAL:PHOSPHOR BRONZE(t=0.15)
2. メッキ仕様 PLATING
   金メッキ （コンタクト部）
   GOLD PLATING (CONTACT AREA)
   錫メッキ(テール部)
   TIN PLATING (TAIL AREA)
   下地メッキ：ニッケルメッキ
   UNDER PLATING : NICKEL
3. △3 テール部に適用。
   APPLY TO THE TAIL AREA.
4. 嵌合相手：55394 / 503376 シリーズ
   MATE WITH : 55394 / 503376 SERIES.
5. テール平坦度は、0.08 以下
   TAIL COPLANARITY TO BE 0.08MAXIMUM
6. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT

D	C	B	A	EMBOSSED TAPE	MATERIAL No.	CKT.
23.0	23.1	21.6	23.6	54552-1102	54552-1100	110
19.0	19.1	17.6	19.6	54552-0902	54552-0900	90
9.0	9.1	7.6	9.6	54552-0402	54552-0400	40
7.8	7.9	6.4	8.4	54552-0342	54552-0340	34
7.0	7.1	5.6	7.6	54552-0302	54552-0300	30
				ORDER No. オーダー番号	MODEL No. : 54552-×××0	

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA
APPR:NUKITA 2009/03/30
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03


TITLE: 0.4 B/B CONN RA REC HSG ASSY


MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-023
SHEET NO.: 1 OF 1
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION









DETAIL D

NOTES

1. 製品詳細寸法については SD-54552-023 を参照下さい。
   RE DETAILED DIMENSION, SEE SD-54552-023.
2. 梱包数量：１５００個／リール
   NUMBER OF CONNECTORS : 1500PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH



4. トップテープの剥離強度：0.1～1.3N {10～130gf}（剥離方向は下図参照）
   尚、本規格値は出荷時に適用。（但し、輸送時に剥離が発生しないこと。）
   PEELING OFF FORCE OF TOP TAPE : 0.1～1.3N {10～130gf}
   (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG.)
   THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
   PEEL OFF SHOULD NOT BE ALLOWED , DURING TRANSPORTATION.



5. 材料(MATERIAL)
   キャリアテープ(CARRIER TAPE)：ポリプロピレン(POLYPROPYLENE)
   トップテープ(TOPTAPE)：PET , PE , PEF
   リール(REEL)：ポリスチレン（PS） <リサイクル材を含む>
   POLYSTYRENE (PS) <RECYCLE MATERIAL CONTAINED>
6. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT

MATERIAL NO.	極数 CIRCUITS
54552-1102	110
54552-0902	90
54552-0402	40
54552-0342	34
54552-0302	30

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV C


GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY	N.AIDA
DATE	'05/02/03
CHECKED BY	K.TOYODA
DATE	'05/02/03
APPROVED BY	N.UKITA
DATE	'05/02/03
MATERIAL NO.	SEE TABLE
TITLE	EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY
	MOLEX INCORPORATED
DOCUMENT NO.	SD-54552-024
SHEET NO.	1 OF 4
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



24mm幅キャリアテープ
24mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	極数 CIRCUITS
24	29.4	25.4	9.8	54552-0402	40
			8.6	54552-0342	34
			7.8	54552-0302	30

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 2 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



32	37.4	33.4	19.8	54552-0902	90
キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL. NO.	極数 CIRCUIT

MODEL NO. 54552-×××2

REVISED
EC NO: J2009-2156
DRWN:MTAKASAKI 2009/03/26
CH'KD:THARUYAMA 2009/03/27
APPR:NUKITA 2009/03/30
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 3 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



44	49.4	45.4	23.8	54552-1102	110
キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	極数 CIRCUITS

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 4 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9