




old P/N (without V42254-)
TE P/N
Manufacturing date consisting of:
2 digits for the year (YY), 2 digits for the week (WW) and 1 digit for the day (D)





































Housing material: PBTP 30% glassfilled (UL94V-0)
pebble grey (similar RAL 7032)




Housing material: PBTP 30% glassfilled (UL94V-0)
pebble grey (similar RAL 7032)



Housing material: PBTP 30% glassfilled (UL94V-0)
pebble grey (similar RAL 7032)

Mounting holes in PCB

Bauform	n	a	b
B C	31	78.74	88.9
B/2 C/2	15	38.1	48.26
B/3 C/3	9	22.86	33.02



V42254 - ✱1✱✱✱ - +✱✱✱

B : Standard version
F : Version with flux tight coating


code for performance level
code for termination style

Style, no of contacts
and contact assignment
see page 2

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS CORORATION, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

Termination Style

Soldering/Wire-Wrap pins




	L	Code
	3 -0.4	00
	2.9±0.3	01
	4.5±0.3	02
	13 +0.5	40
	11 +0.5	41
	17 +0.5	42
Soldering lugs	5.5±0.3 10 -0.5	35

1) Cutting edges not plated


Terminations with galvanic Sn plating

V42254-B1✱✱✱-C✱✱✱

Soldering lug



Contact: Dimensions, plating, material, premating



1) Reference area for plating


	L	A	B
normal contacts	4.8	3.5	4.2
pre-mating contacts	5.8	4.5	5.2

V42254-B1✱✱✱-C✱✱✱


Performance level acc to DIN41612 and IEC603-2	Noble metals	Code
Class I	PdNi + Au or Au	1
	Au	4
Class II	PdNi + Au or Au	2
	Au	5
Class III	PdNi + Au or Au	3

Nickel underlayer
Protection film : HF-grease

Male connecctor with board locks



Wounted in PC-boards
of 1.5 to 1.8 mm
Fm =< 60 N
Fr >= 20 N
Fr >= 200 N, wenn
soldered-in



Fm = Mounting force
(for 1 connector = 2 Clips)

Fr = Retention force
(for 1 connector = 2 Clips)

Wounted in PC-boards
over 1.8 mm
Fm =< 60 N
Fr >= 16 N



TE Connectivity

REV.	CHANGE ORDER	DATE	APP.
B6	ECR-10-004503	13SEP11	MKO
B5	ECR-10-002555	01JUN10	MKO
B4	SR10-0177-03	18 JUN 03	KV
B3	SR10-0415-02	16 Sep 02	BC
B2	SR10-0157-02	15 Mar 02	BC
B1	SR10-0130-02	28 feb 02	BC
B	SR10-0198-01	21.05.01	BC
A	WO 00/7012	20.07.00	VS

DATE '10.02.89
NAME Cuvelier
DEP. PD COM

LOC GW DIMENSIONS IN MM

TOLERANCE UNLESS SPECIFIED OTHERWISE

SCALE
WEIGHT
MATERIAL

PART NAME
Pin Assembly Eurocard
Types B, C and short versions

PART NO. V42254-B1✱✱✱-C✱✱✱-✱-7626

SHT. 1+

Customer Drawing Nr. C 1392009-8

OF 2

		Product description code	Part Number	Style & Number of Positions	Termination posts	Loaded Rows	Standard Pre-Mating (1mm ¹))	Performance Level	Board Locks	
SUPERSEDED BY 5-1393644-6		V42254-B1100-B200	1393644-1	B20	right-angle solder leads	every row , every pitch	No	1	No	
		V42254-B1100-B230	1393644-2	B20	right-angle solder leads	every row , every pitch	Yes	1	No	
SUPERSEDED BY 5-1393644-9		V42254-B1100-B320	1393644-3	B32	right-angle solder leads	every row , every pitch	No	1	No	
SUPERSEDED BY 6-1393644-3		V42254-B1100-B640	1393644-4	B64	right-angle solder leads	every row , every pitch	No	1	No	
	OBSOLETE	V42254-B1100-B641	1393644-5	B64	right-angle solder leads	row a , every pitch	No	1	No	
		V42254-B1100-B645	1393644-6	B64	right angle solder leads	every row , every even pitch	No	1	No	
		V42254-B1100-C480	1393644-9	C48	right-angle solder leads	every row , every pitch	No	1	No	
	OBSOLETE	V42254-B1100-C483	1-1393644-0	C48	right-angle solder leads	row a+c , every pitch	No	1	No	
		V42254-B1100-C910	1-1393644-2	C96	right-angle solder leads	every row , every pitch	No	1	Yes	
		V42254-B1100-C960	1-1393644-6	C96	right-angle solder leads	every row , every pitch	No	1	No	
		V42254-B1100-C963	1-1393644-7	C96	right-angle solder leads	row a+c , every pitch	No	1	No	
	OBSOLETE	V42254-B1100-C965	1-1393644-8	C96	right-angle solder leads	every row , every even pitch	No	1	No	
		V42254-B1100-C968	1-1393644-9	C96	right-angle solder leads	row a+c , every even pitch	No	1	No	
		V42254-B1100-C968H	2-1393644-0	C96	right-angle solder leads	row a+c , every even pitch	No	1	No	3)
		V42254-B1101-B230	3-1393644-2	B20	2,9mm straight solder leads	every row , every pitch	Yes	1	No	
		V42254-B1102-B320	3-1393644-3	B32	4,5mm straight solder leads	every row , every pitch	No	1	No	
		V42254-B1102-B640	3-1393644-4	B64	4,5mm straight solder leads	every row , every pitch	No	1	No	
		V42254-B1102-C960	3-1393644-5	C96	4,5mm straight solder leads	every row , every pitch	No	1	No	
		V42254-B1102-C963	3-1393644-6	C96	4,5mm straight solder leads	row a+c , every pitch	No	1	No	
		V42254-B1135-B640	4-1393644-0	B64	solder lugs	every row , every pitch	No	1	No	
		V42254-B1200-B200	5-1393644-6	B20	right-angle solder leads	every row , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-B310	5-1393644-8	B32	right-angle solder leads	every row , every pitch	No	2	Yes	
		V42254-B1200-B320	5-1393644-9	B32	right-angle solder leads	every row , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-B321	6-1393644-0	B32	right-angle solder leads	row a , every pitch	No	2	No	
		V42254-B1200-B610	6-1393644-3	B64	right-angle solder leads	every row , every pitch	No	2	Yes	
	OBSOLETE	V42254-B1200-B611	6-1393644-4	B64	right-angle solder leads	row a , every pitch	No	2	Yes	
		V42254-B1200-B630	6-1393644-5	B64	right-angle solder leads	every row , every pitch	Yes	2	No	
		V42254-B1200-B640	6-1393644-6	B64	right-angle solder leads	every row , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-B641	6-1393644-7	B64	right-angle solder leads	row a , every pitch	No	2	No	
		V42254-B1200-B645	6-1393644-8	B64	right-angle solder leads	every row , every even pitch	No	2	No	
		V42254-B1200-C300	6-1393644-9	C30	right-angle solder leads	every row , every pitch	No	2	No	
SUPERSEDED BY 6-1393644-9		V42254-B1200-C303	7-1393644-0	C30	right-angle solder leads	row a+c , every pitch	No	2	No	
		V42254-B1200-C310	7-1393644-1	C30	right-angle solder leads	every row , every pitch	No	2	Yes	
SUPERSEDED BY 7-1393644-1		V42254-B1200-C313	7-1393644-2	C30	right-angle solder leads	row a+c , every pitch	No	2	Yes	
		V42254-B1200-C410	7-1393644-4	C48	right-angle solder leads	every row , every pitch	No	2	Yes	
SUPERSEDED BY 5650978-5		V42254-B1200-C413	7-1393644-5	C48	right-angle solder leads	row a+c , every pitch	No	2	Yes	
		V42254-B1200-C430	7-1393644-6	C48	right-angle solder leads	every row , every pitch	Yes	2	No	
	OBSOLETE	V42254-B1200-C433	7-1393644-7	C48	right-angle solder leads	row a+c , every pitch	No	2	No	
		V42254-B1200-C453	7-1393644-9	C48	right-angle solder leads	row a+c , every pitch	Yes	2	Yes	
		V42254-B1200-C480	8-1393644-0	C48	right-angle solder leads	every row , every pitch	No	2	No	
		V42254-B1200-C483	8-1393644-1	C48	right-angle solder leads	row a+c , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-C485	8-1393644-2	C48	right-angle solder leads	every row , every even pitch	No	2	No	
		V42254-B1200-C910	8-1393644-3	C96	right-angle solder leads	every row , every pitch	No	2	Yes	
	OBSOLETE	V42254-B1200-C912	8-1393644-4	C96	right-angle solder leads	row a+b , every pitch	No	2	Yes	
		V42254-B1200-C913	8-1393644-5	C96	right-angle solder leads	row a+c , every pitch	No	2	Yes	
		V42254-B1200-C918	8-1393644-6	C96	right-angle solder leads	row a+c , every even pitch	No	2	Yes	
		V42254-B1200-C930	8-1393644-7	C96	right-angle solder leads	every row , every pitch	Yes	2	No	
	OBSOLETE	V42254-B1200-C933	8-1393644-8	C96	richt-angle solder leads	row a+c , every pitch	Yes	2	No	
	OBSOLETE	V42254-B1200-C938	8-1393644-9	C96	right-angle solder leads	row a+c , every even pitch	Yes	2	No	
		V42254-B1200-C953	9-1393644-0	C96	right-angle solder leads	row a+c , every pitch	Yes	2	Yes	
		V42254-B1200-C960	9-1393644-1	C96	right-angle solder leads	every row , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-C960B	9-1393644-2	C96	right angle solder leads	every row , every pitch	No	2	No	4)
		V42254-B1200-C961	9-1393644-3	C96	right-angle solder leads	row a , every pitch	No	2	No	
		V42254-B1200-C963	9-1393644-4	C96	right-angle solder leads	row a+c , every pitch	No	2	No	
	OBSOLETE	V42254-B1200-C963B	9-1393644-5	C96	right-angle solder leads	row a+c , every pitch	No	2	No	4)
		V42254-B1200-C965	9-1393644-6	C96	right-angle solder leads	every row , every even pitch	No	2	No	
		V42254-B1200-C968	9-1393644-7	C96	right-angle solder leads	row a+c , every even pitch	No	2	No	
	OBSOLETE	V42254-B1201-B320	2-1393645-5	B32	2,9mm straight solder leads	every row , every pitch	No	2	No	
	OBSOLETE	V42254-B1201-B640	1392009-8	B64	2,9mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1201-C300	2-1393645-6	C30	2,9mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1201-C480	2-1393645-7	C48	2,9mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1201-C960	2-1393502-6	C96	2,9mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1201-C963	2-1393502-7	C96	2,9mm straight solder leads	row a+c , every pitch	No	2	No	
		V42254-B1202-B200	2-1393645-9	B20	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-B320	3-1393645-0	B32	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-B640	3-1393645-1	B64	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-C300	1392009-9	C30	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-C480	3-1393645-4	C48	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-C483	3-1393645-5	C48	4,5mm straight solder leads	row a+c , every pitch	No	2	No	
		V42254-B1202-C960	3-1393645-6	C96	4,5mm straight solder leads	every row , every pitch	No	2	No	
		V42254-B1202-C963	3-1393645-7	C96	4,5mm straight solder leads	row a+c , every pitch	No	2	No	
		V42254-B1202-C968	3-1393645-8	C96	4,5mm straight solder leads	row a+c , every even pitch	No	2	No	
	OBSOLETE	V42254-B1235-C480	4-1393645-5	C48	solder lugs	every row , every pitch	No	2	No	
		V42254-B1235-C960	4-1393645-7	C96	solder lugs	every row , every pitch	No	2	No	
		V42254-B1235-C963	4-1393645-8	C96	solder lugs	row a+c , every pitch	No	2	No	
		V42254-B1240-B320	5-1393645-1	B32	13mm straight wire-wrap pins	every row , every pitch	No	2	No	
		V42254-B1240-B640	5-1393645-2	B64	13mm straight wire-wrap pins	every row , every pitch	No	2	No	
		V42254-B1240-C300	5-1393645-3	C30	13mm straight wire-wrap pins	every row , every pitch	No	2	No	
		V42254-B1240-C480	5-1393645-4	C48	13mm straight wire-wrap pins	every row , every pitch	No	2	No	
		V42254-B1240-C960	5-1393645-5	C96	13mm straight wire-wrap pins	every row , every pitch	No	2	No	
		V42254-B1240-C963	5-1393645-7	C96	13mm straight wire-wrap pins	row a+c , every pitch	No	2	No	
		V42254-B1240-C963B	5-1393645-8	C96	13mm straight wire-wrap pins	row a+c , every pitch	No	2	No	4)
SUPERSEDED BY 6-1393644-6		V42254-B1300-B640	4-1393646-5	B64	right-angle solder leads	every row , every pitch	No	3	No	
SUPERSEDED BY 9-1393644-1		V42254-B1300-C960	4-1393646-6	C96	right-angle solder leads	every row , every pitch	No	3	No	
SUPERSEDED BY 9-1393644-4		V42254-B1300-C963	4-1393646-7	C96	right-angle solder leads	row a+c , every pitch	No	3	No	
		V42254-F1200-C480	1-1393647-2	C48	right-angle solder leads	every row , every pitch	No	2	No	2)
		V42254-F1200-C960	1-1393647-3	C96	right-angle solder leads	every row , every pitch	No	2	No	2)
		V42254-F1200-C963	1-1393647-4	C96	right-angle solder leads	row a+c , every pitch	No	2	No	2)

4) According BT 236 level 2.
3) According BT 222 level 1.
2) Connectors have a flux-tight coating.
1) First and last contact of each loaded row is a premating (make first / break last) contact.

Active part numbers.
Contact TE for other configuration availability

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS CORORATION, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

TE Connectivity

LOC GWI DIMENSIONS IN MM

B6	ECR-10-004503	13SEP11	MKO	DATE	10.02.89
B5	ECR-10-002555	01JUN10	MKO	NAME	Cuvelier
B4	SR10-0177-03	18 JUN 03	KV	DEP.	PE Com
B3	SR10-0413-02	16 Sep '02	BC		
B2	SR10-0157-02	13 Mar '02	BC		
B1	SR10-0130-02	28 feb '02	BC	TOLERANCE UNLESS SPECIFIED OTHERWISE	
B	SR10-0198-01	21.05.01	BC		
A	WO 00/7012	20.07.00	VS		
REV.	CHANGE ORDER	DATE	APP.	Customer Drawing Nr. C 1392009-8	

SCALE | WEIGHT
MATERIAL

PART NAME
Pin Assembly Eurocard
Types B, C and short versions

PART NO. V42254-B1***-C***-*-7626

SHT. 2- OF 2

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9