












参考基板レイアウト（マウント面）
P.C.BOARD
PATTERN DIMENSION (REF.)
(MOUNTING AREA)



C	B	A	MATERIAL NO.	CIRCUIT
24.6	23.6	26.7	54684-1203	120
20.6	19.6	22.7	54684-1003	100
18.6	17.6	20.7	54684-0903	90
16.6	15.6	18.7	54684-0803	80
14.6	13.6	16.7	54684-0703	70
12.6	11.6	14.7	54684-0603	60
10.6	9.6	12.7	54684-0503	50
5.4	4.4	7.5	54684-0243	24

MODEL NO. 54684-***3

注記 NOTES:

1. 使用材料 MATERIAL
   ハウジング：液晶ポリマー　ガラス充填 UL94V-0 茶色
   HOUSING:LIQUID CRYSTAL POLYMER
   GLASS FILLED UL94V-0
   COLOR BROWN
   ターミナル：リン青銅（t＝0.15）
   TERMINAL:PHOSPHOR BRONZE(t=0.15)
2. メッキ仕様 PLATING
   金メッキ 0.10 マイクロメートル以上（コンタクト部）
   GOLD 0.10 MICROMETER MINIMUM(CONTACT AREA)
   金メッキ 0.4 マイクロメートル以下（テール部）
   GOLD 0.4 MICROMETER MAXIMUM(TAIL AREA)
   下地メッキ：ニッケルメッキ1.5 マイクロメートル以上
   UNDER PLATING : NICKEL 1.5MICROMETER MINIMUM
   ＊コンタクト部とテール部はニッケルメッキによって分断されている金メッキです。
   DIVIDE INTO PARTS THE GOLD PLATING OF THE CONTACT PART AND THE TAIL PART BY THE NICKEL PLATING.

△3 （全極数／2）＝偶数の場合に適用。
APPLY FOR (CIRCUIT/2)=EVEN.

4. 嵌合相手：55526シリーズ、501017シリーズ。
MATE WITH : 55526 SERIES AND 501017 SERIES.

5. テール平坦度は、0.08MAX.
TAIL COPLANARITY TO BE 0.08MAX.

REVISED
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV D

GENERAL TOLERANCES (UNLESS SPECIFIED)


10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	T.KAIHO 2003/07/15
CHECKED BY / DATE	T.ITO 2003/07/15
APPROVED BY / DATE	T.YAMAGU 2003/07/15
MATERIAL NO.	SEE CHART
TITLE	0.4BB CONN.REC HSGASSY NO BOSS NI BARRIER -LEAD FREE-
	MOLEX INCORPORATED
DOCUMENT NO.	SD-54684-011
SHEET NO.	1 OF 1
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

引き出し方向
PULL OUT
DIRECTION







DETAIL "F"

NOTES

1. 製品詳細寸法については図面 SD-54684-011 を参照下さい。
   RE DETAILED DIMENSION, SEE SD-54684-011
2. 梱包数量：１５００個／リール
   NUMBER OF CONNECTORS : 1500PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH



4. トップテープの剥離強度：0.1N ～ 0.7N(10.2gf ～ 71.4gf)
   （剥離方向は下図参照）
   尚、本規格値は出荷時に適用。（但し、輸送時に剥離が発生しないこと。）
   PEELING OFF FORCE OF TOP TAPE : 0.1N ～0.7N(10.2gf ～ 71.4gf)
   (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG,)
   THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
   PEEL OFF SHOULD NOT BE ALLOWED , DURING TRANSPORTATION.



5. 材料(MATERIAL)
   キャリアテープ(CARRIER TAPE)：ポリプロピレン(POLYPROPYLENE)
   トップテープ(TOPTAPE)： PET , PE , PEF
   リール(REEL)：ポリスチレン（PS）<リサイクル材を含む>
   POLYSTYREN(PS) <RECYCLE MATERIAL CONTAINED>

REVISED				
E	EC NO: J2010-2361	DRWN:MKATO	CHKD:THIRATA	APPR:MSASAO
REV	DESCRIPTION	2010/05/21	2010/05/24	2010/06/09

GENERAL TOLERANCES (UNLESS SPECIFIED)	
10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: ---	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: T.KAIHO	DATE: 2003/07/15	TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-	
CHECKED BY: T.ITO	DATE: 2003/07/15		
APPROVED BY: T.YAMAGU	DATE: 2003/07/15	molex MOLEX INCORPORATED	
MATERIAL NO.: SEE CHART		DOCUMENT NO.: SD-54684-012	SHEET NO.: 1 OF 4

MODEL NO. 54684-***4

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



24mm WIDTH CARRIER TAPE

24	25.5	7.7	54684-0244	24
キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.

MODEL NO. 54684-***4

REVISED
E
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15


TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-


MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-54684-012
SHEET NO.: 2 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

引き出し方向
PULL OUT DIRECTION





32mm幅キャリアテープ
32mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.
32	33.5	20.9	54684-0904	90
		18.9	54684-0804	80
		16.9	54684-0704	70
		14.9	54684-0604	60
		12.9	54684-0504	50

MODEL NO. 54684-***4

REVISED
E
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15
MATERIAL NO.: SEE CHART

TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-

MOLEX INCORPORATED

DOCUMENT NO.: SD-54684-012
SHEET NO.: 3 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



44mm幅キャリアテープ

44mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	B	(A)	MATERIAL NO.	極数 CKT.
44	45.5	26.9	54684-1204	120
		22.9	54684-1004	100

MODEL NO. 54684-***4

REVISED
EC NO: J2010-2361 2010/05/21
DRWN:MKATO 2010/05/24
CH'KD:THIRATA 2010/06/09
APPR:MSASAO
DESCRIPTION
REV E

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: T.KAIHO DATE: 2003/07/15
CHECKED BY: T.ITO DATE: 2003/07/15
APPROVED BY: T.YAMAGU DATE: 2003/07/15
MATERIAL NO.: SEE CHART

TITLE: 0.4BB CON.EMBSTP PKG FOR 54684-***3 -LEAD FREE-

MOLEX INCORPORATED

DOCUMENT NO.: SD-54684-012
SHEET NO.: 4 OF 4

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9