
Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE




5 FIGURE OF INSERTION

HORIZONTALLY ○


DF57-✱S-1.2C

△2 DF57H-✱S-1.2C


DF57-2830SCF




DIAGONAL ×



2 STYLE AND DIMENSION OF BOX



2 STYLE AND DIMENSION OF REEL



DETAIL OF PART No. LABEL

品名コード	CL666-0001-4
品 名	DF57-2830SCF
数 量	40000
仕 様	
LOT No.	
継ぎ目	

検 査

SECTION
Lot No.
SPECIFICATION
QUANTITY
PART No.
CODE No.
INSPECTION

NOTE 1. 1RL:40000 CONTACTS.
2 STYLE OF REEL AND BOX SHOWS IN FIGURE.
3. A MAXIMUM OF 5 REELS ARE PACKED UP IN ONE BOX.
4. PLEASE BE SURE TO CHECK THE FORM OF CRIMPING USING A CABLE. WHEN YOU ADJUST APPLICATOR.
5 AVOID ANGLED INSERTION OF CRIMP CONTACT(DF57-2830SCF) TO MAINTAIN PERFORMANCE RELIABILITY.

NO.	MATERIAL	FINISH , REMARKS
1	PHOSPHOR BRONZE	SURFACE: TIN PLATING 1μmMIN

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	20: 1	△2	1	DIS-H-00000127	MI. SAKIMURA	KI. AKIYAMA	15.02.16

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	09.11.30
CHECED	MN. KENJO	09.11.28
DESIGNED	TS. KUMAZAWA	09.11.28
DRAWN	TS. KUMAZAWA	09.11.28

DRAWING NO. EDC3-322918-00
PART NO. DF57-2830SCF
CODE NO. CL666-0001-4-00 △2 1/1