

This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior concent, & that no right is granted to disclose or to use any information in this document.

REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
A			12/17/07	

D-SUB TECHNICAL DATA

SHELL :	Steel 2.5um (100u") min tin over 1.25um (50u") min nickel
BODY :	Glass filled thermoplastic. Flame retardant to UL94 V-0 Color Black
CONTACTS :	Brass Gold flash over 50u" min nickel on mating area 100u" min tin over 50u" min nickel on solder area
ELECTRICAL :	Voltage rating : 1000 V RMS at 50 Hz Current rating 3A. Insulation resistance >1000 M Ohms Contact resistance 20 mOhms max.
CLIMATIC :	Temperature range -55 °C up to 125°C
MARKING :	Amphenol-...(Series No.) Commercial reference Manufacturing date





Customer drawing

DIM.S / SHELL	A	B	C	D	Pitch
15	30.84	16.92	24.99	19.28	2.29
26	39.24	24.70	33.32	27.51	2.29
44	53.04	38.96	47.04	41.30	2.29
62	69.32	55.42	63.50	57.71	2.41

PRODUCT CODE

L 717 HD X XX P

- L: RoHS Compliance
- 717: tinned shell + dimples for plug
- HD: High density
- Shell Size : E,A,B,C
- Configuration: 15,26,44,62
- Contact type: P: Male

UNLESS OTHERWISE SPECIFIED TOLERANCES

	U.S.	METRIC
.X +/-		0.50
.XX +/-		0.30
.XXX +/-		0.20
FRACTIONS +/-		
ANGLES +/-		2°

FOR MATERIALS AND FINISHES SEE NOTES

REMOVE SHARP EDGES

DIMENSIONS U.S. / METRIC

APPROVAL		DATE
DRAWN	Christine.cui	12/17/07
CHECKED	lik.wang	12/17/07
CHECKED		

DRAWING FILE :

ANGLE OF PROJECTION

Amphenol

TITLE: stamped and formed connector, HD series

SIZE	DRAWING NO.	REV.
A4	C L717HDXXXP	A

SCALE NONE | SHEET 1 OF 1