
This document was generated on 06/03/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 39-00-0181
Status: Active
Overview: Mini-Fit Jr.™
Description: 4.20mm Pitch Mini-Fit® Crimp Terminal, Female, Phosphor Bronze, Gold (Au), 18-24 AWG, Reel



Series image - Reference only

Documents:

Drawing (PDF)
Product Specification PS-5556-001 (PDF)
Product Specification PS-5556-002 (PDF)
Packaging Specification PK-5556-001 (PDF)
Test Summary TS-5556-002 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Crimp Terminals
Series	5556
Application	Power
Crimp Quality Equipment	Yes
Overview	Mini-Fit Jr.™
Packaging Alternative	39-00-0182 (Loose)
Product Name	Mini-Fit®
UPC	800755527933

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Nickel
Net Weight	0.130/g
Packaging Type	Reel
Plating min - Mating	0.762µm
Plating min - Termination	0.762µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.30-3.10mm
Wire Size AWG	18, 20, 22, 24
Wire Size mm²	N/A

Electrical

Current - Maximum per Contact	9A
Voltage - Maximum	600V

Material Info

Old Part Number	5556-PBGSP

Reference - Drawing Numbers

Packaging Specification	PK-5556-001
Product Specification	PS-5556-001, PS-5556-002
Sales Drawing	SD-5556-GSP*
Test Summary	TS-5556-002

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
5556Series

Mates With
5558 Mini-Fit® Crimp Male Terminals. Mini-Fit Jr.™ Header, Dual Row, 5566 , 5569

Use With
5557 Mini-Fit Jr.™ Receptacle Housing, 30067 Mini-Fit® TPA, 42474 Mini-Fit® BMI Panel Mount, 44516 Mini-Fit® BMI Slide and Lock Panel Mount

Application Tooling | **FAQ**

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
FineAdjust™ Applicator for Insulation OD	0639002600

2.50-2.95mm - 18-24 AWG	
FineAdjust™ Applicator for Insulation OD 1.65-2.05mm - 18-24 AWG	0639002900
FineAdjust™ Applicator for Insulation OD 1.90-2.30mm - 18-24 AWG	0639015600
Extraction Tool	0011030044
FineAdjust™ Applicator for Insulation OD 1.40-1.70mm - 18-24 AWG	0639023900
FineAdjust™ Applicator for Insulation OD 2.50-2.95mm Optimized for 18 AWG Only	0639024800
FineAdjust™ Applicator for Insulation OD 2.30-2.60mm - 18-24 AWG	0639024900
T2 Terminator™ for insulation OD 2.50-2.95mm - 18-24 AWG	0639102600
T2 Terminator™ for insulation OD 1.65 – 2.05mm – 18 – 24 AWG	0639102900
T2 Terminator™ for insulation OD 1.90-2.30mm - 18-24 AWG	0639115600
T2 Terminator™ for insulation OD 1.40-1.70mm - 18-24 AWG	0639123900
T2 Terminator™ for insulation OD 2.50-2.95mm optimized for 18 AWG only	0639124800
T2 Terminator™ for insulation OD 2.30-2.60mm - 18-24 AWG	0639124900
Hand Crimp Tool for Male and Female Crimp Terminals, 16-24 AWG Wire	0638190900

Japan

Description	**Product #**
Applicator for M211A Bench Press, 18-24 AWG Wire	0570223000

Side-Feed Applicator	0570223200
For Full-Auto Machine	

This document was generated on 06/03/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION