Distributed by:

JAMECO® ELECTRONICS


www.Jameco.com ✦ 1-800-831-4242


The content and copyrights of the attached material are the property of its owner.


Jameco Part Number 152347

SIGN	DATE	DESCRIPTION	APPROVER


THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!







N=Number of poles



RECOMMENDED PCB LAYOUT

Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Wire guard: Stainless steel
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 15A
- Wire range:
  Solid wire(AWG): 14-22
  Stranded wire(AWG): 14-22
- Torque(Lb-In): 3.5
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.5KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: c UL us

RoHS Compliant

PART NUMBER:

OSTTAXX4163

No. of Poles
02 2 Poles
03 3 Poles
... ...
24 24 Poles

COLOR
0: Black
5: Green
6: Blue (Standard)
8: Grey

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

ON-SHORE TECHNOLOGY, INC.

TITLE	OSTTA - 5.08mm series one interlock, 4.0mm pin					
PART NO.	OSTTAXX4163			DWG NO.	OSTTAXX4163.DWG	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
	Marvin 2006.02.08	Marvin 2006.02.08	Marvin 2006.02.08	SHEET: 01/01	UNIT: mm SCALE: NONE REV.: C	X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°