








参考基板レイアウト（マウント面）
P.C.B. PATTERN DIMENSION.(REFERENCE)
(MOUNTING AREA)

注記 NOTES

1. 使用材料 MATERIAL
   ハウジング：液晶ポリマー ガラス充填 UL94V-0 茶色
   HOUSING:LIQUID CRYSTAL POLYMER, GLASS FILLED, UL94V-0, COLOR BROWN
   ターミナル：リン青銅（t＝0.15）
   TERMINAL:PHOSPHOR BRONZE(t=0.15)
2. メッキ仕様 PLATING
   金メッキ （コンタクト部）
   GOLD PLATING (CONTACT AREA)
   錫メッキ(テール部)
   TIN PLATING (TAIL AREA)
   下地メッキ：ニッケルメッキ
   UNDER PLATING : NICKEL
3. △3 テール部に適用。
   APPLY TO THE TAIL AREA.
4. 嵌合相手：55394 / 503376 シリーズ
   MATE WITH : 55394 / 503376 SERIES.
5. テール平坦度は、0.08 以下
   TAIL COPLANARITY TO BE 0.08MAXIMUM
6. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT

| D | C | B | A | EMBOSSED TAPE | MATERIAL No. | CKT. |
|---|---|---|---|---|---|---|
| 23.0 | 23.1 | 21.6 | 23.6 | 54552-1102 | 54552-1100 | 110 |
| 19.0 | 19.1 | 17.6 | 19.6 | 54552-0902 | 54552-0900 | 90 |
| 9.0 | 9.1 | 7.6 | 9.6 | 54552-0402 | 54552-0400 | 40 |
| 7.8 | 7.9 | 6.4 | 8.4 | 54552-0342 | 54552-0340 | 34 |
| 7.0 | 7.1 | 5.6 | 7.6 | 54552-0302 | 54552-0300 | 30 |
| | | | | ORDER No. オーダー番号 | MODEL No. : 54552-×××0 | |

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA
APPR:NUKITA 2009/03/30
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | |
|---|---|
| 10 UNDER | ±0.2 |
| 10 OVER 30 UNDER | ±0.25 |
| 30 OVER | ±0.3 |
| ANGULAR | ±3 ° |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03


TITLE: 0.4 B/B CONN RA REC HSG ASSY


MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-023
SHEET NO.: 1 OF 1
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION









DETAIL D

NOTES

1. 製品詳細寸法については SD-54552-023 を参照下さい。
   RE DETAILED DIMENSION, SEE SD-54552-023.
2. 梱包数量：１５００個／リール
   NUMBER OF CONNECTORS : 1500PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH




4. トップテープの剥離強度：0.1～1.3N {10～130gf}（剥離方向は下図参照）
   尚、本規格値は出荷時に適用。（但し、輸送時に剥離が発生しないこと。）
   PEELING OFF FORCE OF TOP TAPE : 0.1～1.3N {10～130gf}
   (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG.)
   THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
   PEEL OFF SHOULD NOT BE ALLOWED , DURING TRANSPORTATION.




5. 材料(MATERIAL)
   キャリアテープ(CARRIER TAPE)：ポリプロピレン(POLYPROPYLENE)
   トップテープ(TOPTAPE)：PET , PE , PEF
   リール(REEL)：ポリスチレン（PS） <リサイクル材を含む>
   POLYSTYRENE (PS) <RECYCLE MATERIAL CONTAINED>
6. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT

| MATERIAL NO. | 極数 CIRCUITS |
|---|---|
| 54552-1102 | 110 |
| 54552-0902 | 90 |
| 54552-0402 | 40 |
| 54552-0342 | 34 |
| 54552-0302 | 30 |

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV C


GENERAL TOLERANCES (UNLESS SPECIFIED)

| | |
|---|---|
| 10 UNDER | ±0.2 |
| 10 OVER 30 UNDER | ±0.25 |
| 30 OVER | ±0.3 |
| ANGULAR ±3 ° | |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

| | |
|---|---|
| DIMENSION STYLE | MM ONLY |
| SCALE | --- |
| DESIGN UNITS | METRIC |
| | THIRD ANGLE PROJECTION |
| DRAWN BY | N.AIDA |
| DATE | '05/02/03 |
| CHECKED BY | K.TOYODA |
| DATE | '05/02/03 |
| APPROVED BY | N.UKITA |
| DATE | '05/02/03 |
| MATERIAL NO. | SEE TABLE |
| TITLE | EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY |
| | MOLEX INCORPORATED |
| DOCUMENT NO. | SD-54552-024 |
| SHEET NO. | 1 OF 4 |
| SIZE | A3 |

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION




24mm幅キャリアテープ
24mm WIDTH CARRIER TAPE

| キャリアテープ幅 CARRIER TAPE WIDTH | C | B | (A) | MATERIAL NO. | 極数 CIRCUITS |
|---|---|---|---|---|---|
| 24 | 29.4 | 25.4 | 9.8 | 54552-0402 | 40 |
| | | | 8.6 | 54552-0342 | 34 |
| | | | 7.8 | 54552-0302 | 30 |

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | |
|---|---|
| 10 UNDER | ±0.2 |
| 10 OVER 30 UNDER | ±0.25 |
| 30 OVER | ±0.3 |
| ANGULAR | ±3 ° |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 2 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION




| 32 | 37.4 | 33.4 | 19.8 | 54552-0902 | 90 |
|---|---|---|---|---|---|
| キャリアテープ幅 CARRIER TAPE WIDTH | C | B | (A) | MATERIAL. NO. | 極数 CIRCUIT |

MODEL NO. 54552-×××2

REVISED
EC NO: J2009-2156
DRWN:MTAKASAKI 2009/03/26
CH'KD:THARUYAMA 2009/03/27
APPR:NUKITA 2009/03/30
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | |
|---|---|
| 10 UNDER | ±0.2 |
| 10 OVER 30 UNDER | ±0.25 |
| 30 OVER | ±0.3 |
| ANGULAR | ±3 ° |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 3 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION




| 44 | 49.4 | 45.4 | 23.8 | 54552-1102 | 110 |
|---|---|---|---|---|---|
| キャリアテープ幅 CARRIER TAPE WIDTH | C | B | (A) | MATERIAL NO. | 極数 CIRCUITS |

MODEL NO. 54552-***2

REVISED
EC NO: J2009-2156 2009/03/26
DRWN:MTAKASAKI 2009/03/27
CH'KD:THARUYAMA 2009/03/30
APPR:NUKITA
DESCRIPTION
REV C

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | |
|---|---|
| 10 UNDER | ±0.2 |
| 10 OVER 30 UNDER | ±0.25 |
| 30 OVER | ±0.3 |
| ANGULAR | ±3 ° |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: N.AIDA DATE: '05/02/03
CHECKED BY: K.TOYODA DATE: '05/02/03
APPROVED BY: N.UKITA DATE: '05/02/03

TITLE: EMBSTP PKG FOR 0.4 B/B CONN RA REC HSG ASSY

MOLEX INCORPORATED

MATERIAL NO.: SEE TABLE
DOCUMENT NO.: SD-54552-024
SHEET NO.: 4 OF 4
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

**ООО «НИОКРсистемс» -** это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

## Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709