THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
—	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H2	REVISED PER ECO-11-004587	11MAR11	RK	HMR

NOTES	(13) QC TAB .187 SS FLAT	(12) QC TAB .187 SS FLAT	(11) QC TAB .187 SS 90°	(10) JUMPER	(9) QC TAB DBL SIDE 90° .250	(8) QC TAB DBL SIDE 45° .250	(7) QC TAB DBL SIDE FLAT .250	(6) QC TAB DBL SIDE 90° .187	(5) QC TAB DBL SIDE 45° .187	(4) QC TAB DBL SIDE FLAT .187	(3) QC TAB SGL SIDE 90° .250	(2) QC TAB SGL SIDE 45° .250	(1) QC TAB SGL SIDE FLAT .250	DIM B	DIM A	NO. OF POS.	PART NO.
–	–	–	–	–	–	–	–	–	–	–	–	–	–	180.7	188.2	18	1-1546306-8
–	–	–	–	–	–	–	–	–	–	–	–	–	–	171.2	178.7	17	1-1546306-7
–	–	–	–	–	–	–	–	–	–	–	–	–	–	161.7	169.2	16	1-1546306-6
1 2 3 4 –	–	–	–	–	–	–	–	–	–	–	–	–	–	152.2	159.7	15	6-1546306-2
–	–	–	–	–	–	–	–	–	–	–	–	–	–	152.2	159.7	15	1-1546306-5
–	–	–	–	–	–	–	–	–	–	–	–	–	–	142.7	150.2	14	1-1546306-4
–	–	–	–	–	–	–	–	–	–	–	–	–	–	133.2	140.7	13	1-1546306-3
3 5 –	–	–	–	–	–	–	–	–	–	–	–	–	–	123.7	131.2	12	4-1546306-0
3 4 –	–	–	–	–	–	–	–	–	–	–	–	–	–	123.7	131.2	12	3-1546306-3
–	–	–	–	–	–	–	–	–	–	–	–	–	–	123.7	131.2	12	1-1546306-2
6 –	–	–	11	–	–	–	–	–	–	–	–	–	–	114.2	121.7	11	5-1546306-2
1 3 –	–	–	–	2	–	–	–	–	11	–	–	–	–	114.2	121.7	11	3-1546306-4
3 –	–	–	–	–	–	–	–	–	11	–	–	–	–	114.2	121.7	11	3-1546306-1
–	–	–	–	–	–	–	–	–	–	–	–	–	–	114.2	121.7	11	1-1546306-1
1 –	–	–	–	–	–	–	–	10	3	–	–	–	–	104.7	112.2	10	6-1546306-0
3 6 –	–	–	–	–	–	–	–	–	–	–	–	–	–	104.7	112.2	10	5-1546306-8
–	–	–	–	–	–	–	–	–	–	–	–	–	–	104.7	112.2	10	1-1546306-0
2 3 7 –	4	9	–	–	–	–	–	–	–	–	–	–	–	95.2	102.7	9	6-1546306-3
3 6 –	–	–	–	–	–	–	–	–	–	–	–	–	–	95.2	102.7	9	5-1546306-6
–	–	–	–	–	–	–	–	–	–	–	–	–	–	95.2	102.7	9	1546306-9
–	–	–	–	–	–	–	–	8	–	–	–	–	–	85.7	93.2	8	5-1546306-9
3 5 –	–	–	–	–	–	–	–	–	–	–	–	–	–	85.7	93.2	8	3-1546306-9
–	–	–	–	–	–	–	–	–	–	–	–	–	–	85.7	93.2	8	1546306-8
3 6 –	–	–	–	–	–	–	–	–	–	–	–	–	–	76.2	83.7	7	5-1546306-5
1 –	–	–	–	1	–	–	7	–	–	–	–	–	–	76.2	83.7	7	5-1546306-0
–	–	–	–	–	–	–	–	–	–	–	7	7	7	76.2	83.7	7	4-1546306-5
3 –	–	–	–	–	–	–	–	–	7	–	–	–	–	76.2	83.7	7	3-1546306-7
–	–	–	–	–	–	–	–	–	–	–	–	–	–	76.2	83.7	7	1546306-7
3 6 –	–	–	–	–	–	–	–	–	–	–	–	–	–	66.7	74.2	6	5-1546306-4
1 3 –	–	–	–	–	–	1	6	–	–	–	–	–	–	66.7	74.2	6	4-1546306-9
–	–	–	–	–	6	–	–	–	–	–	–	–	–	66.7	74.2	6	4-1546306-8
–	–	–	–	–	–	–	–	–	–	–	6	6	6	66.7	74.2	6	4-1546306-4
3 –	–	–	–	–	–	–	–	–	6	–	–	–	–	66.7	74.2	6	3-1546306-6
–	–	–	–	–	–	–	–	–	–	–	–	–	–	66.7	74.2	6	1546306-6
6 –	–	–	–	–	–	–	–	5	–	–	–	–	–	57.2	64.7	5	5-1546306-7
6 –	5	5	–	–	–	–	–	–	–	–	–	–	–	57.2	64.7	5	5-1546306-3
1 3 SCREW ON ONE SIDE	–	–	–	–	–	–	–	–	–	–	–	–	–	57.2	64.7	5	4-1546306-7
–	–	–	–	–	–	–	–	–	–	–	5	5	5	57.2	64.7	5	4-1546306-3
3 –	–	–	–	–	–	–	–	–	5	–	–	–	–	57.2	64.7	5	3-1546306-5
–	–	–	–	–	–	–	–	–	–	–	–	–	–	57.2	64.7	5	1546306-5
–	–	–	–	–	–	–	–	–	–	–	4	4	4	47.7	55.2	4	4-1546306-2
3 5 –	–	–	–	–	–	–	–	–	–	–	–	–	–	47.7	55.2	4	3-1546306-8
–	–	–	–	–	–	–	–	–	–	–	–	–	–	47.7	55.2	4	1546306-4
–	3	3	–	–	–	–	–	–	–	–	–	–	–	38.2	45.7	3	6-1546306-1
–	–	–	–	–	–	–	–	–	–	–	–	–	–	38.2	45.7	3	5-1546306-1
–	–	–	–	–	–	–	–	–	–	–	–	–	–	38.2	45.7	3	1546306-3
3 –	–	–	–	–	–	–	–	2	2	2	–	–	–	28.7	36.2	2	4-1546306-6
–	–	–	–	–	2	2	2	–	–	–	–	–	–	28.7	36.2	2	4-1546306-1
–	–	–	–	–	–	–	–	–	–	–	–	–	–	28.7	36.2	2	1546306-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± 0.3
2 PLC ± 0.25
3 PLC ± –
4 PLC ± –
ANGLES ± 2°

MATERIAL –
FINISH –

DWN S SCHLEGEL 20AUG2002
CHK C RICHARD 8/20/02
APVD C RICHARD 8/20/02
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME 9.50MM (.374) DBL ROW BARRIER STRIP W/O WASHER

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1546306	—

CUSTOMER DRAWING | SCALE NTS | SHEET 1 OF 3 | REV H2

1546306

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
—	—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

PHYSICAL PROPERTIES:
HOUSING MATERIAL: THERMOPLASTIC, PC
FLAMMABILITY: UL94V–0 COLOR: BLACK
MAX BOW/WARP: .0056 IN/IN.

TERMINAL:
TERMINALS: BRASS, TIN PLATED
SCREWS: 6–32, STEEL, NICKEL PLATED

MECHANICAL:
PITCH (TERMINAL SPACING): 9.50mm(.374")
WIRE RANGE: 12–22 AWG
RECOMMENDED TIGHTENING TORQUE: 12IN–LBS MAX.

ELECTRICAL PROPERTIES:
MAXIMUM CURRENT: 20A
OPERATING VOLTAGE: 300V

ENVIRONMENTAL PROPERTIES:
OPERATING TEMP RANGE: –40°C TO +120°C.

1. SEE FIGURE.
2. MARKED WITH WHITE INK.
3. PRELIMINARY PART NUMBER.
4. SCREWS AND TERMINALS ARE NICKEL PLATED BRASS.
5. STAINLESS STEEL SCREWS.
6. SCREWS ARE NICKEL PLATED BRASS.
7. WIRE CLAMP SCREWS TO BE USED ONLY ON SIDE OPPOSITE QC TABS.
8. TE CONNECTIVITY LOGO LOCATED APPROXIMATE AREA SHOWN.

-- SELECT LOAD CHART --

(12) QC TAB .187 SS FLAT	(11) QC TAB .187 SS 90°	(10) JUMPER	(9) QC TAB DBL SIDE 90° .250	(8) QC TAB DBL SIDE 45° .250	(7) QC TAB DBL SIDE FLAT .250	(6) QC TAB DBL SIDE 90° .187	(5) QC TAB DBL SIDE 45° .187	(4) QC TAB DBL SIDE FLAT .187	(3) QC TAB SGL SIDE 90° .250	(2) QC TAB SGL SIDE 45° .250	(1) QC TAB SGL SIDE FLAT .250	NO. OF POS.	PART NUMBER
POSITIONS LOADED													
–	–	4–5,5–6	–	–	–	–	ALL	–	–	–	–	11	3–1546306–4
–	–	–	–	–	–	ALL	1–3	–	–	–	–	10	6–1546306–0
–	–	1,2	–	–	ALL	–	–	–	–	–	–	7	5–1546306–0
–	–	–	–	1	ALL	–	–	–	–	–	–	6	4–1546306–9

NOTES	(13) QC TAB .187 SS FLAT	(12) QC TAB .187 SS FLAT	(11) QC TAB .187 SS 90°	(10) JUMPER	(9) QC TAB DBL SIDE 90° .250	(8) QC TAB DBL SIDE 45° .250	(7) QC TAB DBL SIDE FLAT .250	(6) QC TAB DBL SIDE 90° .187	(5) QC TAB DBL SIDE 45° .187	(4) QC TAB DBL SIDE FLAT .187	(3) QC TAB SGL SIDE 90° .250	(2) QC TAB SGL SIDE 45° .250	(1) QC TAB SGL SIDE FLAT .250	DIM B	DIM A	NO. OF POS.	PART NO.
–	–	–	–	–	–	–	–	–	–	–	–	–	–	294.7	302.2	30	3–1546306–0
–	–	–	–	–	–	–	–	–	–	–	–	–	–	285.2	292.7	29	2–1546306–9
–	–	–	–	–	–	–	–	–	–	–	–	–	–	275.7	283.2	28	2–1546306–8
–	–	–	–	–	–	–	–	–	–	–	–	–	–	266.2	273.7	27	2–1546306–7
–	–	–	–	–	–	–	–	–	–	–	–	–	–	256.7	264.2	26	2–1546306–6
–	–	–	–	–	–	–	–	–	–	–	–	–	–	247.2	254.7	25	2–1546306–5
–	–	–	–	–	–	–	–	–	–	–	–	–	–	237.7	245.2	24	2–1546306–4
–	–	–	–	–	–	–	–	–	–	–	–	–	–	228.2	235.7	23	2–1546306–3
–	–	–	–	–	–	–	–	–	–	–	–	–	–	218.7	226.2	22	2–1546306–2
–	–	–	–	–	–	–	–	–	–	–	–	–	–	209.2	216.7	21	2–1546306–1
1 2 SPL MARKING	–	–	–	–	–	–	–	–	–	–	–	–	–	199.7	207.2	20	3–1546306–2
–	–	–	–	–	–	–	–	–	–	–	–	–	–	199.7	207.2	20	2–1546306–0
–	–	–	–	–	–	–	–	–	–	–	–	–	–	190.2	197.7	19	1–1546306–9

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± 0.3
2 PLC ± 0.25
3 PLC ± –
4 PLC ± –
ANGLES ± 2°

MATERIAL –
FINISH –

DWN S SCHLEGEL 20AUG2002
CHK C RICHARD 8/20/02
APVD C RICHARD 8/20/02
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME 9.50MM (.374) DBL ROW BARRIER STRIP W/O WASHER —

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1546306	—


CUSTOMER DRAWING | SCALE NTS | SHEET 2 OF 3 | REV H2


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.


LOC	DIST
—	—


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—












6–1546306–3




3–1546306–2




4–1546306–9







5–1546306–0




6–1546306–2



3–1546306–4



6–1546306–0



4–1546306–7

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S SCHLEGEL 20AUG2002	TE Connectivity	
DIMENSIONS: MM	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – ; 1 PLC ± 0.3 ; 2 PLC ± 0.25 ; 3 PLC ± – ; 4 PLC ± – ; ANGLES ± 2°	CHK C RICHARD 8/20/02	NAME 9.50MM (.374) DBL ROW BARRIER STRIP W/O WASHER –	
		APVD C RICHARD 8/20/02		
		PRODUCT SPEC —		
		APPLICATION SPEC —	SIZE A2	CAGE CODE 00779
MATERIAL –	FINISH –	WEIGHT –	DRAWING NO C-1546306	RESTRICTED TO —
		CUSTOMER DRAWING	SCALE NTS	SHEET 3 OF 3 REV H2

1546306

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709