
molex
one company > a world of innovation

This document was generated on 04/30/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 39-00-0077
Status: Active
Overview: Mini-Fit Jr.™
Description: 4.20mm Pitch Mini-Fit® Crimp Terminal, Female, with Tin (Sn) over Copper (Cu) Plated Brass, 16 AWG, Reel



Series image - Reference only

Documents:

Drawing (PDF)
Product Specification PS-5556-001 (PDF)
Product Specification PS-5556-002 (PDF)
Packaging Specification PK-5556-001 (PDF)
Test Summary TS-5556-002 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Crimp Terminals
Series	5556
Application	Power
Crimp Quality Equipment	Yes
Overview	Mini-Fit Jr.™
Product Name	Mini-Fit®

Physical

Durability (mating cycles max)	30
Gender	Receptacle
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Packaging Type	Reel
Plating min - Mating	0.889µm
Plating min - Termination	0.889µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.80-3.10mm
Wire Size AWG	16
Wire Size mm²	N/A

Electrical

Current - Maximum per Contact	9A
Voltage - Maximum	600V

Material Info

Old Part Number	5556T3

Reference - Drawing Numbers

Packaging Specification	PK-5556-001
Product Specification	PS-5556-001, PS-5556-002, RPS-30067-001, RPS-30067-002, RPS-30067-003, RPS-5557-002
Sales Drawing	SD-5556****
Test Summary	TS-5556-002

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
5556Series

Mates With
5558 Mini-Fit® Crimp Male Terminals. Mini-Fit Jr.™ Header, Dual Row, 5566 , 5569

Use With
5557 Mini-Fit Jr.™ Receptacle Housing, 30067 Mini-Fit® TPA, 42474 Mini-Fit® BMI Panel Mount, 5559 Mini-Fit Jr.™ Plug Housing, Dual Row

Application Tooling | **FAQ**

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
FineAdjust™ Applicator for insulation OD 2.60-3.15mm	0639002800

optimized for 16 AWG only	
Hand Crimp Tool for Male and Female Crimp Terminals, 16-24 AWG Wire	0638190900
FineAdjust™ Applicator for insulation OD 1.80-2.20mm optimized for 16 AWG only	0639015300
FineAdjust™ Applicator for insulation OD 2.20-2.45mm optimized for 16 AWG only	0639003000
T2 Terminator™ for insulation OD 2.60-3.15mm optimized for 16 AWG only	0639102800
T2 Terminator™ for insulation OD 2.20-2.45mm optimized for 16 AWG only	0639103000
Extraction Tool	0011030044

Japan

Description	**Product #**
Applicator for M211A Bench Press, 18-24 AWG Wire	0570223000
Hand Extraction Tool	0570316000
Side-Feed Applicator For Full-Auto Machine	0570223200