







Specifications:
1. Insulation Resistance: 100MOhms min. (initial)
2. Contact Resistance (initial): 30mOhm max at 100mA(max) 1KHz.
3. Dielectric Withstand Voltage: AC 500V, 60Hz for 1 minute.
4. Insertion Force: 3Kgs max. Extraction Force: 0.08Kgs min.
5. Humidity Test: 40±2. 90~95%, 48 hours.


Custom Part Numbers:
1. The last part number in the "Color Index" is a custom part template.
2. Match color number from "Color Chart" to the desired "Input" on the "Color Index."








Color Chart
1 = Black
2 = Red
3 = White
4 = Yellow
5 = Blue
6 = Green

Example: (Black, Red, White)
RCJ-32X1 X2 X3 = RCJ-32123



Color Index			
Part No.	Housing X_1	Housing X_2	Housing X_3
RCJ-32234	Red	White	Yellow
RCJ-32265	Red	Green	Blue
RCJ-32X1 X2 X3	Color X_1	Color X_2	Color X_3

Schematic		
		
L	C	R

No.	Description	Material	Qty	Finish
6	Housing X_3	PBT	1	See Color Index
5	Housing X_2	PBT	1	See Color Index
4	Housing X_1	PBT	1	See Color Index
3	Metal Plate	0.2t Iron	1	Nickel Plated
2	Pin	0.6t Brass	1	Tin Plated
1	Earth Terminal	0.4t Brass	1	Nickel Plated

CUI INC
9615 SW Allen, Suite 103
Beaverton, OR 97005
Phone: (503) 643-4899
800-275-4899
Fax: (503) 372-1266
Website: www.cui.com

TITLE: RCA Jack, 3 Port, Right Angle, PCB Mount, Horiz.

PART NO.: RCJ-32XXX

UNITS: Millimeters

DRAWN BY: Todd R. White

APPROVED BY:

SCALE: 1.5x

PC FILE NAME: rcj-32xxx.dwg

COPYRIGHT 2001 BY CUI INC.