












注記 NOTES:

1. 使用材料 MATERIAL
   ウエハー：液晶ポリマー（ＬＣＰ） ガラス充填 ＵＬ９４Ｖ－０（黒）
   WAFER: LIQUID CRYSTAL POLYMER(GLASS FILLED) UL94V-0 (COLOR:BLACK)
   ピン：黄銅（ｔ＝０．１２）
   PIN: BRASS (t=0.12)
   金具：リン青銅（ｔ＝０．２）
   FITTING NAIL: PHOSPHOR BRONZE (t=0.2)
2. メッキ仕様 PLATING
   ピン PIN
   金メッキ 0.2 マイクロメートル以上（コンタクト部）
   GOLD 0.2MICROMETER MINIMUM (CONTACT AREA)
   金メッキ 0.4 マイクロメートル以下（テール部）
   GOLD 0.4MICROMETER MAXIMUM (TAIL AREA)
   下地メッキ：ニッケルメッキ 1.5 マイクロメートル以上
   UNDER PLATING : NICKEL 1.5MICROMETER MINIMUM
   金具 FITTING NAIL
   錫メッキ 1.0 マイクロメートル以上
   TIN PLATING 1.0MICROMETER MINIMUM
   下地メッキ：ニッケルメッキ 1.0 マイクロメートル以上
   UNDER PLATING : NICKEL 1.0MICROMETER MINIMUM

△3 （全極数／２）＝偶数の場合に適用。
APPLY FOR (CIRCUIT/2)=EVEN.

4. 嵌合相手：５１３３８シリーズ
   MATE WITH : 51338 SERIES.
5. テール平坦度は、０．０８以下
   テール及び金具の平坦度は、０．１以下
   TAIL COPLANARITY TO BE 0.08MAXIMUM
   TAIL AND FITTING NAIL COPLANARITY TO BE 0.1 MAXIMUM
6. 本製品は ５５９０９－＊＊＊３ の鉛フリー品である。
   THIS PRODUCT IS LEAD FREE OF 55909-***3



SECT.V-V

21.2	19.6	22.0	55909-1074	100
19.2	17.6	20.0	55909-0974	90
17.2	15.6	18.0	55909-0874	80
15.2	13.6	16.0	55909-0774	70
13.2	11.6	14.0	55909-0674	60
11.2	9.6	12.0	55909-0574	50
9.2	7.6	10.0	55909-0474	40
8.0	6.4	8.8	55909-3474	34
7.2	5.6	8.0	55909-0374	30
6.4	4.8	7.2	55909-2674	26
6.0	4.4	6.8	55909-2474	24
5.6	4.0	6.4	55909-2274	22
5.2	3.6	6.0	55909-0274	20
4.4	2.8	5.2	55909-1674	16
3.6	2.0	4.4	55909-9974	12
C	B	A	EMBOSSED TAPE PKG. ORDER No. オーダー番号	CKT.
CONNECTOR SERIES NO.			55909-**73	

REVISED
EC NO: J2013-0254 2012/08/30
DRWN:KTOYODA 2012/08/30
CH'KD:TASAKAWA 2012/08/31
APPR:TASAKAWA
DESCRIPTION
REV G

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±1/2 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: HSHIMABUKURO DATE: 2004/02/20
CHECKED BY: K.TOJO DATE: 2004/02/20
APPROVED BY: M.SASAO DATE: 2004/02/20
MATERIAL NO.: SEE CHART

TITLE: 0.4 B-TO-B CONN. PLUG ASSY (HGT=1.5) WITH NAIL -LEAD FREE-


molex

DOCUMENT NO.: SD-55909-003
SHEET NO.: 1 OF 2
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



嵌合断面図（参考）
MATED DRAWING (REFERENCE)



参考基板レイアウト（マウント面）
P.C.BOARD PATTERN DIMENSION.
(REFERENCE)
(MOUNTING AREA)

SEE SHEET 1 OF 2
EC NO: J2013-0254 2012/08/30
DRWN:KTOYODA 2012/08/30
CH'KD:TASAKAWA 2012/08/31
APPR:TASAKAWA
DESCRIPTION
G
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	HSHIMABUKURO 2004/02/20
CHECKED BY / DATE	K.TOJO 2004/02/20
APPROVED BY / DATE	M.SASAO 2004/02/20
MATERIAL NO.	SEE SHEET 1
SIZE	A3


55909-**73 MODEL NO.


TITLE
0.4 B-TO-B CONN. PLUG ASSY (HGT=1.5) WITH NAIL -LEAD FREE-

molex

DOCUMENT NO. SD-55909-003
SHEET NO. 2 OF 2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION





NOTES

1. 製品詳細寸法については製品単体図面を参照下さい。
   RE DETAILED DIMENSION, SEE PRODUCT DRAWING.
2. 梱包数量：２５００個／リール
   NUMBER OF CONNECTORS ：2500PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH
4. 材料 MATERIAL
   キャリアテープ（CARRIER TAPE）：ポリプロピレン（POLYPROPYLENE）
   トップテープ（TOPTAPE）： PET ，PE ，PEF
   リール（REEL）： ポリスチレン（ＰＳ） <リサイクル材を含む>
   POLYSTYRENE (PS) <RECYCLE MATERIAL CONTAINED>
5. ELV 及び RoHS 適合品.
   ELV AND RoHS COMPLIANT.

REVISED	EC NO:	DRWN:	CH'KD:	APPR:	DESCRIPTION	REV
	J2010-2356	TOSHIMA 2010/06/21	KTOYODA 2010/07/20	MSASAO 2010/07/21		J


GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CONNECTOR SERIES No.	55909-**73
DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	H.SHIMAB 2004/02/20
CHECKED BY / DATE	K.TOJO 2004/02/20
APPROVED BY / DATE	M.SASAO 2004/02/20
TITLE	0.4 B-TO-B CONN PLUG ASSY(HGT=1.5) EMBSTP PKG
	MOLEX INCORPORATED
MATERIAL NO.	SEE CHART
DOCUMENT NO.	SD-55909-004
SHEET NO.	1 OF 5
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



SECT. Y-Y



SECT. X-X

注記)製品がポケット内に問題なく収まること。
NOTE. Pocket should contain product smoothly.

キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	CKT
24	29.4	25.4	14.16	55909-0674	60
			12.16	55909-0574	50
			10.16	55909-0474	40
			8.96	55909-3474	34
			8.16	55909-0374	30
			7.36	55909-2674	26
			6.96	55909-2474	24
			6.56	55909-2274	22
			6.16	55909-0274	20

CONNECTOR SERIES No. 55909-**73

REVISED
EC NO: J2010-2356 2010/06/21
DRWN:TOSHIMA 2010/07/20
CH'KD:KTOYODA
APPR:MSASAO 2010/07/21
DESCRIPTION
REV J

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION


DRAWN BY: H.SHIMAB DATE: 2004/02/20
CHECKED BY: K.TOJO DATE: 2004/02/20
APPROVED BY: M.SASAO DATE: 2004/02/20

TITLE: 0.4 B-TO-B CONN PLUG ASSY(HGT=1.5) EMBSTP PKG

MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-55909-004
SHEET NO.: 2 OF 5
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



注記)製品がポケット内に問題なく収まること。
NOTE. Pocket should contain product smoothly.

キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	極数 CKT.
32	37.4	33.4	19.16	55909-0974	90
			18.16	55909-0874	80
			16.16	55909-0774	70

CONNECTOR SERIES No. 55909-**73

32mm幅キャリアテープ
32mm WIDTH CARRIER TAPE

REVISED
EC NO: J2010-2356 2010/06/21
DRWN:TOSHIMA 2010/07/20
CH'KD:KTOYODA
APPR:MSASAO 2010/07/21
DESCRIPTION
REV J

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: H.SHIMAB DATE: 2004/02/20
CHECKED BY: K.TOJO DATE: 2004/02/20
APPROVED BY: M.SASAO DATE: 2004/02/20
MATERIAL NO.: SEE CHART


TITLE: 0.4 B-TO-B CONN PLUG ASSY(HGT=1.5) EMBSTP PKG

MOLEX INCORPORATED

DOCUMENT NO.: SD-55909-004
SHEET NO.: 3 OF 5

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



44mm幅キャリアテープ

44mm WIDTH CARRIER TAPE

注記)製品がポケット内に問題なく収まること。
NOTE. Pocket should contain product smoothly.

44	49.4	45.4	22.16	55909-1074	100
キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	極数 CKT.

CONNECTOR SERIES No. 55909-**73

REVISED
EC NO: J2010-2356 2010/06/21
DRWN:TOSHIMA 2010/07/20
CH'KD:KTOYODA
APPR:MSASAO 2010/07/21
DESCRIPTION
REV J


GENERAL TOLERANCES (UNLESS SPECIFIED)


10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	---
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	H.SHIMAB 2004/02/20
CHECKED BY / DATE	K.TOJO 2004/02/20
APPROVED BY / DATE	M.SASAO 2004/02/20
MATERIAL NO.	SEE CHART
TITLE	0.4 B-TO-B CONN PLUG ASSY(HGT=1.5) EMBSTP PKG
	MOLEX INCORPORATED
DOCUMENT NO.	SD-55909-004
SHEET NO.	4 OF 5
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION





注記)製品がポケット内に問題なく収まること.
NOTE. Pocket should contain product smoothly.

24	29.4	25.4	5.36	55909-1674	16
			4.56	55909-9974	12
キャリアテープ幅 CARRIER TAPE WIDTH	C	B	(A)	MATERIAL NO.	CKT

CONNECTOR SERIES No. 55909-**73

REVISED
EC NO: J2010-2356 2010/06/21
DRWN:TOSHIMA 2010/07/20
CH'KD:KTOYODA
APPR:MSASAO 2010/07/21
DESCRIPTION
REV
J

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: H.SHIMAB DATE: 2004/02/20
CHECKED BY: K.TOJO DATE: 2004/02/20
APPROVED BY: M.SASAO DATE: 2004/02/20

TITLE: 0.4 B-TO-B CONN PLUG ASSY(HGT=1.5) EMBSTP PKG

MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-55909-004
SHEET NO.: 5 OF 5
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331