


DESCRIPTION: R/A 0.590 - MALE D-SUB - ECONOMY







RECOMMENDED PCB LAYOUT

SCALE = 2 : 1

No. OF PINS	DIMENSIONS		
	A	B	C
9	1.213	0.984	0.666
	30.81	24.99	16.92
15	1.541	1.312	0.994
	39.14	33.32	25.25
25	2.088	1.852	1.534
	53.04	47.04	38.96
37	2.729	2.500	2.181
	69.32	63.50	55.42

MATERIALS:


SHELL: SPCC, NICKEL PLATED
INSULATOR: BLACK PA9T NYLON, UL 94V-O
CONTACTS: BRASS, GOLD PLATED
RIVET: COPPER ALLOY, NICKEL PLATED
SCREWLOCK: ZINC ALLOY, NICKEL PLATED
BOARDLOCK: SPCC, TIN PLATED

ELECTRICAL:

CURRENT RATING: 5 AMPS
INSULATOR RESISTANCE: 1,000 MEGOHMS Min.
DIELECTRIC WITHSTANDING: 1,000VAC RMS
TEMPERATURE: -55° C to +105° C

183-YYY-1 1 3 R YY 1

SERIES
POSITIONS
009
015
025
037
GENDER
1 = MALE
TERMINATION
1 = DIP SOLDER
SHELL PLATING
3 = NICKEL PLATED
RoHS COMPLIANT
HARDWARE OPTIONS
SEE SHEET 2
PLATING OPTIONS
1 = GOLD FLASH



BOTTOM VIEW

RoHS COMPLIANT









DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: PAM JENKINS	DATE: 4-28-05
CHECKED:	DATE:
SCALE: 1 : 1	SHEET 1 OF 2
REV 9	
DWG NO. 183-YYY-113RYY1	

DESCRIPTION: **R / A HARDWARE OPTIONS**

	 METAL SHELL WITH INSIDE GROUND STRAPS	 METAL SHELL	 METAL SHELL FORK BOARD LOCKS	 METAL SHELL FORK BOARD LOCKS
 0.120" DIA. HOLE	16	N/A	N/A	N/A
 4-40 FLUSH INSERT	17	45	57 BOARD LOCKS IN REAR HOLE (0.590")	53 BOARD LOCKS IN FRONT HOLE (0.590")
 4-40 HEX STANDOFF FEMALE SCREWLOCK	18	48	54 BOARD LOCKS IN REAR HOLE	56 BOARD LOCKS IN FRONT HOLE
 4-40 ROUND STANDOFF FEMALE SCREWLOCK	N/A	N/A	N/A	N/A

DO NOT SCALE FROM DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: WAYNE ROBBINS	DATE: 8-23-98
CHECKED:	DATE:
SCALE:	SHEET 2 OF 2 / REV 9
DWG NO. 183-YYY-113RYY1	

NorComp

RoHS COMPLIANT

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331